

Douglas County Surveyor's Record of
Government Corners Renewed

T. 20 S. T. S. R. 11 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

39

Sec. Cor. to Secs. 32 & 33, T20-11W. & Secs. 5 & 4, T21-11W.
Found - 58" Old Fir Stump N.75°E. 28.4 ft., cut open & find good
scribing "S" & "11W".

No trace of Corner Tree or any other Bearing Trees. #109

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964
T20S S 32 | S 33
T21S S 5 | S 4

New BT's: 7" Hemlock S.83°E. 12.7 ft. Mkd: T21S R11W S4 CS BT.
16" Hemlock S.85°W. 30.8 ft. Mkd: T21S R11W S5 CS BT.
18" D.Fir N.58°W. 30.3 ft. Mkd: T20S R11W S32 CS BT.
11" Hemlock N.62°E. 20.3 ft. Mkd: T20S R11W S33 CS BT.

Note - Corner is approx. 250 ft. south of centerline of new logging road.

Milo E. Godfrey, Deputy and Crew
September 1964
C. S. File No. 53/66

1/4 Corner to Section 35, T20-11W. & Sec. 2, T21-11W. #125 40
Found - 3/4" I. Pipe, See Ren. # 2.

52" Red Cedar S.10°W. 12.0 ft., prev. opened through rotten
wood on south side, good reverse scribing visible on
overgrowth of old face "1/4".

Fir Stump S.82°W. 11.2 ft., cut off below markings.
Eppstein's other BT destroyed by road construction.

New BT's: 23" Red Cedar N.58°E. 34.4 ft. Mkd: 1/4 S35 CS BT.
52" Red Cedar S.10°W. 12.0 ft. Mkd: 1/4 S 2 CS BT. (Orig. BT)

Note - Corner is on top edge of cut bank on E. side of Smith River
Road.

FD. OK
5/12/80
E. ALVARADO
C.S. 61/6

South 1/4 Corner to Section 19. 41

I find an old Spruce Bearing Tree, now dead and windfell.
Locate the corner from the Spruce S. 34° W. 16 links and #219.
Drive a 2" x 2.5 ft. aluminum Pipe 2 ft. into the ground, from which:
44" Fir bears N. 53° W. 44.0 ft. scribed S 1/4 BT.

Ronald L. Durham
For Menasha Corp.
March 1965
C. S. File No. 51/311

Section Corner to Sections 19 - 20 - 29 - 30. 42
Drive a 2" x 2.5 ft. aluminum Pipe 2 ft. into the ground,
from which:

35" Fir bears S.51°E. 13.2 ft., Orig. BT., now a stump with a
face and an aluminum tag.

24" Fir bears S.55°W. 4.0 ft., Orig. BT., now a stump with
visible scribe.

New BT: 44" Fir bears N.84°W. 20.6 ft. scribed S19 BT. 61
(BT has a forest service Tag & a new BLM tag.)

Closing Corner to Sec. 1, T20-11W. & Sec. 6, T20-10W. 43
Set - Iron Pipe with Brass Cap Mkd: RS 239 C.C. Sec. 1, T20-11W
Sec. 6, T20-10W

Scribed New BT's: 14" Fir S. 46° E. 34.5 ft.
30" Fir S. 24° W. 65.7 ft.

Wilford N.
Haines
Map File
M 31 - 6

SEE GOVT NOTES Vol 91
Pg. 14, 296 FOR BLM CLOSING CORNER

November 1965

1/4 Corner to Section 25 and 36. #155 44
Found - Orig. 36", now 48" Cedar, S. 87° W. 15.8 ft., prev. #155
opened & shows "1/4 S BT". Prev. opened & shows scribe with
approx. 70-75 years of overgrowth. Alive with top broken out.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966
T 20 S R 11 W
S 25
S 36

New BT's: 8" Hemlock N. 69 1/2° W. 19.9 ft. mkd. 1/4 S25 CS BT.
18" R. Cedar S. 61° W. 31.6 ft. mkd. 1/4 S36 CS BT.

Note - This corner lies on top of small bluff approx. 35 ft. high on
N.E. slope 125' west of creek, course S. E.

Vernon "Ray" Tracy
Frank Jones & J. Heritage
Sept. 12, 1966
C. S. File No. 53/66