

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 20 S. T. S. R. 11 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21081

1/4 Corner to Sections 26 and 35.

Found - 1 1/2" Iron Pipe, See Ren. #8.

8", now 9" Maple S. 38° W. 96.0 ft., scribe visible.

14", now 15" Maple N. 69° E. 76.0 ft., scribe visible on rotten face.

As this corner is in a good area for use, I set Brass Cap alongside I.P.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 20 S R 11 W

(Set Steel Fence Post Office 1/4 S 26  
Alongside) 1969 S 35

Rebzd. & Rescrbd: 15" Maple N. 69° E. 76.0 ft. scribed "1/4 S26 CS BT".

9/18/69

73

Section Corner to Sections 29 - 30 - 31 - 32.

Found - No trace of County Brass Cap set in 1969, See Ren. #60.

Brass Cap at Corner mkd. by Crowe, LS 845, See Ren. #63.

48" D. Fir, now stump, S. 65° W. 33.0 ft.

46" D. Fir, now stump, S. 73° E. 37.1 ft., pitched over, scribe vis.

38" D. Fir, now stump, N. 83° E. 36.4 ft., pitched over, scribe vis.

Set - Steel Fence Post alongside Brass Cap.

No trees available to scribe as everthing has been logged.

Tagged all old Bearing Tree Stumps. - It is not practical to set I. Rods as you would probably never find them.

9/24/69

Section Corner common to Sections 13 and 24, T20-12W.

74

Corner marked by a 1 1/2" iron pipe at the top of a bank East of Slonecker's house, and witnessed as follows:

11" Spruce, S. 17° 10' W., 48.10 ft.

14" Holly, S. 22° 30' W., 44.60 ft.

12" Apple, N. 27° 15' W. 35.50 ft.

Closing Corner Sections 18 and 19.

Which is a 1 1/2" pipe in a swamp, approximately 15 ft. from the toe of the slope. No Bearing Trees.

East 1/4 Corner Section 24 only, T20-12W.

76

This point is marked by a 1" pipe with lead filled bell marked for E 1/4 Corner Section 24 and witnessed by a:

64" Spruce stump, S. 66° 13' W., 16.40 ft. The scribing is visible.

Sec. Corner common to Secs. 25 & 36, T20-11W and  
Secs. 30 & 31, T20-10W.

Found - 1 1/2" Pipe from which: Refer to Ren. #22.

24" Maple Stump bears N. 32° W. 25.0 ft. (orig) face chopped out, evidence of old chop marks & face, with tag.

50" Fir bears S. 18° W. 70.3 ft., scribed S36 CS, with tag.

Set - 2"x30" Iron Pipe with brass cap mkd: R T 20 S R 11 W  
11 35 30 10  
36 31 W

from which: 4" Chittewood bears N. 72° E. 1970

27.6 ft. scribed R10 S31 BT, tag. 650

4" Cedar bears N. 20° W. 47.3 ft. scribed R11 S25 BT, with tag.

Set 2 fence posts with signs ± 5 ft. west facing south.

± 5 ft. north facing east.

1/4 Corner common to Sections 7 and 18.

78

Found - No monument, from point of true corner. Refer to Ren. #28.

48" Fir Stump bears N. 83° E. 27.0 ft. (orig) face visible from top, with tag.

Set - 2"x30" Iron pipe with brass cap mkd: T 20 S R 11 W #198

from which: 10" Alder bears S. 68° W. 23.4 ft. 1970

scribed S18 BT, with tag. 650

Set fence post with signs ± 5 ft. east facing south.

RE-RENEWED, SEE CORNER NO. # 203 72

RE-RENEWED, SEE CORNER NO. # 221

RE-RENEWED, SEE CORNER NO. # 220 75

RE-RENEWED, SEE CORNER NO. # 184

RE-RENEWED, SEE CORNER NO. # 198

John M. Powell  
Frank Jones & W. Penley  
Sept., 1969  
C.S. File No. 53/66

Warren D. Hootman  
For Crown Zellerbach Corp.  
Jan. 30, 1963  
C.S. File No. 51/249  
Map File 22-36

TOM O. McCULLOUGH  
For U. S. Forest Service  
Feb. 1970 - C. S. File No. 55/142