

Douglas County Surveyor's Record of
Government Corners Renewed

20 T. S. 11 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

99

$\frac{1}{4}$ Corner to Section 6 only. T 20S R10W.
Original Corner never established.

At the properly proportioned position I placed a 2" x 36" Galv. I.P.,
flanged at the bottom and capped with a bronze disk welded on top.
The monument projects 6" above ground. I filled in around the pipe
monument with stone and packed earth.

I stamped the disk:

| |
|------------------|
| $\frac{1}{4}$ S6 |
| 1971 |
| 4185 |

I established new bearing trees as follows. Each bearing tree has a
scribed face and a U.S.F.S. bearing tree sign breast high and facing
the monument.

Set:; a 28" fir bears N 40° E 24.1 feet.
a 20" fir bears N 24° E 34.6 feet.

100

Section Corner to Sections 1 and 12 only.

Found: Original Maple B.T. in NE quadrant (good face but scribing was
destroyed in 1894) Found fir B.T. now 30" windfall with faint
face on bottom. Corner agrees very well with " canon " call
0.25 chains North.

Note: In 1894 all markings relating to R10W were destroyed making
corner common to Sections land 12 only.

From the original maple B.T. in NE quadrant I placed a 2" x 36" galv.
I.P., flanged at bottom and capped with a bronze disk welded on
top. The monument projects 6" above ground. I filled in around
the pipe monument with stone and packed earth.

Set: a 24" fir bears N 30° W 75.29 feet.
an 18" fir bears S 3° W 23.93 feet.

I stamped the disk:

| | |
|------|------|
| T20S | T20S |
| S1 | R10W |
| S12 | |
| R11W | S6 |
| | 1971 |
| | 4185 |

*FD. OK. 9/18/84
Dou. Co.
SURVEYORS
off.
C.S. 62/21*

101

Closing corner to Sections 6 and 7. T 20S R10 W.

No evidence of original corner found.

At the properly proportioned position I placed a 2" x 36" galv. I.P.
flanged at the bottom and capped with a bronze disk welded on top.
The monument projects 6" above ground. I filled in around the pipe
monument with stone and packed earth.

I stamped the disk:

| | | |
|-----|------|------|
| S12 | T20S | cc |
| | S6 | R10W |
| | S7 | |
| | 1971 | |
| | 4185 | |

I established new bearing trees as follows. Each tree has a scribed
face and a U.S.F.S. bearing tree sign breast high and facing the
monument.

Set: a 16" fir bears N 60° E 72.25 feet.
an 18" fir bears S 49° E 47.59 feet.

RENEWED, SEE CORNER NO. #161

102

$\frac{1}{4}$ Corner to Section 12 only.

No evidence of original corner found.

At the properly proportioned position I placed a 2" x 36" galv. I.P.,
flanged at the bottom and capped with a bronze disk welded on top,
The monument projects 6" above ground, I filled in around the pipe
monument with stone and packed earth.

I stamped the disk:

| |
|-------------------|
| $\frac{1}{4}$ S12 |
| 1971 |
| 4185 |

I established new bearing trees as follows. Each bearing tree has a
scribed face and a U.S.F.S. bearing tree sign breast high and facing the
monument.

Set: A 32" fir bears S 66° W 33.90 feet.
A 20" fir bears N 72° W 29.10 feet.

James W. Prochnau
For U.S. Forest Service
May, 1971 Rev. Aug. 1971
C.S File 55/201
Map File 41-77 Rev. M. 43 - 56