

**Douglas County Surveyor's Record of  
Government Corners Renewed**

T 20

T. S. R 12

R. W. W. M.

ROKE-CHAPMAN CO. EUGENE, ORE. 97101

William Shull  
LS #909  
For: USFS  
April 10, 1985  
M 98 - 69

**104**

1/4 corner for Sections 8 and 9.

Found - 1981 BLM 2" alum. cap, top extending 7" above ground. (& Ren. #80)  
41" spruce stump, S.69°E., 12.2 ft. scribe marks "BT" visible  
in partially open blaze. (41" spruce stump S.69°E., 18 lks. BLM)  
41" spruce stump, S.45°W., 9.3 ft. scribe mark "4" visible  
partially open blaze. (41" spruce stump, S.45°W., 12 lks. BLM)  
5" spruce, N.45 1/2°E., 19.2 ft. healed blaze (5" spruce  
N.45 1/2°E., 29 lks. BLM)  
13" spruce, N.72 1/2°W., 11.0 ft. healed blaze. (13" spruce,  
N.74 1/2°W., 17 lks. BLM).

Set - 2 1/4" USFS x 30" alum. monument with 3 1/4" alum. cap with  
magnet attached under cap. Cap marked "1/4 S8 RM  
S.34°32'E 49.6' 1985 LS 909". Cap bears N.34°32'W.,  
49.6 ft. with 2" exposed.

*FD OK  
BY R. Ward  
M 122-3B  
4/95*

**105**

Section corner for Secs. 16, 17, 20 and 21.

Found - 1 1/2" iron pipe with brass cap 12" exposed. Ren. #45  
18" fir snag, S.67°E., 46.2 ft. scribed "S21 T20S R12W"  
Root hole, S.45°W., 9.9 ft.  
15" fir, S.29°W., 15.8 ft. healed blaze.  
17" spruce, S.70 1/2°E., 67.3 ft. healed blaze.  
20" pine, N.78°W., 52.8 ft. healed blaze.

Set - USFS alum. monument, N.78°36'W., 48.5 ft.

New BT - 4 1/2" hemlock N.29°E., 18.3 ft. scribed "X BT".

William Shull  
LS #909  
For: USFS  
March 20, 1985  
M 98-67

**106**

1/4 Corner for Section 20 and 21.

Found - 1" I.P. with brass cap, loose, 12" exposed. Ren. #77 ~~#44~~  
I mounded soil and compacted around it.  
40" spruce stump, N.32°E., 9.8 ft. blaze visible.  
(Rec. BLM, N.21°E., 17 lks.)  
48" fir stump, S.76°W., 6.5 ft. blaze, no scribing visible.  
BLM rec. S.73°W., 8 lks.)  
18" fir, S.88°E., 29.9 ft. healed blaze. (Rec. 15" fir, S.87 1/2°E  
45 lks.)  
22" spruce, S.60°W., 20.4 ft. healed blaze. (Rec. 21", S.59 1/2°W.  
31 lks.)

Set - 2 1/2" USFS alum. monument, N.88°39'W., 49.2 ft. 3" exposed.  
Cap stamped "1/4 S20 RM S88°39'E 49.2' 1985 LS 909"

**107**

1/4 Corner for Secs. 12 and 13

Found - 1 1/2" iron pipe. Ren. #7  
20" Fir, N.34 1/2°E., 92.5 ft. with healed face.  
Hemlock stump, N.18 1/2°E., 53.0 ft. to face. (Rec. S.10°W., 45.5 ft.)

New BTs - 22" Spruce, N.28°E., 6.6 ft.  
11" Hemlock, S.44°E., 43.1 ft.

Set - Replaced I.P. with 3/4"x30" rebar with 2" alum. cap.

Clyde Mulkins  
L.S. #2008  
For: Sparrow-  
Pacific &  
Richard Holmes  
Oct. 30, 1987  
M 101 - 31

*FOUND OK 8/94 BY STUNTNER  
M 120-75 A-D* **108**

1/4 Corner for Secs. 13 and 14

Found - 1 1/2" iron pipe. Ren. No. 55  
Orig. BT, 30" spruce stump bears N.43°30'W., 21.1 ft. with visible  
face. (GLO records, N.62°W.)  
Orig. BT, double spruce stump remains bears N.77°30'E.,  
26.4 ft. (GLO record is East.)

Set - 3/4"x30" rebar and 2" alum. cap.

New BTs - 14" spruce scribed "1/4 S 14 BT" bears N.85°W, 35.6 ft.  
23" spruce scribed "1/4 S 14 BT" bears S.2°W., 21.3 ft.

**109**

1/4 Corner for Section 13 only. (east)

Found - 1" iron pipe. Ren. No. 19  
Orig. BT, Spruce stump with visible scribe marked "BT" bears  
S.8°W., 27.1 ft.  
Schoolmarm Spruce bears N.50°W., 63.9 ft. (Rec. N.52°W, 63.1 ft.)  
32" Hemlock stump bears S.61°W., 37.0 ft.

Set - 3/4" x 30" rebar and 2" alum. cap

New BTS - 9" fir scribed "1/4 BT" bears N.75°E., 21.8 ft.  
6" D. fir scribed "1/4 BT" bears S.23 1/2°W., 4.9 ft.