

Douglas County Surveyor's Record of
Government Corners Renewed

20

T. S.

12

R. W. W. M.

Meander Corner of Sections 22 and 27. 11
Spruce 30" DBH bears N.58°15'E. 45.4 ft.
Fir 9" DBH bears S.75°30'W. 31.9 ft.

$\frac{1}{4}$ Corner common to Sections 22 and 23. 12
Proportioned distance 471.5 ft. South 0°43'E. of the N.
Meander Corner of Sections 22 and 23 by driving an iron
pipe and marking the following bearing trees:

D. Fir 6" DBH bears N.60°45'E. 13.0 ft.
D. Fir 5" DBH bears N.19°00'W. 17.9 ft.

This corner lays on an East slope approximately 145 ft.
West of the Creek.

West Meander Corner Sections 14 and 23. *SEE ALSO REN. #65* 13
I calculate the position by a series of triangulations
locating the approximate position of this corner on the lake
shore. I find the 2 original bearing trees with visible scribing
and the corner point marked by a pipe. Both bearing trees are
short snags. I mark new bearing trees as follows:

Hemlock 6" DBH bears N.74°30'E. 45.3 ft.
Hemlock 6" DBH bears S.82°15'E. 64.4 ft.

$\frac{1}{4}$ Corner common to Sections 23 and 14. *SEE ALSO REN. #66* 14
I find the pipes set by Corbett and the 2 Spruce stumps
blazed by him and the remains of the original D. Fir BT.
I re-witness this corner by marking:

D. Fir 7" DBH bears S.12°00'W. 17.7 ft.
Spruce 4" DBH bears N.33°00'E. 6.5 ft.

$\frac{1}{4}$ Corner common to Sections 23 and 26. *SEE ALSO REN. #62* 15
I identify from the original bearing trees. Corner point
is marked by a pipe. I mark one new bearing tree as follows:
Spruce 28" DBH bears N.53°30'E. 29.3 ft.
The Orig. BT bears S.22°00'W. 16.5 ft.
measured to the face; the tree is dead at this time.
The corner lays on an East slope approx. 60 ft. East of the
top of the ridge. Timber in the SE quad. has been cut in
recent times.

$\frac{1}{4}$ corner common to Sections 23 and 24. *ONLY PER FRITZ 6/9/92* 16
I set a pipe witnessed as follows: *SEE G.I.S.*
Hemlock 22" DBH bears S.43°00'W. 4.0 ft.
Alder 16" DBH bears S. 3°30'E. 10.1 ft.

Center of Section 23. 17
I set a pipe at the CS $\frac{1}{4}$ corner and witness it as follows:
Fir 50" DBH bears N.70°30'W. 34.0 ft.
Fir 52" DBH bears S.84°30'W. 29.5 ft.

By Warren D. Hootman
For Crown Zellerbach Corp
July 28, 1960 Filed Jan. 1961
C. S. File No. 51/165
Map File M 11 - 77

RE-RENEWED CORNER NO. 134

NO. 135