

**Douglas County Surveyor's Record of  
Government Corners Renewed**

T 20      T. S.      R 12      R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE. 97501

Clyde Mulkins  
L.S. #2008  
For: Sparrow-Pacific  
& Richard Holmes  
Oct. 30, 1987  
M 101 - 31

Section Corner for Secs. 13, 14, 23 and 24. *FIND. OK 3/92 BY STUNTZNER*  
Found - A 4" square white post very rotted at base, bears *M 120-75 A-D* **110**  
    NW 0.5 ft. Ren. #53 (No monument found) See #33 for report.  
    30" Spruce, N.25°W., 38.2 ft. with healed face.  
    Orig. 36" D. fir snag, N.4°E., 43. ft. to face with visible scribe.  
    60" Spruce stump, S.31°30'W., 26.2 ft. with tag.  
    Orig. 36" Spruce stump, S.52°W., 29.0 ft. with visible chop marks.  
    Orig. BT, 46" D. fir snag, N.3°W., 52.0 ft. Face not opened.  
    Cruiser marks.  
    30" Spruce of unknown origin with healed face, N.25°W., 38.2 ft.  
Set - 3/4" x 30" rebar with 2" alum. cap based on W.G. Corbitt 1943  
    measurements.  
New BTs - 15" Hemlock scribed S13 T20S R12W. BT" bears N.3°W., 38.1 ft.  
    32" Spruce scribed S24 T20S R12W BT" bears S.1°E., 43.6 ft.  
    6" Hemlock scribed "X-BT" bears S.79°W., 5.1 ft.

10/30/87

Daniel Baker  
For: International  
Paper Company and  
Davidson Industries  
July 1988  
M 106 = 67

Closing Corner for Sections 7 and 18 of T.20-11  
Found - 2" very rusted pipe. Ren. No. 40 **111**  
    35" spruce, N.45°E., 30.5 ft.  
    54" fir stump, N.52°E., 108.0 ft.  
    32" deadspruce, S.61½°E., 62.0 ft.  
Set - 3/4" x 42" alum. rod and cap mkd. "RLS 1978 T20S S13 | <sup>S7</sup>/<sub>S18</sub> R12W  
    R11W 1988".

**112**

Meander corner for Sec. 12; and Sec. 7 of T.20-11  
(Point 1366.62 ft. southerly of point for sec. cor. for 1 and 12.)  
Set - 3/4" x 42" alum. rod and cap mkd. "RLS 1978 MC S12 | S7 T20S R12W  
    R11 1988".  
    30" spruce, N.44°E., 68.5 ft. scribed MC S7 BT.  
    16" alder, S.28°W., 11.8 ft. bark scribed MC S12 BT.

7/88

Douglas County  
Surveyors Office  
Randall Smith  
Stephen Flause  
Oct. 4, 1988  
C.S. 62/59

1/4 Corner for Sections 10 and 15 **113**  
Found - 2" O.D. iron pipe rusted and top broken, protrudes 2" above  
    the ground. Ren. No. 90  
    24" now 32" dia. 3 ft. high burnt spruce stump, we open, no #126  
    scribing or blazes found, nail was found along east side of  
    stump. Bears N.21°W., 15.8 ft. (Orig. Ren. N.14°W., 15.2 ft.)  
    36" dia. spruce now a 30" dia. 4 ft. high burnt D. fir stump  
    occupies position. Possible open blaze with axe marks, no scribin  
    found. Bears S.65°E., 13.8 ft. (Orig. rec. S.65°E., 13.2 ft.)  
    24" now 24" dia. 3½ ft. high D. fir stump with a possible open  
    face, no marks see bears N.70½°E., 25.5 ft. (Rec. N.70½°E.,  
    24.9 ft. dist. is a possible face measurement.) Ren. No. 90  
New BTs - 11" spruce, PK nail on East base, bears S.25½°E., 2.85 ft.  
    10" D. fir, PK nail on south base, bears S.81°E., 9.60 ft.  
    15" double trunked spruce, PK nail on east base, bears N.1°E.,  
    16.0 ft.  
    11" 1 ft. high D. fir stump, PK nail in center on top, bears  
    S.53½°W., 10.55 ft.

I.P. lies in an area that is to be clear cut in near future. Possible orig.  
SE D. Fir does not appear large enough to have once been a 36" spruce.

10/4/88

Section corner for Sections 1, 2, 11 and 12 **114**  
Found - 1982 BLM 3½" alum. cap on a 2½" O.D. alum pipe, protudes 5 in.  
    above ground. *#128*  
    A 1½" I.D. iron pipe was found 5" below ground along west edge  
    of alum. cap and pipe. Ren. #57 This apparently is the  
    position commonly accepted as the corner location.  
    10" dia. power pole No. "A Co84" with scribe marks "S1RE4079BP"  
    bears N.24°E., 25.0 ft. (Agrees with rec.) Ren. #3  
    10" now 6" dia. 5 ft. high rotted spruce snag, no scribing visible  
    bears S.41°E., 39.6 ft. (agrees with 1982 BLM rec.) Ren. #3  
    20" now 12" dia. 3 ft. high rotted spruce stump, scribe marks  
    visible "79 BT" bears S.5°W., 69.0 ft. (BLM Rec. S.5°W., 69.9 ft.)  
    Ren. #3 BT.  
    48" now 60" dia. spruce with a partially healed single blaze,  
    scribe marks visible "S11 RE4079" bears N.88°W., 132.2 ft.  
    (agrees with Ren. #3)

Douglas County Surveyors  
Office  
Randall Smith  
Stephen Flause  
Aug. 16, 1988  
C.S. 62/59