

Douglas County Surveyor's Record of
Government Corners Renewed

T 20 T. S. R 12 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97301

C O N T. - - -

Douglas County
Surveyors Office
R.W. Smith - S.J.
Flause
Aug. 16, 1988
C.S. 62/59

8" now 14" dia. spruce with a fully healed single blaze bears S.7°E., 60.1 ft. (agrees with record) 1982 BLM BT. **114**
7½" now 12" dia. spruce with a partially healed single blaze, illegible scribe marks visible, bears S.4°W., 51.1 ft. (agrees with rec.) 1982 BLM BT.
No original BTs or BTs from GLO 1905 resurvey found.
1½" I.D. iron pipe firmly set and protruding 10" above ground, bears S.31 3/4°E., 19.7 ft. (See Renewal records in C.S file No. 52/91)
A loosely set 1½" I.D. iron pipe protruding 11" above ground bears N.47°E., 51.7 ft. (Source unknown)

No new accessories.
Monument lies approx. 100 ft. south of south Lake Shore of Siltcoos Lake, near the first cove west of railroad bridge at mouth of Fiddle Creek Arm.

8/16/88

Center Found: 1/4 S.1, T20S, R12W.
1981 2 1/2" dia. brass cap on a 2 1/4" O.D. iron pipe protruding 10" above ground. Cap is stamped PLS 1457, T20S R12W, C 1/4 S 1, 1981. **115**
A 1/2" iron pipe 46" long loosely set and protruding approx. 40" above ground. REN#101
Per M 88-13 (bearings and distances to M 98-13 BC/IP) #101
24" now 26" Dia. maple with a possible fully healed blaze bears S.64°W., 30.8 ft. (agrees with record)
12" now a 13" dia. alder with bark scribing "C 1/4 BT S 1" bears S.29°E., 19.3 ft. (record S 29° E, 20.2 ft.)
9" now 11" dia. double trunked spruce a fully healed blaze is on pistol butt south trunk. Center of root crown bears N 45°E, 27.7 ft. (record N 40° E, 29.8 ft.)
Set: A 2 3/8" dia. DCSO brass cap on a 1 3/8" O.D. by 42" long iron pipe protruding 6" above ground.
26" Dia. maple with a possible fully healed blaze bears S 68° W., 29.8 ft.
13" dia. alder with bark scribing "C 1/4 BT S1" bears S 35° E, 15.7'
11" dia. double trunked spruce, a fully healed blaze is on pistol butt south trunk. Center of root crown bears N 37°E, 30.5 ft.
A 1981 2 1/2" BC/IP bears N 3°E, 3.3 ft.

*Fd. 6/90
M 110-42*

Douglas County Surveyors Office
R.W. Smith - Stephen Flause
July 26, 1989
C.S. 62/64

1/4 Corner Sections 1 and 12 T20S, R12W. **116**
Found: A 1 1/2" O.D iron pipe with B.C. protrudes 4" above ground per ren. #27.
A 1 1/2" I.D. iron pipe protrudes 1.5" above ground per ren. #4 (described as accessory found below)
NOTE DIST. & BEARINGS TO BC/IP
36" now 43" dia. 6 ft. high spruce stump with a fully healed double blaze bears N 72 1/2° W., 47.2 ft. (agrees w/rec. per ren#27)
36" now 44" dia. spruce with a fully healed double blaze bears S 63° E, 48.0 ft. (agrees with rec. per ren # 27)
A 1 1/2" I.P. set per ren #4 as 1/4 cor. bears N 87 1/4° E, 226.11 ft. (agrees well with M 88-13, record per RM 1-47 apparently has a mixup in bearing (S 87°11'40"E, 226.19 ft.)
New BT's: 7" hemlock double blazed and scribed "1/4 S1 CS BT" bears N 77°E, 14.5 ft.
NOTE: On visit to corner Aug. 18, 1988 new 7" hemlock BT was destroyed by recent cat work it is down and out of position. Corner lies at the east edge of a recently logged clear cut.

Center West 1/16 Section 1 **117**
Found: A 2 1/2" dia. brass cap on a 2 1/4" O.D. I.P. protrudes 8 in. above ground.
26" now 29" dia. D. fir with an axed "X" upper blaze and a partially healed lower blaze with illegible scribing visible, bears N 82°W, 8.0' (rec. N82°W, 8.7' to center of trunk)
25" now 28" dia. spruce with an axed "X" upper blaze and a partially healed lower blaze, no scribing visible, bears S 29°E, 11.5 ft. (agrees with rec.)
Set: A 2½" dia. DCSO B.C. on a 1 3/8" O.D. by 32" long iron pipe, protruding 6" above ground.

*Fd. 7/92 BY WOSSE
M 115-42*