

Douglas County Surveyor's Record of
Government Corners Renewed

20 T. S. 12 R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORS. 97101

Douglas County
Surveyors Office
Randall Smith
Stephen Flause
Aug. 16, 1988
C.S. 62/64

Continued:

Set: 29" dia. D. fir with an axed "X" upper blaze and partially healed lower blaze with illegible scribing visible bears S 65°W, 8.6 ft. BT per M 88-13 (Blaze faces S 82°E).
28" dia. spruce with an axed "X" upper blaze and partially healed lower blaze. No scribing visible, bears S 22°E, 15.8 ft. BT per M 88-13.
1981 2½" dia. brass cap / iron pipe bears S 1°E, 4.7 ft.

117

New County Line Marker on East R/W Line of S.P.R.R. (on E-W center-line of section 1) 118

Set : A 2 3/8" diam. brass cap marked "T20S R12W C____C S 1 1989 Office" on a 1 3/8" O.D. x 32" long galvanized iron pipe is firmly set and protruding approx. 5" above ground.
11" D.B.H. spruce D. blazed "S1 CS BT" bears N 64°W, 11.2 ft.
8" D.B.H. spruce D. blazed "S1 CS BT" bears S 38°W, 8.3 ft.
A 5/8" I.R./ALC. bears S 1½°E, 28.86 ft.

Monument is located on timbered bench between Ada Park Rd. and S.P.R.R. tracks. Monument lies nearer railroad tracks.

119

Sec. Cor. for Secs. 24 and 25 only

Found - 3" dia. brass cap on a 1¼" O.D. Iron pipe protruding 12" above ground. Ren. No. 25
24" now 60" dia. 8 ft. high Spruce stump, no blazes or scribing found, bears S.38°E., 40.8 ft. (Rec. S.35°E., 38.3 ft.) Orig.
40" now 56" dia. 7 ft. high Spruce stump, with an axed "X" facing BC/IP and scribing found, illegible scribe marks and a "W" found facing S.70°W., on a previously opened blaze, bears N.15°E., 25.1 ft. (agrees w/rec) Orig. BT.
3" now 10" dia. down and rotted Spruce, no blazes or scribing found, roots bear S.25°W., 46.2 ft. (agrees w/rec) Orig. BT(?)
Unrecorded 28" dia. R.Cedar with a healed blaze, bears S.20°E., 15.6 ft. (tag dated 1968, N.20°W., 15.0 ft.)
New BTs -14" dia. R.Cedar, double blazed and scribed "T20S R12W S24 CSBT" bears N.46°W., 2.8 ft.
21" dia. Hemlock double blazed and scribed "T20S R12W S25 CS BT" bears S.52°W., 43.5 ft.

6/9/92

120

Section Corner for 19 and 30 only of T.20-12

Found - 3" dia. brass cap on a 1¼" O.D. Iron pipe, protruding 12" above ground. Ren. No. 20
18" now 24" dia. uprooted and down rotting Spruce, trunk is earth covered, root hole bears N.44°E., 21.8 ft. (agrees w/rec) Orig.
20" now 30" dia. uprooted and down rotting Hemlock, trunk unearthed, a blaze with illegible scribe marks found. Root hole bears S.80°W., 14.5 ft. (agrees w/rec) Orig. BT.
8" dia. Hemlock now roots found, bears S.66½°E., 21.1 ft. Orig. BT(?)
4" now 21" dia. Hemlock with a fully healed single blaze facing N.30°W., bears S.78°E., 10.7 ft. (agrees w/rec) Ren. No. 20
4" now 12" dia. R.Cedar with a fully healed single blaze, bears S.4°W., 7.1 ft. (Rec. S.4°W., 7.8 ft.) Ren. No. 20
New BTs -13" dia. Hemlock double blazed and scribed "CC T20S R11W S19 CSBT" bears N.64°E., 43.1 ft.
21" dia. D.Fir double blazed and scribed "CC T20S R11W S30 CS BT" bears S.36°E., 13.6 ft.

6/10/92

121

Section Corner for 27, 28, 33 and 34

Found - 48" now 42" dia. 6 ft. high Spruce stump with scribing visible on a partially healed blaze "S34 T20S R12W", bears S.11°E., 35.0 ft. horizontal (as per record)
No other original BTs found.
BT from Ren. No. 71 not found.
Area recently logged, corner in slide area.
Set - A 2 3/8" dia. Brass cap on a 1¼" O.D. x 31" long Iron pipe, is set at rec. brg. < dist. from remaining orig. BT. BC/IP protrude 1" above a 2 ft. dia. mound of sandstone. Cap mkd:
Douglas County Surveyors T20S S28|S27 R
Office 1992 S33|S34 12

(Cont. Next Page

W

Douglas County
Surveyors Office
Randall Smith
Stephen Flause
June 1992
C.S. 64/26

Doug. County
Surveyors Office
Randall Smith, Deputy
Stephen Flause
August 6, 1992
C.S. File 64/31