

Douglas County Surveyor's Record of
Government Corners Renewed

T. 20 T. S. R 12 W R.W.W.M.

POPE-CHAPMAN CO., EUGENE, ORE. 97501

John Minor
For: Menasha Corp.
Feb. 1993
M 116 - 56

Section Corner for Sections 13 and 24 only. East side.
Found - Two 3/4" Iron pipes side by side. Org. unknown. A 1 1/2" iron pipe is called for in M 22-36. **130**
Ren. No. 32.
15" Holly S23°W 44.6' , side center.
14" Apple N23°W 34.7' , side center.
48" Spruce S15°E 48.5' , side center (rec. S17°10'W 48.10')
2/93

Corner Secs. 26, 27, 34, & 35
Found - 1 1/2" I.D. iron pipe protruding 8" above ground. **Ren. # 58** **131**
24" now 60" dia., 10' high spruce stump no blazes or scribing visible, bears N.66 1/2°W., 43.5' to root crown (rec. N.61°W., 35.6' is a possible blaze measurement) Orig. BT.
40" now 48" dia., 8' high rotted spruce stump with scribing visible "34" bears S.88°W., 73.2' to root crown (rec. S.88°W., 65.3' is a blaze measurement) Orig. BT.
30" now 50" dia., 8' high spruce stump with illegible scribe mark visible in a previously opened blaze bears S.64°E., 12.7' (rec. S.64°E., 11.2' is a blaze measurement) Orig. BT.
Set - 2 3/8" dia., brass cap on a 1 3/8" O.D. iron pipe is set at referenced position of 1 1/2" I.P. BC/IP protrudes 7" above ground. Stamped:

DOUGLAS COUNTY SURVEYORS

FO. OK 8/94 BY STUNTNER T208 R
M 120-76 A-D; CS 63/145
S27|S26 1
S34|S35 2
1994 W

OFFICE

1 1/2" I.P. measured 27' long when removed is set along North edge of BC/IP, protrudes 7" above ground.
6" dia., Spruce, double blazed "T208 R12W S27 CS BT" bears N.34°W., 29.1'.
24" dia., 2' high Hemlock stump with boat spike through BT tag set near center on top BS stamped "BO2", BS S.2°E., 36.4'.
30" dia., 1 1/2" high Spruce stump with Boat spike through BT tag set near center on top, BS Stamped "BO1" BS bears N.83 1/2°E., 38.8'.
26" dia., 1 1/2" high Hemlock stump with Boat spike through BT tag set near center on top, BS stamped "BO3" BS bears S.58 1/2°W., 17.9'.
See C.S. File for sketch.

Note: Corner lies in a new clear cut.

Meander Corner, Secs. 26 & 35

Found - 1 1/2" I.D. iron pipe leaning 12" East of a plumb position. **132**
(Rens. # 60 & 81)
30" now 50" dia., 7' high Spruce stump, knife made scribe marks "R1" and nail from Ren. #60 visible on East trunk of stump. Nail bears S.15°E., 22.4', center of stump bears S.10°E., 22.4' (Orig. Rec. S.18°E., 22.4'). North side of stump shows evidence of being previously opened no evidence of scribing or blazes visible.
Set - 2 3/8" dia., brass cap on a 1 3/8" O.D. by 32" long iron pipe is set a plumb position of found 1 1/2" I.P. protrudes 5" above ground. Stamped:

DOUGLAS COUNTY SURVEYORS

FO OK BY STUNTNER 8/94
M 120-75 A-D; C.S. 63/145
T208 R
S26|MC 1
S35| 2
OFFICE W
1994

1 1/2" I.P. measured 27' long is set along North side of BC/IP protrudes 5" above ground.
46" dia., Hemlock double blazed & scribed "MC S35 CS BT" bears S.73°W., 29.6'.
19" dia., Alder bark scribed "MC S26 CS BT" bears N.68°E., 29.3'.
18" dia., Pistol Butt Cascara bark scribed "MC S26 CS BT" also BT tap w/PK nail to top, PK nail bears N.6 1/2°W. 18.4'.
See sketch in C.S. File for more detail.

Note - We remonumented MC position as determined by Corbitt in 1943

Douglas County Surveyor's Office
Randall W. Smith, Deputy
Stephen J. Flause
4/21/94
C.S. File 64/51