

Douglas County Surveyor's Record of
Government Corners Renewed

20 T. S. 12 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97501

1/4 Corner for Sections 14 & 23.

133

Found - A 2" pipe as shown in M11-77. See renewal # 66.
Set - A 3/4" x 30" iron rod with 2" aluminum cap marked "Stuntzner Engineering 1/4 S14 S23 1994 LS 1342". Placed in the center of the 2" iron pipe.

Found BT's -

30" spruce stump bears N.61°E., 32.8 ft. to center, (rec. N61°E., 30.9 ft.)

27" Fir with healed face and tag bears S.12°W., 16.9 ft. to side center, (rec. S.12°W., 17.7 ft.)

48" Spruce stump bears S.81°W. 17.8 ft. (rec. S.81°W., 15.9 ft.)

New BT - 18" Hemlock face scribed "N 1/4 S23 BT" with X-chop and tag at B.H. bears S.57°E., 7.0 ft. to spike at side center.

1/4 Corner for Sections 22 & 23.

134

Found - 3/4" iron pipe (M11-77). See renewal #12.

Set - 3/4" x 30" iron rod with 2" aluminum cap marked "Stuntzner Engineering 1/4 S22 S23 1994 LS 1342". Set in the center of iron pipe.

Found BT's -

20" Fir stump bears N.19°W., 17.9 ft., scribed "BT" on new face.

New BT's - 22" Fir stump face scribed "BT" bears N.85°E., 8.6 ft. to center.

75" Spruce stump bears S.78°E., 43.2 ft. to center, not tagged or marked.

60" Spruce stump bears N.19°W., 58.3 ft. to center, not tagged or marked.

Center 1/4 for Section 23.

135

Set - 3/4" x 30" iron rod with 2" aluminum cap marked "Stuntzner Engineering C 1/4 S23 1994 LS 1342".

New BTs-37" Spruce, face scribed "C 1/4 S23 BT" with X-chop and tag at B.H. bears S.58°E., 19.4 ft. to spike at side center.

9" Fir, face scribed "C 1/4 S23 BT" with X-chop and tag at B.H. bears N.67°W., 23.6 ft. to spike at side center.

56" Fir stump, bears N.37°W., 59.8 ft. to center. Hootman BT.

52" Fir stump, bears N.36°E., 37.5 ft. to center. Hootman BT.

Note - Hootman's iron pipe not found. (Ren. # 17)

1/4 Corner for Sections 23 & 26.

136

Found - 1 1/2" iron pipe. (C.S. file 52/91) See renewal #62.

Set - 3/4" x 30" iron rod with 2" aluminum cap marked "Stuntzner Engineering 1/4 S23 S26 1994 LS 1342".

Found BT's -

28" Spruce stump with healed face and tag bears N.53°E., 29.3 ft.

44" Fir stump with visible scribe and tag bears S.25°W., 16.5 ft. (Original BT)

New BTs-16" Spruce, face scribed "S 1/4 S23 BT" with X-chop and tag at B.H. bears N.65°E., 12.9 ft. to a spike at side center.

15" Fir, face scribed "N 1/4 S23 BT" with X-chop and tag at B.H. bears S.50°E., 22.1 ft. to a spike at side center.

Closing Corner common to Sections 23 & 24.

137

Found - 1" iron pipe (C.S. File 51/249) See renewal #38.

Set - 3/4" x 30" iron rod with 2" aluminum cap marked "Stuntzner Engineering T20S R12W S23 S24 CC 1994 LS 1342"

Found BTs -

30" rotten Hemlock stump bears N.23°30'W., 19.8 ft. to face (Original BT)

46" Fir snag with visible scribe and tag bears N.79°E., 17.9 ft.

New BTs-21" Fir, face scribed "CC S24 BT" with X-chop and tag at B.H. bears N.39°E., 22.2 ft. to spike at side center.

14" Spruce, face scribed "CC S23 BT" with X-chop and tag at B.H. bears N.74°W., 13.0 ft. to spike at side center.

Ronald Stuntzner
For: Takkenitch Tree Farm
August 1994
M 120 - 75 A - D
C.S. File 63/145