

Douglas County Surveyor's Record of
Government Corners Renewed

20 T. S. 12 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97401

138

Original Section Corner common to Sections 25 & 26 only.
Found - 1" iron pipe inside the rusted remains of a 3" iron pipe
(C.S. File 51/249) See renewal # 37.
Set - 3/4" x 30" iron rod with 2" aluminum cap marked "Stuntzner
Engineering T20S R12W S24 S25 S26 1994 LS 1342" at
position of 1" iron pipe.
Found BTs -
36" Spruce stump bears N.55°W., 8.58 ft. (Original BT)
48" Spruce stump bears S.76°W., 26.4 ft. (Original BT)
New BTs-16" Fir, face scribed "T20S R12W S24 BT" with X-chop and tag
at B.H. bears N.58°E., 9.0 ft. to spike at side center.
14" Hemlock, face scribed "T20S R12W S26 BT" with X-chop and
tag at B.H. bears S.74°W., 22.6 ft. to spike at side
center.

139

1/4 Corner for Sections 26 & 35.
Found - 58" Fir stump (Original corner tree).
Set - 3/4" x 30" iron rod with 2" aluminum cap marked "Stuntzner
Engineering 1/4 S26 S35 1994 LS 1342" in stump.
Found BTs -
A leaning 44" Fir stump, bears S.69°W., 14.5 ft. to a point
where center of stump would be if leaned back into
position. (Original BT)
New BTs-13" Spruce, face scribed "S $\frac{1}{4}$ S26 BT" with X-chop and tag at
B.H. bears N.13°W., 8.9 ft. to a spike at side center.
11" Cherry, bark scribed "S $\frac{1}{4}$ S26 BT" with X-chop and tag at
B.H. bears N.76°E., 8.2 ft. to spike at side center.
27" Spruce, face scribed "N $\frac{1}{4}$ S35 BT" with X-chop and tag at
B.H. bears S.57°W., 32.0 ft. to a spike at side center.

140
14

Meander Corner common to Sections 35 & 36.
Found - 2" iron pipe 2 feet high in lake. (C.S. File 52/91)
See renewal # 52.
Set - 3/4" x 5 ft. iron rod with 2" aluminum cap marked "Stuntzner
Engineering MC S35 S36 1994 LS 1342"
New BTs-37" Spruce, face scribed "MC S36 BT" with X-chop and tag at
B.H. bears S.13°E., 66.0 ft. to a spike at side center.
13" Alder, bark scribed "MC S35 BT" with X-chop and tag
bears southwest along shoreline.
Bearing Object - The shoreline bears South, 2 feet.

141

1/4 Corner for Sections 35 & 36.
Found - 2" iron pipe (C.S. File 52/91). See renewal #51.
Set - 3/4" x 30" iron rod with 2" aluminum cap marked "Stuntzner
Engineering $\frac{1}{4}$ S35 S36 1994 LS 1342". Set inside 2" I. pipe
Found BTs -
83" Fir stump with visible scribe bears S.6°30'E., 43.7 ft.
to nail in face. (C.S. File 52/91)
48" Fir stump with tag bears N.35°W., 9.25 ft. to nail in
face. (C.S. File 52/91)
Possible cedar root bowl bears S.18°W., 9.24 ft. (Orig. BT)
New BTs-19" Hemlock, face scribed "W $\frac{1}{4}$ S36 BT" with X-chop and tag at
B.H. bears N.75°E., 3.82 ft. to a spike at side center.
10" Hemlock, face scribed "E $\frac{1}{4}$ S35 BT" with X-chop and tag at
B.H. bears S.2°W., 9.76 ft. to a spike at side center.

142

Section Corner for Sections 35, 36; Sections 2, 1 of T. 21-12.
Found - 2 $\frac{1}{2}$ " Brass cap properly marked on 2" iron pipe with 1 $\frac{1}{2}$ " iron
pipe lying along side. (C.S. 58/140) See renewal #97.
Found BTs -
20" Hemlock, with healed face and tag bears S.13°W., 40.2
ft. (C.S. 58/140)
15" Spruce, with healed face and tag bears N.50°30'W., 53.8
ft. (C.S. 58/140)
48" Fir stump, bears N.78°E., 1.0 ft. to face (C.S. 58/140)
Bearing Object - An iron fence post bears N.66°E., 1.2 ft.

Ronald Stuntzner
For: Tahkenitch Tree Farm
August 1994
M120 - 75 A - D
C.S. File 63/145