

**Douglas County Surveyor's Record of
Government Corners Renewed**

20 T. S. 12 R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE. 97501

143

Closing Township Corner Amended (NW Cor. Sec. 6, T.21-11)
Set - 2" Brass cap on 2" iron pipe for amended closing corner. Cap is stamped "T20S R11W S31 CC S6 T21S T21S S1 R12W 1995 LS 2656"
New BTs-12" Alder, N.71°E., 27.7 ft. bark scribed "T20S R11W S31CC BT"
18" Hemlock, S.39°W., 45.3 ft. scribed "S1 BT"
8" Spruce, N.84°W., 28.3 ft. chopped "X"
County Surveyor's Brass Cap per C.S. file 54/1 bears N.89°29'E., 4.97 ft.

144

Original closing Township Corner (SW Cor. Sec. 31 T.20-11)
Found - 2½" Douglas County Surveyor's Office brass cap on a 1½" iron pipe. (C.S. 54/1) See renewal # 30.
20" Fir stump, N.6°E., 20.4 ft. (rec. 21.1 ft.)
32" Fir stump, S.19°E., 6.7 ft. (rec. S.20°E., 6.3 ft.)
Uprooted Fir stump, N.43°W., 18.0 ft. to root hole. (rec. 20.5 ft.)
New BTs -
14" Spruce, S.20°E., 34.5 ft. scribed "T21S R11W S6 CC BT"
13" Alder, N.44°W., 2.5 ft. bark scribed "S1 BT"

145

Original Township Corner (SE Corner Sec. 36)
Found - 2½" aluminum pipe (set by Durham in 1964) Menasha records.
BTs per C.S. 54/1 - See renewal # 31.
30" Fir snag, S.88°W., 41.6 ft. (rec. S85°W., 40.9 ft.)
22" Hemlock stump, N.15°E. 29.8 ft. (rec. N.15½°E. 30.1')
38" Fir stump, N.48°W., 42.2 ft. very rotten (rec. 40.1 ft.)
Rotten Fir stump, N.5°E., 30.7 ft. scribing visible (rec. N.5½°E., 28.4 ft.)
New BTs -
9" D.Fir, N.39°E., 16.5 ft. scribed "S31 BT"
11" Alder, S.19°E., 20.9 ft. bark scribed "S31 BT"
8" Alder, S.61°W., 21.0 ft. bark scribed "T21S R12W S1 BT"
14" Alder, N.14°W., 10.1 ft. bark scribed "T20S R12W S36 BT"

146

1/4 Cor. Secs. 16 & 21
Set - 2½"x30" Alum. monument with 3" cap mkd:
T20S R12W
S16
S1721
1994
LS 1091
BTs - 21" Spruce, bears N.81 3/4°W., 63.6', scribed "¼ S16 BT"
6" Spruce, bears S.21½°W., 34.2', scribed "¼ S21 BT"
20" Spruce, bears S.4°E., 63.1', scribed "¼ S21 BT"
12" Alder, bears N.15½°W., 10.8', scribed "¼ S16 BT"

147

Witness Corner to Meander Corner West of Cor. Secs. 15, 16, 21, & 22
Set - 2½"x30" Alum. monument with 3" cap mkd:
T20S R12W
S16 | WC
S21 | MC
1994
LS 1091
BTs - 6" Fir, bears N.57½°W., 6.9', blazed & scribed "X BT"
14" Spruce, bears S.30°E., 6.5', blazed & scribed "X BT"

148

1/4 Cor. Secs. 33 & 4, T21S R12W
Found - Corbitt's 1½" I.P. (Ren. #91), REPLACED pipe with a 2½"x30" Alum. cap mkd: T20S R12W ¼ S33 S4 T21S 1994 LS 1091
BTs - 18" Spruce, bears N.45°E., 22.1' (¼ S33 BT)
30" D.Fir, bears S.50°E., 8.0' (¼ S4 BT)
10" Spruce, bears S.4°E., 19.4' (X BT)
10" Spruce, bears S.13 3/4°W., 13.6' (¼ S4 BT)

John C. Bentley
For: I.P. Timberlands Operating Co., Ltd.
Feb. 1995 M121-68

Robert Ward, L.S. # 1091
For: Siuslaw National Forest &
Tahkenitch Tree Farm Partnership
April 1995
M 122-3 A & B & M 122-4