

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 20 S. T. S. R. 12 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 91881

Section Cor. common to sections 13 and 24 only.

Corner marked by a 1 1/2" iron pipe at the top of a bank East of Slonecker's house, and witnessed as follows:

- 11" Spruce, S. 17° 10' W., 48.10 ft.
- 11 1/2" Holly, S. 22° 30' W., 44.60 ft.
- 12" Apple, N. 27° 15' W., 35.50 ft.

**RE-RENEWED, SEE CORNER NO. #130**

32

Section Corner common to Sections 13-14-23 and 24.

Which is a 1 1/2 in. iron pipe witnessed by three of the orig. bearing trees as follows:

- 56" Spruce, S. 52° W., 51.7 ft.
- 42" Douglas Fir, N. 3° W., 51.5 ft.
- 44" Douglas Fir, N. 4° W., 44.2 ft.

**RE-RENEWED, SEE CORNER NO. #110**  
*see Rev. #53 for 1943 Corner Report*

33

1/4 Corner Section 13 and 24.

1" Brass capped pipe, witnessed as follows:

- 8" Hemlock, S. 70° W., 30.5 ft.
- 32" Spruce, N. 60° W., 50.6 ft.

*(Duplicate of #24)*

This corner is about 10 ft. West of the west cut slope of the Forest Service Road.

34

Closing Corner Section 18 and 19, T20-11W.

Which is a 1 1/2" pipe in a swamp, approximately 15 ft. from the toe of the slope to Bearing Trees.

**RE-RENEWED, SEE CORNER NO. #129**

35

East 1/4 Corner Section 24 only.

This point is marked by a 1" pipe with lead filled bell marked for E 1/4 Corner Section 24 and witnessed by a:

- 64" Spruce stump, S. 66° 13' W., 16.40 ft. The scribing is visible.

36

Section Corner to Sections 25 and 26 only.

Said point being a 1" iron pipe and witnessed by the original bearing trees as follows:

- 36" Spruce, N. 66° E., 33.66 ft.
- 38" Spruce, S. 65° E., 13.20 ft.
- 36" Spruce, N. 55° W., 8.58 ft.
- 48" Spruce, S. 76° W., 26.40 ft.

Said point being 5229.90 ft. N. 89° 34' W. of the Section Corner Sections 24 and 25.

**RE-RENEWED, SEE CORNER NO. 138**

37

Closing Corner for Sections 23 and 24.

On the North line of Section 26, which is, also, an iron pipe witnessed by the original bearing trees which were:

- 28" Spruce, N. 20° E., 26.40 ft.
- 30" Hemlock, N. 23 1/2° W., 19.8 ft.

**RE-RENEWED, SEE CORNER NO. 137**

38

Standard Corner to Secs. 12 & 13 only, T20-12W.

Found - 1" Pipe and Old Post, from which:

- 70" Fir bears N. 51° E. 17.8 ft., old face chopped out, with tags.
- 40" Fir Shell bears S. 22° W. 6.9 ft.

Set - 2"x30" Iron Pipe with Brass Cap mkd: R12W T 20 S R11W

from which:

- 18" Spruce bears N. 18° W. 28.7 ft. scribed S12 R12 BT.
- 6" Spruce bears S. 20° W. 27.6 ft. scribed S13 R12 BT.

12		7
13		
		1970
		650

Set 1 fence post ± 5 ft. west facing north  
Placed the 1" pipe east of corner.

*Fd. ok 7/88  
D. Baker  
M106-67*

39

Warren D. Hootman  
For Crown Zellerbach Corp.  
Jan 30, 1963  
C.S. File No. 51/249, Map File 22-36

TOM O. McCULLOUGH  
For. U.S. Forest Service  
Feb. 1970  
C.S. File No. 55/142