

Douglas County Surveyor's Record of
Government Corners Renewed

T. 20 S. T. S. R. 12 W. R.W.W.M.

ROKE-CHAPMAN CO., EUGENE, ORE. 97101

45

John
J. Heritage
June, 1971
C.S. File 53/66

Section Corner to Sections 17, 16, 20, and 21.
Found - 1 1/2" I. pipe, badly rusted, at section corner. See C.S. 52/91
18" D. Fir, now 22" stob, S.67°E. 46.2 ft. Scribe visible
T.20S, R.12W S21. Opened BT scar for scribe "BT!" Very
old scribing.
1943 5' Spruce stump, S.22°E. 34.9 ft. to H.R. spike. #105
No trace of other nails set or original BT's.
Possible original Fir stump, N.63°W. 51.9 ft. (Rec. 48.2 ft.)
Set - Brass Cap along side I. pipe marked: County Surveyor's Office, 1971

RE-RENEWED, SEE CORNER NO.

T20S
S17 S16
S20 S21
R12W

New BT's: 7" Fir, S.31°W. 15.7 ft. scribed T20S R12W S20 CS BT.
No other trees available.

JAN 1972

6/16/71

46

1/4 Corner for Secs. 4 and 9.
Found - 1 1/2" I.P. set by W. G. Corbitt in April 1943
(Crown Zellerbach),
60" Spruce tump bears N.83°W., 25.3 ft. to old face
with spike, no scribing visible.
60" Spruce stump, bears S.83°E., 21.7 ft. to face with
scribing visible.
I remove Corbitt's iron pipe and it its place set:
a 2" x 36" concrete filled galvanized I.P. with 3"
brass cap fully stuamped from which I set:
New BT's-18" Spruce, bears N.13°E., 19.41. ft. to face scribed
"1/4 S4 BT".
18" Spruce bears S.4°E., 13.0 ft. to face scribed
"1/4 S 9 BT".

(SEE ALSO REN. #89)

47

Karl F. Foeste
for: Crown Zellerbach
Sparrow Pacific Corp.
U.S. Forest Service
November 25, 1974
M 49 - 80 and M 56 - 1
C.S. 58/25

1/4 Corner for Secs. 4 and 3.
Found - 1 1/2" I.P. set by Kruger in 1941 (Crown Zellerbach)
10" Hemlock, now a stump, bears S.10°E., 9.2 ft. to
face with portion of scribing visible.
Corbetts 22" Fir snag bears N.41°W., 27.2 ft. to nail
in face.
I remove Krugers I.P. and set:
a 2" x 36" concrete filled gal. I.P. with 3" Brass
cap fully stamped, from which I set:
New BT's-8" Hemlock bears S.62°W., 3.6 ft. to face scribed
"1/4 S 4 BT".
13" Hemlock bears S.51°E, 27.35 ft. to face scribed
" 1/4 S 3 BT".

RE-RENEWED, SEE CORNER NO.

#102

11/25/74

48

Center 1/4 of Section 3.
Set - a 2" x 36" concrete filled Galv. I.P. with 3" BRASS
cap fully stamped, from which I set:
BT's 24" Spruce bears S.88°W., 34.2 ft. to face scribed
"C 1/4 S 3 BT"
24" Spruce bears N.51 1/2°E., 35.2 ft- to face
scribed "C 1/4 S 3 BT".

RE-RENEWED, SEE CORNER NO.

#103

11/25/74

49

1/4 Corner for Secs. 4 and 5.
Found - Orig. SW BT scribed by H. Gordon in 1858. It is now
a 26" fir snag, but was called an 18" Pine in U.S.
notes. scribing is visible.
At record distance of 536.58 ft. and record bearing of N.2°45'E.,
from said BT:
I set - Flush a 2" x 36" concrete filled galv. I.P. with a 3"
brass cap fully stamped, from which I set:
New BT's-9" Pine bears N.45°W., 40.9 ft. to face scribed "1/4
S 5 BT".
10" Pine bears S.89°30'W., 27.8 ft. to face scribed
"1/4 S 5 BT".