

Douglas County Surveyor's Record of
Government Corners Renewed

T 20 T. S. R 12 R.W.W.M.

1/4 Corner for Secs. 3 and 10.

- Found - 1 1/2" I.P. set by Corbitt in 1943 (Crown Zellerbach)
 - Corbitt's 30" Cedar snag, bears S.4°W., 27.2 ft. to boat spike
 - Corbitt's 24" Cedar stump, brars N.16 1/2°E., 37.3 ft. to boat spike.
 - Doug. Co. BT 8" Alder, now dying, bears N.36"E., 8.6 ft. to scribed face Ren. No.43
 - Doug. Co. 13" Spruce bears S.24°W., 17.4 ft. to scribed face.

I remove Corbitt's I.P. and:

- Set - a 2" x 36" Concrete filled Galv. I.P. with 3" Brass cap fully stamped. from which I set:
- BT - 7" Spruce bears N.24°E., 34.1 ft. to face scribed "1/4 S 3 BT".

Karl F. [redacted]
for: Crown Zellerbach
Sparrow Pacific Corp.
U.S. Forest Service
M 49 - 80 and M 56 - 1
C.S. 58/25
11/25/74

50

1/4 Corner for Secs. 35 and 36.

- Opened old blaze on Hemlock & found scribe marks. Relocated corner.
- Set - 1 1/2" I.P. & 3"x3"x5 ft. Spruce post mkd: 1/4S S35/36 R.L.Follett W.G. Corbin Oct.14,'43.

- from which:
 - Orig. 16" Cedar, now 24" Hemlock snag, S.18°W., 9.24 ft. to nail, scribed 1/4.
 - 6 ft. Fir N.35°W., 9.25 ft. to nail, crayon mkd: RP BT 1/4 S35 RLF.
 - 6 ft. Fir, S.6°30'E., 43.7 ft. to nail, crayon mkd. RP BP 1/4 S36 RLF.
- This corner stands on side hill 40 ft. E. of small gulch & Krugur's Tined Line where cruiser Srotschy signed up at false corner, Dec. 4, 1942.

141

10/14/43

52

Meander Corner, Section 35 and 36.

Ran compass line N. Var. 21°30'E., to Lake line & distance came close to old Alder tree. Assuming it to be a BT, we relocated M.C.:

- Set - 1 1/2" I.P. & 2"x2"x2' White post crayon mkd: S35/36 9 + 66

- from which:
 - 24" Rotten Alder snag S.21°W., 15.48 ft. no marks.
 - 16" Alder N.81°E., 12.5 ft. to nail crayon mkd: RPBT 9 + 66 M.C. R.L.F.

This pipe stands 2.6 ft. W. of our compass line, Run N. from 1/4 Cor. 35/36. thus making true line N.0°9'W., 966.0 ft from 1/4 corner.

10/14/43

53

Section Corner for Secs. 13,14,23,24

Found orig. BT's as described. Since distance did not check with field notes I reset corner (not Frey's stake) with a 1 1/2" I.P. & 2"x2"x5' fir post crayon mkd: S14 S13 1943
S23 S24

from which:

- Orig. 30" Fir, now 36", N.4°E., 43 ft. to nail scribed S13 T20S BT is on root to east.
- Orig. 30" Fir, now 40", N.3°W., 52 ft. scribe mks. covered so could not reach the orig. face. Cruiser's mark V.
- 48" Fir, N.48 ft. stands btwn. other 2 Fir BT's.
- Orig. 36" Spruce, now 36" S.52°W., 29 ft. to nail scribed S23 T20S R12W. Most of scribe marks remain covered. The annual ring count shows this tree was scribed in 1857 so must be one of the BT's for the first corner established here. A 5 ft. Spruce bears S.31°30'W. 26.2 ft. to nail below old blaze.
- Orig. 6" Vine Maple S.23°E., 28.8 ft. to crack in trunk. Tree bent over.

This corner stands in gulch on N. side of ridge. Few trees around.

3/29/43

W. G. Corbitt
R. L. Follett for
Crown Zellerbach, 1943
C.S. 52/91

See Ren. #33
for 1963
Coener
Report

#110