

Douglas County Surveyor's Record of
Government Corners Renewed

T 20 T. S. R 12 R. W. W. M.

MOSE-CHAPMAN CO., EUGENE, ORE. 21991

Section Corner for Secs. 29, 28, 32 and 33.
Found - 60" Spruce with scribe marks standing for corner.
Set - 1 1/2" I.P. 2 ft. East of tree.
Found - 50" Spruce S W Iron marks
60" Spruce N E Iron Marks
50" Spruce N W Iron marks
70" Spruce S E
Corner stands on N.W. slope of hill, South of Lake Takhenitch.

1/21/41

75

Section Corner for Secs. 20, 21, 29 and 28.
Found - Post and marks as described. 3 ft. Spruce stump - NE 4 ft. stump -
NW 18" Spruce tree - SW hacked into but no scribe marks.
Doubtful if these are orig. BT's but everyone seems to have taken this for
corner which stands W. side of ridge 50 ft. E of Cat Road. Selective cutting
around here.
Set - 1 1/2" I.P. on top of 16" Spruce stump.

11/1941

76

1/4 Corner for Secs. 20 and 21.
Found - Orig. BT's North, scribes covered.
Reset - Corner with 1 1/2" I.P. & 2"x2"x6' Fir post crayon mkd: S20 / S21
W. G. Corbitt, April 13, 1943 from which bears:
Orig. 36" Spruce now 5 ft. Dbl. Fir, S.73°W., 5.28 ft. to nail
between scribe BT. Rest covered.
Orig. 24" Spruce, now 4 ft. N.10°E., 7.8 ft. to head of boat spike
protruding from root of tree. All scribes covered. Too much
to cut into.

4/13/43

77

Section Corner for Secs. 8, 9, 17 and 16.
Found - Bearing trees to corner.
Set - 1 1/2" I.P. using orig. field notes from which now bears 2 x 2 x 4 1/2
Spruce stake E. side of Pipe:
36" Spruce stump N.2°W., 16.5 ft. scribe rmrks. R12W
48" Spruce stump S.70°W., 6.0 ft. covered.
44" Spruce stump S.24°E., 20.5 ft. covered.
24" Spruce stump N.86°E., 44.2 ft. Rotten Face.

This corner is in logged land & has never been relocated. No cruisers marks
found. Corner stands on Ridge about 3 chs South of edge of swamp.

1/7/41

78

1/4 Corner for Secs. 9 and 16.
Found - Orig. BT's at 1/4 Corner. Never opened before. Relocated corner
by using given distances.
Set - 1 1/2" I.P. from which bears:
Orig. 12" Spruce N.78°W., 59.4 ft. scribed BT.
Orig. 90" Spruce tree S.22°W., 23.1 ft. scribed BT.
Put nail in each BT. Corner stands in draw west side of Main Ridge about
400 ft. W. of old Spar tree on Ridge.

11/13/41

79

1/4 Corner for Secs. 8 and 9.
Found - Orig. BT's and reset 1/4 Corner
Set - 1 1/2" I.P. from which bears:
Orig. 36" Spruce, now 48" at marks, S.62°E., 10.56 ft. to nail scribed
BT., rest covered.
Orig. 36" Spruce S.40°W., 7.92 ft. to nail, now 48" at marks,
scribed 1/4 S, rest covered.
Set - 2"x2"x6' crayon mkd 1/4 S8/S9, W.G. Corbitt, 1943.

4/5/43

80

Meander Corner, Secs. 26 and 35. Sec Ren # 60 for additional information.
Found - Orig. 30" Spruce BT. and from it reset M.C. information.
Set - 1 1/2" I.P. and 2"x2"x5' Fir post crayon mkd: 1943 S26 M.C.
S 35.
From which bears:
Orig. 30" Spruce, now 7 ft. stump S.18°E., 22.44 ft. to nail scribed
R 12, rest covered.
Had to cut through 14" of wood to find the inscription. Tough going, corner
stands 30 ft. above water.

4/29/43

81

RE-RENEWED CORNER NO. #106 & 44
RE-RENEWED CORNER NO. #104
RE-RENEWED CORNER NO. #132