

Douglas County Surveyor's Record of  
Government Corners Renewed

T 20

T. S.

R 12

R. W. W. M.

MOKE-CHAPMAN CO., EUGENE, ORE. 21881

82

Meander Corner, Secs. 27 and 26.

Found - Both BT's, opened up Hemlock & from it set M.C.

Set - 1 1/2" I.P. and 4x4x5 ft. Spruce post crayon mkd. S27/S26  
M.C. 1943

From which bears:

Orig. 5" Spruce (really a 30" Hemlock, dead) S.37°E., 6.60 ft. to  
nail scribed R12W, rest covered.

Orig. 48" Spruce, now 6 ft. N.55°W., 12.4 ft. to nail in overgrowth.  
Old scar and scribe marks not visible. This tree has sign  
on it. X on both lake & land side.

Corner comes on Spruce root notched for pipe 10 ft. above water.

4/29/43

Meander Corner, Secs. 16 and 15.

Found - 12" Spruce BT stump standing. The 25" Spruce was dead & down.  
Dug into rotten trunk and found old blazed face with scribe  
marks S15. Had to reset corner from 12" stump.

Set - 1 1/2" I.P. & 4x4x5 Post crayon mkd. S16/S15 M.C. 1943

From which bears:

Orig. 12" Spruce stump, now 14" N.27°W., 13.2 ft. nail scribed  
BT. rest covered.

40" Spruce stump, N.4°30'E., 9.3 ft. to nail, crayon mkd:  
MC RP BT.

Corner stands 2 ft. above water at this date in thicket of Huckleberry  
brush.

5/1/43

1/4 Corner for Secs. 9 and 10.

Found - Orig. 90" BT about 2653 ft. North of Sec. Corner, 9,10,16,15.  
There were no indications that it had ever been found since orig.  
survey. Relocated corner.

Set - 1 1/2" I.P. and 2x2x5 ft. Spruce post crayon mkd: S9/S10  
1/4S W.G. Corbitt, April 1943.

From which bears:

Orig. 90" Spruce, now only 6 ft. stump, S.77°W., 184.8 ft. to nail  
scribed 1/4, rest covered.

I mkd. - 6 ft. Spruce Stump S.18°30'W., 31.8 ft. to nail, crayon mkd.  
1/4 S RP BT.

Corner stands on small ridge course N. & S. slope to North, about  
40 ft. south of Cat Road. Stump mkd: X is too far East, no relation to crner.

4/14/43

1/4 Corner for Sec. 34 and Sec. 3 of T.21-12.

Found - Orig. Spruce BT with scribe marks. From it reset 1/4 Corner.

Set - 1 1/2" I.P. & 3x3x5 ft. Spruce post crayon mkd:  $\frac{S34}{S^3}$  1/4  
T20S R12W, T21S R12W, W.G. Corbitt, April 1943.

From which bears:

Orig. 30" Spruce stump S.44°E., 12.54 ft. to nail scribed  
1/4S BT marks are covered.

Orig. 18" Hemlock has been pulled out in construction of  
Cat Road.

I mkd: - 36" Spruce stump N.58°E., 27.4 ft. to nail in blazed face  
crayon mkd: 1/4 S34 RP BT.

NE corner about 25 ft. East of Cat Road.

4/2/43

Meander Corner for SEcs. 33 and Sec. 4, T21-12.

Found - Orig. 10" Fir BT and from it reset corner as 8" Fir is dead  
and down in the lake.

Set - 1/2" I.P. and 3x3x5 ft. Post crayon mkd: WCG  $\frac{S33}{S^4}$  M.C. 1943

From which bears:

Orig. 10" Fir, now 30" N.68°W., 31.68 ft. to nail scribed S33,  
rest covered.

5' Fir S.55°45'W., 28.3 ft. to nail crayon mkd. S4 RP BT.  
No cruisers mks. here.

4/26/43

W. C. Corbitt  
J. K. Elliott  
For: Crown Zellerbach  
1941 - 43  
C.S. 52/91