

Douglas County Surveyor's Record of
Government Corners Renewed

T 20 T. S. R 12 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97501

97

Richard J. Hintz
For: Champion Intern.
& International
ber
Ma 1980
M - 30
S. 58/140

Section corner for Secs. 35 and 36; and 2 & 1 of T.21-12
Found - Broken 1 3/4" I.P. lying on the ground (unrecorded) from which:
a 48" Fir stump bears N.78°E., 1.0 ft.
Set - Stamped 2" I.P. with brass cap from which:
14" Fir bears N.21°30'E., 35.0 ft. scribed.
48" Fir stump bears N.78°00'E., 1.0 ft.
22" Fir bears S.51°15'E., 40.3 ft. scribed.
12" Hemlock bears S.13°00'W., 40.2 ft. scribed.
10" Spruce bears N.50°30'W., 53.8 ft. scribed.
Note: This corner was tied in by a Bonneville power Admin. crew on
Dec. 2, 1948, at which time the I.P. was in place. The fir was
a green tree, but was erroneously called a spruce by the crew.
A copy of their field notes, Index No. A49-386A, may be obtained
by contacting John Sink, Dept. of Energy, P. O. Box 3621, Portland
Oregon, 97208.

NO. 142

98

1/4 Corner for Sec. 36; and Sec. 1 of T.21-12
Found - 2" Alum. pipe and 45" Cedar BT stump, Ren. #28, C.S. 51/311
Durham's new BT's are gone - probably destroyed during the sub-
sequent logging.
I Place - An alum. tag on a 36" Fir stump which bears S.47°W., 25.7 ft.
3/80

99

East 1/4 corner of Sec. 1.
Set - 2 1/2 " Brass Cap.
BT's - 12" Fir bears N.81°E., 32.5-ft.
14" Spruce bears S.35°E., 28.6-ft.
6/81

1/4 corner for Sec. 1 and Sec. 36 of T.19-12.
Set - 2 1/2 " Brass Cap.
BT's - 45" Spruce bears S.82°W., 63.6-ft.
14" Spruce bears N.53°E., 51.7-ft.
12" Willow bears N.17°W., 74.7-ft.
6/81

Fd 6/90
M 110-42

100

Center 1/4 corner of Sec. 1.
Set - 2 1/2 " Brass Cap
BT's - 24" Maple bears S.64°W., 30.8-ft.
12" Alder bears S.29°E., 20.2-ft.
9" Spruce bears N.40°E., 29.8-ft.
6/81

RE-... CORNER NO. #115

101

1/4 Corner for Sections 3 and 4.
Found - 2" I.P. with brass cap, 3" exposed. Ren. #47
Rotted hemlock stump, 12" dia., S.8°E., 10.2 ft. no marks
visible on blaze, but scribing visible on fragments. (Orig.)
13" hemlock, S.54°E., 27.9 ft. marked "1/4 S3 BT" and bark scribed
"C". (13" hemlock S.56°E., 42 1/2 lks. healed blaze, BLM)
12" hemlock, S.58°W., 4.1 ft. healed blaze. (12" hemlock, S.59 1/2
W. 6 lks. BLM)
24" snag, fir or hemlock, N.42°W., 28.2 ft. open blaze with
cruiser mark above it, apparently not a record tree.
Set - USFS 2 1/4" x 30" alum. pipe with a 3 1/3" alum. cap with
magnet attached under cap, bears N.51°21'W., 48.3 ft., 5"
exposed. Cap stamped "1/4 S4 RM S51°21'E 48.3 1985 LS 909".

102

Center 1/4 Corner for Section 3.
Found - 1982 BLM 2 1/2" alum. cap, 4" exposed.
26" spruce, N.79°E., 8.7 ft. marked "C 1/4 S3 BT". (26" spruce,
N.69°E., 13 lks. - BLM).
22" cedar, N.12°W., 12.1 ft. marked "C 1/4 S3 BT". (22" cedar,
N.19°W., 18 lks. - BLM).
Brass cap n an I.P. set by Foeste, bears N.50°56'W., 22.8 ft.
with 2 bearing trees. (Not tied) Ren. #48
Set - USFS alum. monument, N.58°39'E., 43.5 ft. 6" exposed. Cap
mkd. "C 1/4 S3 RM S58°39'W 43.5 1985 LS 909".

103

Perry Fox.
For: Davidson Industries
June 1981
M 88 - 13
C.S. 58 / 238 (N)

William Shull
LS #909
For: USFS
April 30, 1985
198 - 68