

Douglas County Surveyor's Record of
Government Corners Renewed

21 T. S. 4 R. W. W. M.

COR. BET. SECS. 31, 6 (F. B. 39 P. 17)

24.00' Set temp. stake distance, only
40.65 Intersect E & W $\frac{1}{4}$ random line at 41.94 chs.

80.83 Intersect Twp. line 38 lks. East

Find both trees one 316' E cut

Set corner and mark

A Fir 38 ins. diam., S.10°E., 49 lks.

RE-NEWED SEE CORNER NO. 50
5/4 S 31 10

F. J. Cole
Apr. 8, 1914
F.B. 39/17

CENTER SEC. 31

Return and set $\frac{1}{4}$ sec. corner in Sec. 31, 19 lks. W. of
random North and South through section, and 14 lks. North of
random East and West and mark:

A Cedar 4 ins. diam., N.71 $\frac{1}{2}$ °W., 31 lks.

A Fir 40 ins. diam., N.32°E., 3 lks.

A Fir 36 ins. diam., S.30°W., 38 lks.

A Fir 4 ins. diam., S.59 $\frac{1}{2}$ °E., 38 lks.

F.B. 39 P. 20 11
SET BY COLE-1914

$\frac{1}{4}$ COR. WEST SIDE SEC. 6

Reset from 40" Red Cedar N.43°W., 110² ft.

Marks plain. Drove 2 $\frac{1}{2}$ " x 30" auto spring from which a

30" White Fir Bears s.61°E., 23.5 ft.

RE-NEWED SEE CORNER NO. 39

F. C. Frear
N. E.
Richardson
B. A. Lane
J. L. Cline
Oct. 24, 1937

COR. SEC. 19, 20, 29 and 30

Corner in road. Set a 1 $\frac{1}{2}$ " x 30" I. Pipe 23 feet North of
true corner. Set Iron pipe S50° 77' ft. in old camp (no
marks visible) only probable witness tree. The corner
comes 39 feet north of creek and 594.4 ft. South of D.L.C.
line. Also later mark a 14" R. Fir S.62 $\frac{1}{2}$ °W., 32.5 ft. c.s. 15/12

RE-NEWED SEE CORNER NO. 28

4-1-1938
F. C. Frear
N. E. Richardson
B. A. Lane
Merl Clark
Farrell - Witness
March 1949

W. C. TO SEC. COR. 25-30-31-36 with cor. 15

Set 1 $\frac{1}{2}$ " x 72" G. I. P. for Cor. (in Pass Creek) Location determined from

O.B.T., 70" Cedar S 36° E 60 lks., down and dead.

Blazed and scribed new B. T.'s. SEE 2/30 COR # 24

14" Ash, S 65° W 66.0 ft., mkd. T 21 R 5 W 36 C.S.B.T.

15" Ash N 55° E 70.0 ft., mkd. T 21, R 4, S 30 C.S.B.T.

No trees available in Secs. 31 & 25.

RE-NEWED SEE CORNER NO. 14

Surv. A. R. Evans
Mt. R. Matthews
C. Blosser
F. F. Wolfer
Nov. 3, 1949

$\frac{1}{4}$ COR. 16-21

Found O. B. T. for $\frac{1}{4}$ cor, 30" Fir (now 42") N 5° W 37 lks.

Blaze very plain, scribe mark visible.

Set 2" x 60" iron pipe for $\frac{1}{4}$ cor from which

20" Cedar bears N 65° E 32.0 ft., blazed and scribed

$\frac{1}{4}$ S - 16 - C.S. - B.T.

42" Douglas Fir bears S 53° E 50.5 ft., blazed and scribed

$\frac{1}{4}$ S - 21 - C.S. - B.T.

RE-NEWED SEE CORNER NO. 81

Nov. 3, 1949

COR. BET. 16-21

Found O. B. T., 30" Fir (now 42") N 5° W 37 lks. Blaze very plain, scribe
mark visible. Set by H. Eppstein, Deputy County Surveyor

Set 2" x 72" iron pipe for corner from which

20" Cedar bears N 65° E 32.0 ft., blazed and scribed $\frac{1}{4}$ S-16-C.S.B.T.

42" Doug. Fir bears S 53° E 50.5 ft. blazed and scribed $\frac{1}{4}$ S-21-C.S.B.T.

RE-NEWED SEE CORNER NO. 10