

Douglas County Surveyor's Record of
Government Corners Renewed

T. 21 S. T. S. R. 4 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Section Cor. to Secs. 31 & 32, T21-4W. & Secs. 5 & 6, T22-4W. 51
Found - Old Fir Stump, now 42", N.60°E. 52.8 ft., traces of old bark scribing, probably 50 years old or more. "CS" is all that is legible. Believe this to be the Orig. N.E. BT. which was later bark scribing

No trace found of the other 3 Orig. BT's.
Fir tree approx. 10 ft. North of Cor. has N. & S. line blazes approximately 20 years old.

Set - Brass Cap at Cor. Mkd: County Surveyor's T21S R4W S31 | S32
Office, 1962 T22S S 6 | S 5

Milo E. Godfr
and Crew
Sept. 1962
C.S. File
No. 49/42

New BT's: 14" W.Fir N.32°E. 18.0 ft. Mkd: T21S R4W S32 CS BT.
18" D.Fir N.50°W. 15.3 ft. Mkd: T21S R4W S31 CS BT.
9" W.Fir S.30°E. 30.8 ft. Mkd: T22S R4W S5 CS BT.
13" D.Fir S.17°W. 58.4 ft. Mkd: T22S R4W S6 CS BT.
A Fence Corner - Fences West & S.E., bears S.65°W. 4.5 feet.

C.S. 49/42

1/4 Corner to Sections 31 and 32.

Found - 10" Fir S.29 1/2°E. 101 lks., now stump - REN.#1 52
24" Cedar N.18°E. 104.6 ft. (not 140 lks.) now stump.

Set - 1" x 1" x 36" T. Iron by using bearing and dist. to
10" Fir and bearing only to 24" Cedar, scribed 2 New BT's.

New BT's: 8" Fir S.30°E. 38.3 feet, scribed, alive & standing.
8" Fir N.53°W. 31.7 ft., uprooted & down., probably blown over in October 1962 Storm.

Note by Milo Godfrey - My point for corner, assuming 20 lk. error in Cole's notes, falls S.85°W. 1.8 feet from Haines' "T" Iron. April 23, 1963. See Notes in C. S. File 51/247

Wilford N.
Haines
For Glenn C
Nov. 1962
C.S. File
No. 51/247
H-65

Section Corner to Secs. 1 & 12, T21-4W. & Secs. 6 & 7, T21-3W. 53
Found all BT's. cut down & post gone.

Set - Stone 18 x 18 x 10 marked with 1 notch on North and 5 notches on South sides & CS from which:

An Oak 5" diam. bears N.74°E. 27 lks. dist. mkd: CS S6 BT.
An Oak 4" diam. bears N.85°W. 40 lks. dist. mkd: CS S1 BT.

The stumps of the orig. trees all showing some of the marks have the correct bearings & distances as originally notes.

9/17/1895

1/4 Sec. Cor. on line betwn. Sec. 1, T21-4W. & Sec. 12, T21-4W. 54

Found - Stub of N.W. BT, nearly burned up. Slight traces of mks. vis.
Stump of SW. BT., cut down, slight traces of marks visible.

Set - Stone 19 x 14 x 10 ins. mkd. 1/4 on N. face & CS from which:
Said remains of Orig. BT's. have correct bear. & dist. and
18" Fir bears S.61°E. 3 lks. dist. mkd: 1/4 S CS BT.
18" Fir bears N.61°W. 11 lks. dist. mkd: 1/4 S CS BT.

9/20/1895

1/4 Sec. Cor. Bet. Sec. 12, T21-4W. & Sec. 7, T21-3W. 55

Found - Post gone & both BT's. cut down. Stumps still showing lower marks.

Set - Stone 24 x 12 x 12 ins. mkd. CS from which:
40" Fir bears N.52°W. 71 lks. dist. Mkd: CS BT.

(9/20/1895

1/4 S. Corner on line bet. Sections 12 and 13. 56

Found - Post & both trees gone. Stump of W. Oak 10" diam. when mks. bearing N.69 3/4°W. 18.41 chs. dist., still showing plain the lower marks BT. Also there is a little pile of stone at the spot shown by said BT. which Ira Hawley says he put exactly where the post stood.
Also there is a stump of a W. Oak 12", S.30 1/2°E. 10.90 lks. distant. No marks remaining.

Set - Stone 12 x 13 x 10" marked C.S.

May 4, 1897

C. M. Collier, County Surveyor
For Wit. present, see file
1895 and 1897
C. S. File No. 53/1