

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 21 S. T. S. R. 4 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

C. M. Collier,  
Lane County Surv.  
C. S. File  
No. 53/1

57  
South S.W. Corner of the Ira Hawley D.L.C. No. 38.  
Found - Post & both trees gone. Stump of 24" Fir bearing S.46°E. 417 lks.,  
mkd. with BT. still showing under several inches growth of wood.  
The other tree lost, though there is a fir fallen which stood  
S.5°E. 333 lks. dist. about 24" diam. at that time.  
Set - Stone 24 x 12 x 10" marked C.S.

May 6, 1897

A.D. Collier,  
Lane Co. Dep.  
C.S. 53/1

58  
N. E. Corner Section 2, T21S R4W.  
Found - 20" Fir S.14°W. 50, standing O.K. Also, the "redwood" cedar 40"  
S.20°E. 53. Fd. stump of Fir 30" N.55°E. 90. Other fir gone.  
Set - Post CS and new Fir 6" N.56°E. 9 lks. and 6" Fir N. 17 lks. CS BT.  
June 4, 1912

59  
 $\frac{1}{4}$  Corner between Sections 13 and 14.  
Found - Old Post Gone. Old BT, a Fir 15" N.60°E. 164 lks., Cut down.,  
Found figure  $\frac{1}{4}$  S in stump. No trace of old BT, a fir 18" S.80°W.,  
120 lks.  
Marked Fence Post  $\frac{1}{2}$  round 10" diam. on flat side 7" high for corner CS.  
from which: 9" Fir bears S.80°E. 26 lks. marked C S B T  
11" Fir bears N.40°W. 36 lks. marked " "

Oct. 5, 1932

60  
Section Cor. to Sections 1, 2, 11 and 12.  
Found - Old Post gone. Old BT., a 36" Fir N.45°W., cut down for  
saw logs. No fig. Old BT, a 60" Fir N.80°E. 73 lks., gone,  
stump standing. No figures. Old BT., a 40" Fir S.30°E. 41 lks.,  
cut down, with fig. BT. in lower spot. Old BT, a 36" Fir S.60°W.  
51 lks., burned down; no figures.

Marked fence Post C.S. from which:  
9" Fir bears S.23 links. Mkd: C S B T.  
12" Fir bears S.88°W. 94 links. Mkd: C S B T.

Oct. 8, 1932

61  
 $\frac{1}{4}$  Corner bet. Sections 11 and 12.  
Found - Old Post gone - Old BT, 10" Oak S.34°E. 162, standing in fir  
thicket and in poor condition, upper spot rotten, no figure visible, dist. O.K.  
Old BT, 20" Fir N.86°W. 61 lks., cut down, fig.  $\frac{1}{4}$ S in upper spot.  
Marked Stone 10" x 12" x 16" C.S. for corner from which:  
10" Fir bears N.20°E. 28 links; 40" Fir bears S.40°W. 74 lks. mkd. CSBT.

Oct. 8, 1932

62  
N. W. Cor. of the Ira Hawley D.L.C. No. 38.  
Found - Old Post gone. Old BT., 7" Oak S.50°W. 87 lks., gone with stump  
standing with fig. B.T. in lower spot. No traces of old BT.,  
an Oak 18" S.50°E. 54 links.

Set - Stone 10" x 10" x 10" Mkd: C.S. for corner. No trees convenient.  
Oct. 8, 1932

63  
 $\frac{1}{4}$  Section Corner bet. Sections 24 and 25.  
Start at NE corner of Sec. 25; run S.89°21'W. 5330.5 ft. to the  
N.W. cor. of said Sec. 25. At a point halfway between said Sec. Cors.,  
find old stump of 24" Fir when scribed, now 40"; chopped out lower part of  
stump and find "B" plainly visible. From this BT. at a point N.40°W. 16.5',  
SET - 2" Iron Pipe 48" Long. and Mkd:  
50" D. Fir bears North 17°E. 20.0 ft.  
17" D. Fir bears S.20°E. 26.5 ft.  
From this point the NE cor. of Sec. 25 bears N.89°20'E. 2671.35 ft. and  
the NW cor. of Sec. 25 bears S.89°22'W. 2659.15 ft.

Harvey Taylor, Deputy County Surveyor, Lane County  
Howard Taylor, present  
October 1932  
C. S. File No. 53/1

Gilbert A Gardner  
Robert Barta, wit.  
Dec. 16, 1953  
C.S. File No. 53/1

OVER