

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 21 S. T. S. R. 4 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 31881

73

$\frac{1}{4}$  Corner to Sections 32 and 33.  
Found - 28" Fir N.48°E. 6.6 ft., cut open & fd. good scribing "3 CS".  
Old Fir Stump S.33°W. 5.9 ft., no marks found, bark gone on NE face.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964  
T21S R4W  $\frac{1}{4}$  S 32/S 33  
New BT's: 9" Red Cedar N.73°E. 15.3 ft. Mkd:  $\frac{1}{4}$  S33 CS BT.  
10" D.Fir S.78°W. 39.6 ft. Mkd:  $\frac{1}{4}$  S32 CS BT.  
Note - Corner is in 3-Way Fence Corner, fences E., W., & N. See Ren. #37.

74

$\frac{1}{4}$  Corner to Sections 30 and 29.  
Found - Incense Cedar, now 32", N.62 $\frac{1}{2}$ °W. 47.5 ft., opened & found fragmentary,  
but unmistakable scribing, on badly, rotted old face.  
Did not find Cole's other BT., nor eith Orig. BT. See Ren. # 2  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964  
T21S R4W  $\frac{1}{4}$  S 30/S 29  
New BT's: 9" D.Fir S.64°E. 22.8 ft. Mkd:  $\frac{1}{4}$  S29 CS BT.  
13" White Fir S.64°W. 12.4 ft. Mkd:  $\frac{1}{4}$  S30 CS BT.  
Note - Fence Corner - fences N., S., & W., bears N.52°E. 5.0 feet.

75

Sec. Cor. Secs. 32 & 33, T21-4W. & Sec. 5 & 4, T22-4W.  
Found - Small Fir Snag N.7 $\frac{1}{2}$ °E. 15.2 ft., scribing visible on badly  
rotted exposed face, "T21S R4W S33", BT scar visible,  
See Ren. #36. No other BT's. found.  
Set - Brass Cap at Cor. Mkd: County Surveyor's R4W T21S S32 | S33  
T22S S 5 | S 4  
New BT's: 9" D.Fir N. 2°E. 89.6 ft. Mkd: T21S R4W S33 CS BT.  
17" D.Fir N.25°W. 12.0 ft. Mkd: T21S R4W S32 CS BT.  
7" Hemlock S.72 $\frac{1}{2}$ °W. 24.8 ft. Mkd: T22S R4W S5 CS BT.  
No other trees convenient S.E. of Corner.

76

$\frac{1}{4}$  Section Corner to Sections 29 and 32.  
Found - Orig., badly rotted Fir Stump N.47°W. 35.6 ft., faint scribing  
"BT" on old face.  
No trace of S. W. Tree.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T21S R4W  $\frac{1}{4}$  S29  
Office, 1964 S32  
New BT's: 11" White Fir S.80°W. 43.0 ft. Mkd:  $\frac{1}{4}$  S32 CS BT.  
18" D.Fir N.2 $\frac{1}{2}$ °W. 41.4 ft. Mkd:  $\frac{1}{4}$  S29 CS BT.  
Note - Fence Corner, fences North & West, bears S.19°W. 24.0 ft.

77

Wit. Cor. to Secs. 30 & 31, T21-4W. & Secs. 25 & 36, T21-5W.  
Found - 1 $\frac{1}{2}$ " Iron Pipe on bank of Pass Creek. See Rens. #14 & #24.  
Ash Tree N.55°E. 70.0 ft., scribing visible on open face, Tree dead.  
14" Maple S.66°E. 65.2 ft., shows scars. This tree across  
Pass Creek from corner.  
Dead Ash Tree S.65°W., appears to be approximately correct dist. in  
thick blackberry jungle. Distance not measured.  
Reblaze & Scribe - 14" Maple S.66°E. 65.2 ft. Mkd: T21S R4W W.C. S31 CS BT.  
New BT's: 18" Alder S.6°W. 65.8 ft. Mkd: T21S R5W WC S36 CS BT.  
(Alder is across creek from corner, scribed 5 ft. high.  
No other trees available.

FD BC  
BY Riley  
10/93  
M117-7

O.F. Thiel MKD BT'S IN  
1904 - See C.S. 64/48  
P68

78

$\frac{1}{4}$  Corner to Section 31, T21-4W. & Secs. 36, T21-5W.  
Found -  $\frac{3}{4}$ " Iron Pipe, top approx. 12" above ground. (See Ren. #12, T21-5W)  
20" Fir Stump N.14 $\frac{1}{2}$ °E. 37.9 ft. (to face) good scribing visible.  
24" Fir Stump N.10 $\frac{1}{2}$ °W. 84.6 ft., good scribing visible "BT".  
DID NOT SET BRASS CAP.  
New BT's: 16" D.Fir S.87 $\frac{1}{2}$ °W. 29.4 ft. Mkd:  $\frac{1}{4}$  S36 CS BT.  
5" W. Fir S.83 $\frac{1}{2}$ °E. 18.0 ft. Mkd:  $\frac{1}{4}$  S31 CS BT.  
An old fence corner, fences N. & E., bears N.40°W. 8 feet.  
Corner is approx. 300 ft. south of Power Line.

Oct. 27, 1964

Township Corner -

T21S  
S 36 S 31

Milo E. Godfrey, Deputy Co. Surveyor  
Wm. Steffel & Mike Stone  
October 1964  
C. S. File No. 49/68

RENEWED CORNER NO. #149