

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 21 S. T. S. R. 4 W. R. W. W. M.

MOKE-CHAPMAN CO., EUGENE, ORE. 21881

85

$\frac{1}{4}$  Section Corner to Sections 20 and 21.  
Found - Fir Stake set by Bayles, 1953, & Red Painted Broom handles  
North & East of Corner. See Ren. #21 & Map of Bayles'  
job in C. S. File No. 41/183.  
No trace of Original BT's.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964  
T21S R4W  $\frac{1}{4}$  S 20/S 21  
New BT's: 12" D.Fir N.15°W. 7.0 ft. Mkd:  $\frac{1}{4}$  S20 CS BT.  
18" D.Fir S.39°E. 36.0 ft. Mkd:  $\frac{1}{4}$  S21 CS BT.

*FD. OK. by W. Elmstad  
OCT. 1981 M 89-25*

86

Section Corner to Sections 16 - 17 - 20 - 21.  
Found - 36" Fir S.15°E. 19.8 ft., opened & found good scribing, "S".  
Rotten remains of Fir Stump S.19°W. 41.6 ft.  
No trace of N.E. or N. W. BT's.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964  
T21S R4W 

S17	S16
S20	S21

  
New BT's: 7" D.Fir S.43 $\frac{1}{2}$ °W. 25.7 ft. Mkd: T21S R4W S20 CS BT.  
14" D.Fir S. 8° E. 60.5 ft. Mkd: T21S R4W S21 CS BT.  
20" D.Fir N.55°W. 45.5 ft. Mkd: T21S R4W S17 CS BT.  
42" D.Fir N.31°E. 59.0 ft. Mkd: T21S R4W S16 CS BT.  
Note - Corner is in E. and W. Fence Line 2 ft. West of Fence Corner.

*FD OK PER PEEL  
APRIL-87 M104-12  
M 105-50 (CS 43/17)*

*FD. OK 12/91  
L. ROBERTS  
M 115-33*

87

Sec. Cor. to Secs. 18 & 19, T21-4W. & Secs. 13 & 24, T21-5W.  
Found -  $\frac{3}{4}$ " I.Pipe - See Ren. No. 5. -T21-4W  
23" Fir S.48 $\frac{1}{2}$ °E. 34.3 ft., prev. opened, good scribing visible on face  
Fir Stump N.71 $\frac{3}{4}$ °W. 129.0 ft., scribing visible "T21", rest illegible.  
New BT's: 27" D.Fir S.32 $\frac{1}{2}$ °E. 37.4 ft. Mkd: T21S R4W S19 CS BT.  
12" D.Fir N.69 $\frac{1}{2}$ °W. 133.2 ft. Mkd: T21S R5W S13 CS BT.  
No trees near to S. W. or N. E.  
Note - Corner is approx. 1 foot south of E. & W. Fence Line. 102

88

$\frac{1}{4}$  Corner to Sec. 30, T21-4W. & Sec. 25, T21-5W.  
Found - Old Fir Stump S.37°W. 54.1 ft., cut open & found good scribing.  
38" Old Fir Stump S.20°E. 16.5 ft., shows very good scar.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964  
T21S R5W  $\frac{1}{4}$  S 25/ S 30 R4W.  
New BT's: 11" D.Fir S.78°W. 6.8 ft. Mkd:  $\frac{1}{4}$  S25 CS BT.  
12" D.Fir S.54°E. 3.3 ft. Mkd:  $\frac{1}{4}$  S30 CS BT.  
Notes - Remnants of old fence lines extend north & east from corner.

*FD. 2/81  
R. KIMBLE  
M 79-69*

89

$\frac{1}{4}$  Corner to Sec. 2, T21-4W. & Sec. 35, T20-4W.  
(North  $\frac{1}{4}$  Corner to Section 2)  
Found - No trace of 1854 Post.  
12" Fir N.10°E. 42 lks. 27.7 ft., stump hole. 96  
12" Redwood S.29°E. 30 lks., 19.8 ft., decayed wood, Cedar.  
Survey Record, Lane Co., Aug. 1900. Old post gone. Found stump of 12" Red  
Fir. When marked bearing N.10°E. 43 lks., showing old face. Also  
fallen trunk of old "Redwood" Cedar 12" S.29°E. 30 lks.  
Set post from which: 8" Fir N.17 $\frac{1}{2}$ °W. 38 lks. 25.8 ft. Found 17" standing  
Fir with 2 faces. Chopped out upper face, found scribed "S 33 $\frac{1}{4}$  CS".  
The "33" in error, should have been "35".  
4" Fir S.30°E. 29 lks. 19.1 ft., now 21" stump, chopped out & found  
"BT". Found long butt & chopped out negative "S2".  
Set Iron Pipe & Cedar Post, set by dist. & bear. from 1900 Co. Survey BT's.  
New BT's: 17" Fir N.17°W. 24.4 ft., Orig. BT. Added "W" nail & Plate.  
10" Fir S.36°E. 39.6 ft., add "W" Nails & Plate.

90

Section Corner to Sections 4 - 5 - 8 - 9.  
Found - 10" Fir N.15°E. 19.8 ft., gone.  
12" Fir S.12°E. 11.2 ft., now 16" Fir Stump 12' high. Upper face  
open & badly burned. Scribing visible. Chopped out lower scar and  
found "BT" scribing.  
7" Maple S.14°W. 17.8 ft., gone.  
15" Fir N.73°W. 18.5 ft., fd. stump hole & 24" fir slid 15' downhill.  
Set - 10" x 10" x 18" Basalt Stone

93

(continued over)

Milo E. Godfrey, Deputy Co. Surveyor  
Wm. Stoffel & Mike Stone  
November 1964  
C. S. File No. 49/68

Weyerhaeuser Company  
By Glen McChesney  
Nov. 1959  
C. S. File No. 53/104 Pages 2 & 3.

RE-RENEWED CORNER NO.

RE-RENEWED CORNER NO.

RE-RENEWED CORNER NO.