

Douglas County Surveyor's Record of  
Government Corners Renewed

T 21 T. S. R. 4 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

R. E. Stuntzner  
for: Reservation  
Ranch  
Oct. 8, 1974  
C.S. 58/10

1/4 Corner for Sections 21 and 28.  
Found no evidence of original 1/4 Corner.  
Set - 1/2" Iron pipe at proportionate distance from which:  
S.W. Corner of a cabin bears N.23°E., 5.8 ft.  
10" Maple bears N.77°W., 14.1 ft.  
20" Fir bears N.78°E., 35.2 ft.

114

JAN 75

Vic Cangie  
Michael Tompkins  
Co. Surveyors  
Office  
Oct. 26, 1976  
C.S. 59/24

1/4 Corner for Secs. 2 and 11. See also Ren. #16  
Found - 3/4" pipe 8" above ground not of record.  
Three corner posts lying beside pipe.  
Found no trace of bearing trees.  
BLM location poster on 16" Fir, 5 ft. NE of pipe.  
Note: Pipe lies on old East-West blazed line and the pipe if not of record.  
WE DO NOT SET CORNER FOR LACK OF EVIDENCE.

115

Gary Langlitz  
A. Vic Cangie  
M.L. Tompkins  
Co. Surveyors  
Office  
Oct. 27, 1976  
C.S. 59/24

1/4 Corner for Secs. 10 and 11. See also Ren. #17  
Found - A wooden post set by Herm Pieske for Sun Studs. It was set at the intersection point of an E-W and N-S fence line.  
36" Cedar, down and rotted. No trace of scribing or blaze.  
21" Maple, alive but rotted through the face and middle of the tree. No trace of scribing.  
No trace of orig. corner post.  
WE DO NOT SET THE CORNER FOR LACK OF EVIDENCE.

116

3-77

JAN 78

JAN 78

Ronald Quimby  
L.S. #1654  
For: Revestco  
Sept. 1979  
M 79 - 7

Center 1/4 Corner for Section 29  
Set - 5/8" Iron rod  
BT's - 4" Fir bears S.46°E., 14.4 ft. scribed C 1/4 S29 BT.  
8" Fir bears N.16°W., 6.0 ft. scribed C 1/4 S29 BT.

117

1/4 Corner for Secs. 29 and 28  
Set - 5/8" Iron rod  
BT's - 12" Hemlock bears S.66°W., 6.5 ft. scribed 1/4 S29 BT.  
24" Cedar bears N.56°E., 4.0 ft. scribed 1/4 S28 BT.

118

(B.N.W. ENC. DESTROYED CORNER)  
FO. OK 7/95 BY ROBERTS M122-43

1/4 Corner for Secs. 27 and 28  
Found - 24" Fir Snag on ground and stub in ground bears S.81°E.  
9.24 ft. scribed "1/4 S2"  
Set - 5/8" x 30" rebar for corner  
BT's - 12" Fir bears N.60°E., 39.9 feet scribed "1/4 S27 BT"  
7" Incense cedar bears N.7°W., 28.4 feet scribed "1/4 S28 BT"

119

Eimstad & Associates  
William A. Eimstad LS#377  
For: Charles Booher  
Dec. 1979  
M 82 - 14

1/4 Corner for Secs. 28 and 33  
Set - 3/4" Rebar  
BT's - 17" Fir bears N.71°E., 70.7 ft. scribed "1/4 S28 BT".  
16" Fir bears S.44°W., 7.9 ft. scribed "1/4 S33 BT".

120

Note - This 1/4 corner proportioned in by survey M 82 - 14.

Center 1/4 Corner Sec. 28  
Set - 5/8" Re-bar.

121

Note - Set by proportionate measurement.

William Eimstad  
For: Charles Booher  
Dec. 1979  
M 82 - 14

1/4 Corner for Secs. 29 and 28.  
Set - 3/4" re-bar  
BT's - 16" Fir, N.46°W. 17.95 ft. scribed 1/4 S29 BT.  
8" Fir, N.26°E., 14.3 ft. scribed 1/4 S28 BT.

122

(See also void corner #118 M79-7 & Co. notes in C.S. 61/6)

12/79