

**Douglas County Surveyor's Record of  
Government Corners Renewed**

T. 21 S    T. S.    R. 4 W.    R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Gary T. Johnston  
P.L.S. # 1467  
June 16, 1986  
M 102 - 14

1/4 CORNER SECS. 9-10. 132  
Corner set by proportion, original not found.  
Set: 5/8" x 30" Iron rod 26" in ground with 1 1/4" plastic cap stamped "Willamette Industries Inc."  
New  
BT'S: 6" Douglas Fir bears N 84° W, 10.5 ft. to the face Mkd. "1/4S 9 BT."  
12" Douglas Fir bears S 66°E, 15.9 ft. to face mkd. "1/4 S10 BT".  
Note: Painted faces orange. Placed Willamette Ind. Yellow bearing tree tags on both trees. Set white fiberglass post 1.0 ft. South of corner.

*FO. OK, 5/96 BY BRADSBY-M123-76* 133  
Section Corner common to Sec's 7,8,17 and 18.  
Found: Douglas County (1969) brass cap. Ren # 107.  
BT'S : 10" Fir bears S 34°E, 17.5 ft.  
50" Fir bears S 23°W, 13.3 ft.  
8" Fir bears S 86°W, 7.8 ft.  
9" Fir bears N 72 1/2° W, 9.7 ft.  
New BT: A 10" Fir bears N 74°E, 28.2 ft. to "W" nail, "Sec. 8 BT".

Section corner for sec. 17,18,19 and 20. 134  
Found: Douglas County (1968) brass cap. Ren #99  
Bt's : 22" Fir bears N 82 3/4° E, 26.9 ft.  
30" Fir bears S 66 1/2°E, 17.9 ft.  
22" Fir bears S 43 1/2°W, 51.9 ft.  
New BT's 16" Fir bears N 72 1/4°W, 10.7 ft to "W" nail, "SE Cor. S 18 BT".

Center 1/4 Section 19. 135  
Found : A 1" Aluminum pipe. Ren # 43.  
: 27" Fir bears S 84°E. 56.4 ft.  
14" Fir snag bears N 46 1/2°W, 103.0 ft.  
52" Fir stump bears S 86 3/4°W, 66.4 ft.  
New Bt's: 7" Fir bears N 87°W, 1.6 ft. to "W" nail, "C 1/4 BT".

West 1/4 Corner for Section 18 and Sec. 13 of T21-5. 136  
Set : 1" x 36" Iron Pipe with cap stamped "Guile PLS 472".  
Found : 3/4" Iron Pipe bears S 75°20'46"W, 23.74 ft.  
New Bt's 18" fir bears N53 1/2°W, 8.8 ft to "W" nail, "E 1/4 S 13 BT".  
19" Fir bears N 86 3/4°E, 14.2 ft. to "W" nail, "W 1/4 S 18 BT".

Center 1/4 Corner Section 18. 137  
Set - 1" x 36" Iron Pipe with cap marked " Guile PLS 472".  
New  
Bt's - 28" Fir bears N 54 3/4°E, 47.4 ft. to "W" nail, "1/4 WT".  
16" Fir bears S 34 1/4°E, 31.0 ft. to "W" nail, "1/4 WT".

East 1/4 Corner for Sec. 2 only. (Lane County)  
CORNER REPORT ONLY 138  
Found - 1979 Lane County Brass cap  
11" fir, N.60°W., 23.4 ft.(cen) with healed blaze.  
19" yew, N.15 1/2°W., 12.1 ft. (cen) with "CSBT" showing.  
42" fir stump, N.48°W., 10.8 ft. with scar  
A stone, 6"x9" bears North 0.50 ft. marked "1/4".  
Fence corner N, E < W bears East 1.50 ft.

*FO OK 10/94 M120-70* 139  
Center 1/4 Corner for Section 2  
Set - 1" x 36" iron pipe with cap  
BTs - 10" fir bears N.40°W., 19.8 ft. to "W" nail scribed "C 1/4 BT".  
10" fir bears S.63°W., 18.1 ft. to "W" nail scribed "C 1/4 S2BT"  
A fence corner bears N.54°47'E., 39.4 ft. fence runs E,W & N.  
*FO OK 10/94 - M120-70*

Charles W. Guile  
For: Weyerhaeuser Co.  
November 17, 1986  
M 103 - 9  
C.S. 63/45(n)

*FWD OK 12/91  
D PEEL M 114-41*

Charles W. Guile  
For: Weyerhaeuser  
Feb. 27, 1987  
M 103 - 68  
C.S. 63/45