

Douglas County Surveyor's Record of
Government Corners Renewed

T 21 T. S. R 4 R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE. 91881

162

Section Corner for 35 and 36; 2 & 1 of T.22-4
Found - 3 1/4" dia. BLM brass cap on a 2 1/2" O.D. iron pipe protruding 7" above ground. (1958 BLM)
8" now rotted D.Fir stump of indeterminate size, no marks visible, bears N.11°E., 46.9 ft. (agrees w/rec.) Orig. BT.
20" now 18" dia. 2 1/2' high rotted D.Fir stump, no marks visible, bears S.62°E., 79.2 ft. (agrees w/rec) Orig. BT.
56" I.Cedar BT noted as not of record in 1958 BLM survey is gone (Road construction)
29" dia. D.Fir with a fully healed double blaze, and a "W" nail driven through the center of a 3" dia. bronze disk marked "Reg. Engineer No. 2149" bears S.65 1/2°E., 6.6 ft. (agrees with 1958 BLM record) Wey. BT)
60" dia. 25 ft. high I.Cedar snag, bears S.7°E., 29.5 ft. (Rec. S.4 1/2°E., 25.7 ft. 1958 BLM) (No "W" nail found) Wey. Co. BT.
32" dia. D.Fir with a fully healed single blaze and a "W" nail driven through the center of a 3" dia. bronze disk marked "Reg. Engineer No. 2149" bears S.69°W., 42.2 ft. (agrees with record) Wey. Co.
26" dia. D.Fir with a fully healed single blaze and a "W" nail driven through the center of a 3" dia. bronze disk marked "Reg. Engineer No. 2149" bears N.54°W., 12.2 ft. (agrees with 1958 BLM) Wey. Co.
12" now 31" dia. D.Fir with a fully healed single blaze, bears N.77 1/2°E., 73.9 ft. (Rec. N.79 3/4°E., 73.9 ft.) 1958 BLM BT
16" now 24" dia. tipped out D.Fir with a fully healed single blaze, root hole bears S.74 1/4°E., 44.9 ft. (agrees w/rec) 1958 BLM
7" now 12" dia. 7 ft. high cedar snag with an open blaze, scribing visible, "T22S R4W" bears N.79°W., 38.6 ft. (Rec. N.80°W., 38.6 ft.) 1958 BLM BT
12" Fir bearing N.27°W. in 1958 BLM is gone.

Douglas County
Surveyors Office
Randall Smith
Stephen Flause
November 18, 1991
C.S. File 64/21

11/18/91

163

1/4 Corner for Sec. 34, and Sec. 3 of T.22-4.
Found - U.S.B.L.M. Brass cap dated 1980. Condition report only
17" White fir, N.2 1/2°E., 47.5 ft. to spike - visible scribe record: North, 47.5 lks. (1980 BLM)
20" White fir, S.14 1/2°E., 44.8 ft. to spike - closed face record: S.18 1/2°W., 70 lks. (1980 BLM)
Note - Spikes were set this survey at side center.

FD OK, 1/4/96 D. BAKER, M124-4

Section Corner for 33, 34 & 3, 4 of T.22-4

Found - U.S.B.L.M Brass cap dated 1980.
13" Cedar, N.56°E., 19.7 ft. - closed face record: N.56°E., 30 lks. (1980 BLM)
9" Cedar, S.53 1/2°E., 18.0 ft. - closed face record: S.53 3/4°E., 27 lks. (1980 BLM)
15" Fir, S.56°W., 29.5 ft. - closed face record: S.55 1/2°W., 45 lks. (1980 BLM)
8" Fir, N.33 3/4°W., 38.7 ft. - down and out. record: N.33 1/2°W., 59 lks. (1980 BLM)

New BT- 7" Fir, N.52°W., 8.5 ft. to "W" nail

scribed "T21S R4W S33 BT"
FD OK, 1/4/96 D. BAKER, M124-4

164

1/4 Corner for Secs. 10 & 11

Found - 44" Fir Stump, S.45°W. 40.3'. (Scar Vis) No scribing found. See Ren. #17 in T21S R4W. (Rens #17 & 116)

Corner Falls on old N-S fence line.

Set - A 4"x 4" square cedar post, bears N.15°E., 8.5'.
5/8"x 30" iron pin with yellow plastic cap stamped "ROBERT P.L.S. 1039"
4" W.Fir, N.42°E., 29.7', (Scribed/painted Red)
12" Fir, S.4°W., 15.0', (Scribed/painted Red)
12" Maple, S.84°E., 45.5', (Scribed/painted Red)
14" Maple, N.23°W., 22.0', (Scribed/painted Red)

165

Les Roberts
For: Willamette
Industries Inc.
April 1996
M 123-56

Daniel Baker
For: Weyerhaeuser Co.
Jan. 1995
M119 - 54