

Douglas County Surveyor's Record of
Government Corners Renewed

21 T. S. 5 R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE. 97196

B. H. McGillicuddy
 July 1953
 Map and Explanatory notes filed in
 drawer 41, Envelope 182
 Witnesses - Marvin
 Francis Yoder
 Leo Martin
 Vern Olson
 deeds

Southeast corner to sec 36.
 Found 40" fir (burned stub) S 11° 30' W., 200 lks. Orig. S 14° W., old
 scribed post. BT's destroyed. *SEE ALSO their Book 5 PG 18 144*
 in. iron pipe twp. corner. Scribed BT's (new)
 24 in. fir-N.42°30'E., 26.4 ft. Mkd. Tp 21 S, R 4 W., S 31 B.T.
 28" fir-N. 9°30'W., 51.7 ft. Mkd. Tp 21 S, R 5 W., S 36 B.T.
 28 in. fir-S.21°10'W., 60.7 ft. Mkd. Tp 22 S, R 5 W., S 1 B.T.
 26 in. fir-S.25°30'E., 5.0 ft. Mkd. Tp 22 S, R 4 W., S 6 B.T.

11

FOUND O.K. - Oct. 1967 M.E.C. J.L.
 D.F. THIEL MKD B.T.S IN 1904
 SEE C.S. 64/48 PG 8

1/4 Sec. corner east side of sec 36.

Set 4" iron pipe
 No original B.T.s found.
 Set new B.T.s;
 24" fir N.10°25' W., 84.6 ft.
 22" fir N. 14°30' E., 37.9 ft.

12

N.E. CORNER Sec. 36 - Wit. Cor.

Witness Corner 20.46 ft. north of true corner to secs 25 and 36 on
 Tp line between Rs 4 and 5.
 Original 70" Cedar B.T. windfall.
 New 10" maple S66°E., 65.2 ft.
 Mkd. CS S36 Tp 20 S., R 5 W.
 Reference point-iron pin-East 45.6 ft.

13

South 1/4 sec. corner to sec. 36.

Original B.T.s
 10" fir (now 52") S52°E., 171 lks. scribed 1/4 s B.T.
 8" fir (now 44") N10°E., 100 lks. not examined.
 New B.T.
 15" fir S24°W., 79.6 ft.

14

Southwest sec. corner to sec. 36.

This corner described on 1952 map as:
 Post at junction of two fences.

Original bearing trees
 fir 30" N55°W., 16 lks. (defaced stump)
 fir 30" N12°E., 134 lks. (Burned windfall)
 fir 50" S70°E., 45 lks. (burned stump)
 fir 15" S28°W., 82 lks. (destroyed)

15

Found iron capped pipe 1953

Set new B.T.s
 14" fir N 65° E., 30.8 ft. Mkd. Tp 21 S, R 5 W., Sec 36 B.T.
 8" fir S 55° E., 16.5 ft. Mkd. Tp 22 S, R 5 W., Sec 1 B.T.

SEE SHANER'S SURVEY, 1972 - M 42-68

Old B. T.

36" fir stump N 55° W., 10.0 ft. Mkd. S 35 B.T.

1/4 sec. corner between secs. 35 and 36.

Set post and iron pipe. - *Fd. O.K. Dec. 1964 M.E.C. # 203 R.KIMBERLING M 79-69*
 Original B.T.s
 6" fir S 78° E., 48.18 ft. (fir stump) scribe visible.
 6" fir N-17° W. (destroyed)

16

New B.T.s

30" fir N-24° E., 46.8 ft. *IN GOOD CONDITN. DEC. 1964*
 32" fir S 54 1/2° W., 26.7 ft.

South 1/4 corner of sec. 35.

Placed 1 1/2" X 42" axle.

Marked new B.T.s

36 " fir S 85° W., 70.7 ft. Mkd. 1/4 S B.T.
 24 " fir stump N 60° W. 195 ft. Mkd. 1/4 S B.T.

17

No original B.T.s existing.