

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 21 S. T. S. R. 5 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

119

N. E. Township Corner to T. 21 S. R. 5 W.

Found -  $\frac{3}{4}$ " I. P., 19" long.

Broken Stone 20"x9"x6" mkd. "20 R5 S36", firmly set.

Orig. 8", now 23" R. Fir Stump N.50°W. 5.3 ft. Open & find **177**

"T R 5 BT", scribed reverse.

Orig. 8", now 26" R. Fir Stump N.75°E. 6.6 ft., no scribe found.

8", now 14" R. Fir Stump S.15°W. 5.9 ft., reverse scribe "B".

No trace S. E. BT. All BT's. badly rotted, measurements taken from face.

Set - Brass Cap at Cor. Mkd: Doug Co. Surv. Office, 1965

R5W	S 36	S 31	R4W
	S 1	S 6	

T20S

T21S

New BT's: 7" D. Fir S.46°W. 4.5 ft. Mkd: T21S R5W S1 DCS BT.

8" D. Fir N. 4°W. 7.0 ft. Mkd: T20S R5W S36 DCS BT.

7" D. Fir East 17.3 ft. Mkd: T20S R4W S31 DCSBT.

8" D. Fir S.21°E. 23.2 ft. Mkd: T21S R4W S 6 DCS BT.

$\frac{1}{4}$  Corner to Sections 17 and 20.

120

Found - Haines' "T" Iron, see Ren. #79.

Orig. 20", now 50" Fir N.30°E. 35.6 ft., shows "BT  $\frac{1}{4}$  S". Bark scribe appears to be very old. This BT. has another tree leaning into it.

Orig. 36", now 58" Fir S.64°E. 13.2 ft. found possible bark scribe. This BT. injured & bark is burned.

Due to the size & condition of Orig. BT's., we mark new BT's:

New BT's: 8" D. Fir S.80°E. 32.1 ft. Mkd:  $\frac{1}{4}$  S20 CS BT.

15" D. Fir N.28°W. 28.5 ft. Mkd:  $\frac{1}{4}$  S17 CS BT.

Note - This corner lies on N. side of ravine, course N. 70° W.

Section Corner to Sections 2 - 3 - 10 - 11.

121

Found - Haines' "T" Iron & BT's. as recorded in Ren. #42, as follows:

8", now 10" Madrone S.36°W. 25.5 ft., bark scribe almost completely disappeared.

10", now 14" D. Fir N.81°40'W. 8.9 ft., shows good scar. **148**

6", now 9" Chinq. S.73°E. 25.3 ft., bark scribe in very poor cond.

New BT's: (10" Madrone S.36°W. 25.5 ft. Mkd: T21S R5W S10 CS BT.

Rescribed - (9" Chinq. S.73°E. 25.3 ft. Mkd: T21S R5W S11 CS BT.

New BT - 8" Chinq. N. 53° E. 24.4 ft. Mkd: T21S R5W S2 CS BT.

$\frac{1}{4}$  Corner to Sections 10 and 15.

122

Found - Haines' "T" Iron & BT's. as recorded in Ren. #40, as follows:

18", now 20" D. Fir S.41°E. 65.5 ft., scar healed, alive & O. K.

12", now 14" D. Fir N.76°W. 19.7 ft., broken top & bark scribed.

New BT: 9" Hemlock N. 42° E. 49.6 ft. Mkd:  $\frac{1}{4}$  S10 CS BT.

Section Corner to Sections 5 - 6 - 7 - 8.

FD. OK 12/94 BY ROBERTS  
M 121-30

123

Found - "T" Iron, See Ren. #30 & #37, and scribed Post.

Orig. BT. gone, 20" Fir N.34°W. 42.9 ft.

48" Fir Stump, no scribing visible, S.72°W. 16.5 ft.

24" Fir, now 30" N.49°E. 33.7 ft., bark scribed, "BT".

New BT's: 12" Hemlock N. 23° E. 44.3 ft. scribed T21S R5W S5 CS BT.

18" Hemlock N.14°W. 65.1 ft. mkd: T21S R5W S6 CS BT.

14" D. Fir S.31°W. 72.3 ft. mkd: T21S R5W S7 CS BT.

Section Corner to Sections 4 - 5 - 8 - 9.

FD. OK 12/94 BY ROBERTS  
M 121-30

124

Found - Haines' "T" Iron at Corner, See Ren. #35.

Find Real old scribed stake at corner.

Orig. 40", now 60" Down Fir, face down, N.20°W. 33.0 ft.

N. E. & S. E. Orig. BT's. down & rotted.

Orig. 12", now 32" Fir S.34°W. 18.5 ft., shows axe marks, scribe marks on chip nailed to tree.

New BT's: 9" Hemlock bears N.16°E. 7.0 ft. scribed S4 T21S R4W CS BT.

7" Hemlock bears S.9°E. 13.9 ft. scribed S9 T21S R5W CS BT.

11" Hemlock bears N.3 5°E. 15.9 ft. scribed S5 T21S R5W CS BT.

Rescribe now 32" Fir S.34°W. 18.5 ft. scribed S8 T21S R5W CS BT.

Vernon "Ray" Tracy  
M. Darby - Mike Stone - T. Connell  
August and Sept. 1965  
C. S. File No. 54/14

Feb. 6/90  
M 110-31

RENEWED CORNER NO. 177