

Douglas County Surveyor's Record of
Government Corners Renewed

T. 21 S. T. S. R. 5 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Vernon "Ray"
Tracy
&
Crew
C. S. File
No. 54/14

Sec. Cor. to Secs. 7 & 18, R5W. & Secs. 12 & 13, R6W. #176
Found - Co. Surv. Brass Cap, See Ren. #69.
Orig. 24" Cedar N. 75° W. 23.1 ft.
Orig. 40" Fir Stump N. 47° E. 5.3 ft.
Orig. 34" Fir Stump S. 54° E. 9.4 ft.
Also BT's. as recorded Ren. #69.
New BT: 7" Chinquapin N. 78° E. 19.9 ft. Mkd: T21S R5W S7 CS BT.

131

RE-RENEWED SEE CORNER NO. #176
Fd. 7/89
D. PEEK
M108-55

MICROFILM TO HERE 10/67

Wilford N.
Haines
or: Churchill
& Woolley
Logging
M 35 - 12

Center $\frac{1}{4}$ Corner to Section 27.
Set - 5/8" Steel Rod, from which:
Scribed-24" D. Fir S. 83° W. 77.0 feet.
36" D. Fir N. 36° E. 22.5 feet.
(This tree looks like old BT.)

132

December 1967

Wilford N.
Haines
3/15/68
Map File
M 35 - 52

Section Corner to Sections 17 - 18 - 19 - 20.
Found - 24" Fir S. 17° W. 41 lks., down.
Stub for 36" Fir S. 55° E. 66 lks.
Stump Hole for 40" Fir N. 72° E., not 59° E.
Set - Iron Pipe with Brass Cap, from which:
Scribed New BT's: 16" Fir N. 3° W. 15.8 ft.
20" Fir N. 55° E. 29.1 ft.
18" Fir S. 46° E. 23.7 ft.
20" Fir S. 26° W. 4.2 ft.

133

March 5, 1968

SEPT 78

Vernon "Ray"
Tracy &
Crew
C. S. File
No.
54/14

Sec. Cor. to Secs. 18 & 19, T21-4W. and Secs. 13 & 24, T21-5W. #157
Found - 3/4" I.P. bent over & BT's., See Ren. #97.
27" D. Fir, alive, S. 32 1/2° E. 37.4 ft., scribe visible on pitched blaze.
12" D. Fir, alive, N. 69° W. 133.2 ft., scribe vis. on ptchd. & healing. blk.
Orig. BT. to S.E. alive.
Orig. N.W. BT. stump in place & shows scribe.
Set - Brass Cap at Cor. Mkd: County Surveyor's R T 21 S R
(Reset old I.P. Office 5 S 13 | S 18 4
alongside Brass Cap) 1968 W S 24 | S 19 W
New BT: 6" D. Fir N. 1 1/2° E. 34.1 ft. mkd: T21S R4W S18 CS BT.
This corner lies 1 ft. S. of E - W fence. No trees available to S.W.

134

12/31/68

Ronald W.
Van Domelen
Feb. 1969
M 37 - 72

Section Corner to Sections 29 - 30 - 31 - 32.
Found = 5"x8"x12" Stone mkd: "S +31" on top & "NEC" on N.E. face.
3/4" Iron rod on N.W. side of stone & rotted fence post
on N.E. side of stone.
No bearing objects present.
Marked for BT's: 6" Doug. Fir bears N. 24° E. 22.4 ft.) mkd: CS BT.
8" Doug. Fir bears N. 89° E. 9.0 Ft.)
(SEE Co. Ro. #65 FOR FEAR'S CORNER 1924)

135

136

$\frac{1}{4}$ Corner to Sections 30 and 31.
Found - S.S. Rock mkd: "CS $\frac{1}{4}$ S" set by B.B. Irving, See C.S. File 53/86. ^{FD. 15} _{76 38}
16", now 24" W. Oak, alive, N. 44 1/2° W. 19.8 ft., shows scar, we tag.
5", now 10" W. Oak, alive, S. 72 1/2° E. 37.6 ft., shows scar, we tag.
At a point for the Orig. BT, we find depression in ground, N. 67° E. 42.2 ft.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 21 S R 5 W
(Reset Rock Alongside) Office 1 S 30
1970 S 31 ^{FD. OK} _{4/11/80}
New BT's: 6" D. Fir N. 40° E. 17.3 ft. mkd: "1 S30 CS BT". #192 ^{S. FLAUC} _{DC 50}
10" D. Fir S. 46° E. 3.1 ft. mkd: "1 S31 CS BT". ^{CS. 6/16} _{FD. BT'S RE-MEASD}
Top of hill sloping south bears west 165 ft.
Haines' "T" Iron bears N. 52 1/2° W. 62.7 ft. Do not find Haines' BT's. in place.
(See Ren. #23) 7/28/70
Fd. 8/90
M110-52

Vernon "Ray" Tracy
Vincent Perron
C.S. File No. 54/14