

Douglas County Surveyor's Record of  
Government Corners Renewed

21 T. S. 5 R.W.W.M.

KONE-CHAPMAN CO., EUGENE, ORG. 21881

Russell T. Pinard  
For: Dale Black &  
Guistina Lumber Co.  
Dec. 1979  
M 79 - 13

1/4 Corner to Secs. 25 & 26

155

Set - 1" Galv. Iron Pipe with Brass Cap set 6" above ground stamped "1/4 Cor. S. 26 S. 25 1979" <sup>#158</sup>  
BT's - 12" Douglas Fir bears S. 88°W., 49.3 feet with double blaze and scribed "1/4 S26 BT".  
10" Douglas Fir bears N. 39 1/2°E., 5.5 feet with double blaze and scribed "1/4 S25 BT".

RE-RENEWED SEE CORNER NO. #158

156

Sec. Cor. to Secs. 30 & 31, T21-5W and Secs. 25 & 36, T22-5W Ren. #113  
Found - Haines "T" Iron protruding approx. 10" from ground and firmly set from renewal #22. T21-5  
Found no evidence of the original 6" B. Oak or the original 8" fir.

An original 18" fir now a 30" stump at record bearing and distance.

An original 45" fir now a 49" stump at record bearing and distance. Both stumps are cut low and we find no scribing or blazes.

Haines BT's from ren. #22 gone, we find some evidence of fire having burned area since then as noted in ren. #61.

A 12" cedar now a 17" cedar snag 25 feet tall bears S. 11°W., 85.5 feet. (Rec. distance 83.6 feet.) partially healed single blaze has scribing "T21S R6W S30" visible (Should be S36) with Haines washer at bottom of blaze.

A 16" now a 24" D. Fir bears N. 53°W., 52.3 feet (Rec. distance 54.3 feet) double blaze with no scribing visible.

A 12" now a 15" Maple bears S. 26°W., 77.9 ft. (Rec. distance 76.9 ft.) has partially healed double blaze with scribing "T21S R6W S36 BT" visible.

We do not find any evidence of 12" Cedar.

Set - Accepting the position of Haines "T" Iron as the original corner position because of agreement of bearing and distance calls to orig. BT's stumps and stream call 0.6 chains south of corner we reference out "T" iron.

Set a Douglas County Surveyor's Office brass cap on 1" x 30" iron pipe properly stamped and replace "T" iron on north edge of cap.

New BT's - An 11" D. Fir bears N. 45°E., 17.0 ft. scribed on double blaze "T21S R5W S30 CS BT".

We tag original BT stumps and all other found BT's. Cap and "T" iron are approx. 25 ft. east of a random north/south fenceline.

Stephen John Flause  
Terry Plouff  
Douglas County Surveyor's Office  
April 1980  
C.S. 61/6

Karen Reed  
Douglas County  
Surveyors Off.  
Deputy.  
Ed R. Scott, Witness  
Aug. 4, 1980  
C.S. 61/11

FD OK Les Roberts 7/96 M125-47 Section Corner for Secs. 13 and 24; and Secs. 18 & 19 of T.21-4 157

Found - 1968 County Brass cap properly marked, on a 1" x 3 ft. I.P. protruding 1.2 ft. above ground. Ren. #134

3/4" (I.D.) x 37" Iron pipe lying along side cap. Ren. #97

Cap lies .2 ft. North of a fence bearing S. 85°E., N. 85°W. An old fence is North of cap 1.0 ft.

BT's - No originals found.

A 14" Fir, now 25 in. with healed over blaze bears S. 48 1/2°E., 34.3 ft. dist. Ren. #5 of T.21-4

A 14" Fir, now a 33" x 4 ft. stump badly rotted scribe visible on open face "T 21" bears N. 71 3/4°W., 129.0 ft.

A 27" D. Fir, now a 28" diam. with pitched over blaze bears S. 32 1/2°E., 37.4 ft. Ren. #97

A 12" Fir, now a 16" with well healed double blaze bears N. 69°W., 133.2 ft.

A 6" D. Fir, now 12" with well healed double blaze bears N. 16°E., 34.1 ft. (Record N. 1 1/2°E., Ren. #134) PUT new tag on this tree.

Left cap in place. No new accessories. No available trees to the SW.

8/4/80

FND. OK 7/92  
BY FINDORFF, 1993-0016