

Douglas County Surveyor's Record of  
Government Corners Renewed

T 21 T. S. R 5 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Roderick Kimberling  
For: Dale Black and  
Guistina Lumber  
Jan. 1981  
M 79 - 69

158  
# 202  
1/4 Corner for Sections 26 and 25.  
Set - 1" Galv. I.P. with brass cap set 6" above ground marked  
T21S R5W 1/4 Cor S26 S25 1979.  
BT's - 12" D. Fir N.86°W., 29.4 ft. double blazed and scribed "1/4 S26  
BT"  
10" D. Fir, N.79 1/2°E., 24.0 ft. double blazed and scribed "1/4  
S25 BT"  
Note - This is an Amended Renewal from Survey Filed as M 79 - 13 and  
M 79 - 58. See Ren. #155

Gregory E. Quibell  
Deputy, Doug. County  
Surveyors Office  
Debbie Stewart, Witness  
Sept. 15, 1981  
C.S. 61 / 27

159  
1/4 corner for Sec's. 9 & 10.  
Found - Haines "T" Iron w/Brass Button, firmly set, protruding 9" out  
of the ground per survey M 7 - 64. Ren. # 45.  
Fnd BT's - 6-ft. high snag (orig. 20" Cedar) with visible 1/4 S10 BT  
and Haines Button bears N.61°E., 41.5-ft. Ren.# 45.  
30" Cedar stump per Ren.#45, lying on its side, badly decayed,  
with scribed 1/4S BT. Stump hole bears N.61°E., 12-ft.  
Stump (orig. 30" Fir)per Ren# 130 with visible 1/4 S10 CS BT,  
bears N.14°E., 39.8-ft.  
15" Hemlock (orig. 10" Fir) per Ren.#130 bears S.34°W.,  
37.7-ft. withwell healed double blaze.  
No trace of original BT's.  
Set - County Surveyors Office Brass Cap marked : County Surveyors  
Office T21S 1/4 S9 S10 R5W 1981.  
I replace the referenced out "T" Iron in ground at South edge of  
New BT's -9" Fir scribed 1/4 S9 CS BT in double blaze bears N.68°W., cap.  
24.0-ft.  
9" Fir scribed:1/4 S10 CS BT in double blaze bears N.13°E., 14-ft.  
12" Fir scribed 1/4 S10 CS BT in double blaze bears N.73°E.,  
31.5. 9/15/81

Wilford N. Haines  
For: E.O. Breier &  
Leroy Churchill  
May 1982  
M 92 - 30

160  
(West Northwest)  
Northwest corner DLC #37  
Found - 48" fir, orig., Bears S.38°E., 100 lks. Now very rotten stub with  
pitchy slab of old face.  
No trace of old 12" fir  
Set - 5/8" x 48" rebar with 1 1/8" brass disk inscribed Wilford N. Haines  
Drain, OR #239.  
New BT - 14" D. fir, bears S.42°20'E., 66.9 ft.

Gregory Quibell,  
Deputy, Doug. Co.  
Surveyors Office  
Randy Smith  
John Powell  
May 10, 1983  
C.S. 62/7

5/82  
Township corner, Secs. 36, 31, 1 and 6 of T.20-5 & 6;  
and T.21-5 & 6. 161  
Found - 1958 Douglas County brass cap lying on ground alongside road.  
Cap marked: Doug Co. Lane Co. Ren. #48

1958  
T 20 S  
R S 36 | S 31 R  
6 S 1 | S 6 5  
W T 21 S W

USBLM 1962

Surveyors Office

Also found hole which brass cap had been pulled out of.  
From hole BT's bear:  
Orig. 30" now 52" cedar with well healed blaze bears N.36°E., 69.3'  
Orig. 20" now 48" sawed fir stump with well healed blaze bears  
S.82°W., 58.7 ft.  
Orig. 20" now 48" sawed fir stump with no blaze visible bears  
N.87°W., 79.2 ft.  
14" fir, Ren. #48, now 18" with well healed blaze bears N.45°E.,  
32.3 ft.  
14" fir, Ren. #48, now 20" with well healed blaze bears  
S.78°E., 24.5 ft.  
20" cedar, Ren. #48, now 29" with well healed blaze bears  
S.75°W., 97.0 ft.  
24" madrone, Ren. #48, now 26" stump bears N.18°W., 104.9 ft.  
16" fir per resurvey, now 26" with well healed blaze bears  
N.6°E., 52.8 ft.