

# Douglas County Surveyor's Record of Government Corners Renewed

T 21      T. S.      R 5      R. W. W. M.

177

MOKE-CHAPMAN CO., EUGENE, ORE. 21891

C O N T. - -

Doug. Co. Surveyors Off.  
Randall Smith  
Stephen Flause  
Oct. 29. 1991  
C.S. File 64/21

Found - 12" now rotted D.Fir stump of indetermiabile size with illegible scribing visible, bears S.4°E., 150.4 ft. (Rec. S.2°E., 150.4 ft. in Ren. #140) Ren. No. 8  
8" now 26" dia. D. Fir with a fully healed single blaze bears S.3°E., 232.2 ft. (Rec. S.1°E., 232.2 ft.) Ren. No 140  
14" now 17" dia. Apple with a partially healed single blaze, bears S.57°W., 135.8 ft. (Rec. S.59°W., 135.8 ft.)  
Power Pole #7c-48 2, bears N.30°W., 104.2 ft. (Rec. N.28°W., 104.2 ft.)

New BT - 36" dia. measured 1 ft. above ground, English Walnut, not blazed or scribed, bears N.59½° W., 174.8 ft.  
10/29/91

Center 1/4 Corner for Section 18

178

Found - 2½" dia. brass cap on a 2" O.D. iron pipe protrudes 9" above ground. Ren. #167  
9" now 9" dia. Alder with bark scribing visible "C¼ S18 BT" A "W" nail is at base. Bears N.27½°E., 4.2 ft. (Rec. N.33½°E., 3.7 ft. dist. is to "W" nail)  
11" now 13" dia. D.Fir with a partially healed double blaze, scribing visible "¼ S18", A "W" nail is at base, bears N.32°W., 24.3 ft. (Rec. N.28½°W., 23.8 ft. dist. is to "W" nail). BT is pistol butted bearings and distances taken to plumb portion of trunk.

New BTs - 8" dia. Alder bark scribed " C ¼ S18 CS BT" bears S.14°E., 14.6'  
5" dia. D.Fir double blazed and scribed "X BT" bears S.32½°W., 6.6 ft.

Corner is approx. 30 ft. East of C/L of Upper Smith River Road.

11/19/91

179

Section Corner for 6 and 7; 1 and 12 of T21-6

Found - 2½" dia. DCSO brass cap 1¼" O.D. iron pipe protrudes 12" above ground. Ren. No. 59  
Wilford N. Haines T-Iron marked "239" is found Northwest of BC/IP 0.5 ft. protrudes 7" above ground. Ren. No. 28  
12" now rotted tipped out stump of indetermiabile size, no scribing visible, root hole bears N.27°W., 9.9 ft. (Orig. BT)  
28" now 30" dia. 4 ft. high D.Fir stump with a galv. steel cap on top, a partially healed single blaze facing Southwest, has scribe marks "BT" visible, bears S.87°E., 10.4 ft. Ren. No. 59  
22" now 22" dia. 3½ ft. high D.Fir stump with a galv. steel cap on top and a fully healed single blaze, bears S.48°E., 15.2 ft. Ren. No. 59  
14" now 20" dia. 3½ ft. high rotted D. Fir stump with an open blaze, scribing "S12 BT" visible, bears S.17°W., 19.9 ft. (Rec. S.17°W., 21.5 ft.) Ren. No. 59  
48" now 40" dia. 4½ ft. high D.Fir stump with a fully healed blaze and a galv. steel cap on top, bears S.14°E., 52.1 ft. 1962 BLM BT.  
62" now 60" dia. 3 ft. high D. Fir stump with a fully healed blaze and a galv. steel cap on top, bears S.45°W., 49.2 ft (Rec. S.45°W., 47.5 ft. dist. to face). 1962 BLM  
4" now 15" D.Fir with a fully healed single blaze, bears N.18°W., 31.0 ft. (1962 BLM)

New BTs - 9" dia. Hemlock double blazed and scribed "T21S R5W S6 CS BT" bears N.66°E., 8.0 ft.  
8" dia. D.Fir double blazed and scribed "T21S R6W S12 CS BT" bears S.19½°W., 8.0 ft.  
12" dia. Hemlock double blazed and scribed "T21S R5W S7 CS BT" bears S.47½°E., 29.6 ft.

FD OK - D. EDWARDS - 1/96 - M 125-40 11/19/91

N.E. Township Corner to T. 21 S. R. 5 W.

177A

Found - 2½" dia. DCSO brass cap dated 1965 on 1¼" O.D. iron pipe, protruding 14" above ground. See renewal no. 119.  
¾" I.D. iron pipe found along east edge of BC/IP (source unknown)  
A stone measuring 20" x 9" x 5" marked "R5WS36" is found loose along NE edge of BC/IP (source unknown)

Accessories Found -

8" now 14" dia. rotted D. Fir stump, no blazes or scribing visible, bears N.50°W., 5.3 ft. agrees w/record (orig. BT)

Office

Surveyors

County

Douglas

Randall Smith - Stephen Flause

November 19, 1991

C.S. File 64/21

Douglas County  
Surveyor's Office  
R.W. Smith  
S.J. Flause  
11/7/91  
C.S. 64/21