

Douglas County Surveyor's Record of
Government Corners Renewed

21 T. S. 5 R. W. W. M.

Southwest section corner of section 35.

Original B.T.s

30" fir (now stump) S.33° E. 26 lks. scribe visible.
14" fir N 54° W., 12 lks. windfall.

New B.T.s

14" white fir N 21° E., 31.3 ft. Tp 21S R5W., S35 B.T.
28" fir N 21° W., 9 ft. Tp 21S, R5W., S34 B.T.
46" fir S 22° W., 44.2 ft. Tp 22S, R5W., S3 B.T.
S.W. B.T. destroyed.

110

18

B.H. McGillicuddy
Presence of Roy Doty
and Howard Hopkins
Map filed Vol. 41
Env. 182
July, 1953 (F. 8-H-114)

~~Section corner to sections 6 & 7, T21S, R5W and 1 & 12, T21S, R6W.~~

~~Found the bearing tree, with scribe visible, marked SIBT, now a blowdown.
Reset the corner from this original B. T., setting a 3" x #1 stake for
corner stake. I marked the following trees for bearing trees:~~

~~A 14 inch Fir, bearing S.34°W., for 16.5 feet scribed S 12 BT.
A 22 inch Fir, bearing S.60°E., for 7.6 feet scribed S 7 BT.
A 28 inch Fir, bearing N.48°E., for 7.1 feet scribed S 6 BT.~~

19

~~VOLD - SEE RENEWAL NO. 59 - BY BYRON - 12/22/59~~

$\frac{1}{4}$ section corner to secs. 27 and 28.

Set a stake for the corner half way between the section corners.

Claude Kerr
January 15, 1955.
C. S. File 41/3324
Gilbert A. Gardner
Nov. 1, 1955.
C. S. File
No. 42/34.

$\frac{1}{4}$ corner to secs. 27 & 28.

Found 8" red cedar, N.55°W., 81.5 feet mkd. $\frac{1}{4}$ S B. T.
Set a 4" x 4" x 4" stake for corner half way between section corners.
Marked new B. T.:
An incense cedar, S.6°E., 92 feet.

90 20

$\frac{1}{4}$ section corner to secs. 22 and 27.

No evidence of old bearing trees found, logging having destroyed or removed them.

At one half the distance between section corners, set a 4"x4"x4" cedar stake for corner and marked:

20" red fir N.57°W., 29 feet.
10" alder S.59°W., 23 feet.

21

HAINES
SEE M 35-12 - FOUND CORNER - DEC. '67

Gilbert A. Gardner
Dec. 15, 1955.
Witness: Robert Barta.
C. S. File No. 42/34.

Southwest corner of Section 30.

Set Lot Marker. Found: Stump of 4.5 inch BT. S.52°E 12 lks.

Stump of 18 inch BT N.84°W 61 lks

Scribed: 14 inch Maple S.58°W. 14.5 feet.

6 inch Inc. Cedar N.69°W. 14.2 feet.

22

South $\frac{1}{4}$ Corner Section 30.

Set Lot Marker. 14 inch D.Fir N.47°30'E. 25.6 feet

5 inch D.Fir S.85°E 9.7 feet. Set by proportional measurement.

23

West $\frac{1}{4}$ Corner Section 30.

Set Lot Marker. Found 40 inch Fir Snag S.60°E 20 lks.

Scribed 5 inch Fir N.33°E 9.9 feet. Scribed 18 inch

Fir N.45°W 27.2 feet. - Fo. O.K. 6-1965-

24

North west corner of Section 30.

Set Lot Marker. Found 24 inch Fir S.15°W. 21 lks.

Scribed 44 inch Inc. Cedar N.35°E. 61.1 feet

25

North $\frac{1}{4}$ Corner Section 30.

Set Lot Marker by Proportional Measurement. - Fo. O.K. Dec. 1964 H.E.G.

Scribed 12 inch D.Fir N. 74°W. 2.7 feet

Scribed 18 inch D.Fir S.13°W. 5.3 feet

26

Center Corner Section 30.

Set Lot Marker. 30 inch Fir N.59°W. 99.2 feet.

10 inch Fir N.12°W. 120.8 feet.

27

for RENEWAL
Wilford N. Haines
For John Woolley
1955
C.S. File No. 42/77 M 12-32