

**Douglas County Surveyor's Record of
Government Corners Renewed**

21 T. S. 5 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21891

Donald Peel
For: Weyerhaeuser Co.
Feb. 1992
M114 - 60

190

Section Corner for 31, 32 & 5, 6 of T.22-5
Set - By proportionate measurement a 2" x 41" I.P with brass cap.
BTs - 22" Cedar, N.48°E., 24.4 ft. - scribed "T21S R5W S32 BT"
FD OK 26" Fir, S.61°E., 19.7 ft. - scribed "T22S R5W S5 BT"
M121-24 8" Fir, S.8°W., 38.4 ft. - scribed T22S R5W S6 BT"
11/10/94 11" Fir, N.86°W., 13.1 ft. - scribed T21S R5W S31 BT"

191

1/4 Sec. Cor of 31 & 36 of T21-6 - Cond. Report Only
Monuments FD. - 1961 DCSO 2 1/2" B.C.
Accessories FD. - 6" W.Oak, N.20°W. 19.1', healed face
8" W.Oak, S.62°E. 4.9', snag, scribing visible
24" W.Oak, N.79°W. 69.1', healed face, snag
30" W.Oak, (S.51°E. 106.9'), down, rotted, out of position

192

1/4 COR SEC. OF 30 & 31 - Cond. Report Only
Monuments FD. - 1970 DCSO 2 1/2" B.C.
Accessories FD. - 6" D.Fir, N.40°E 17.3', healed face
10" D.Fir, S.46°E 3.1', healed face
24" W.Oak, (N.44°W. 19.8'), down & rotted
10" W.Oak, S.66°E 38.3', dead, healed face

193

1/4 Cor Sec of 31 & 6 of T22-5
Monument Set - 5/8" x 30" rebar w/ YPC "LS 2603"
Accessories Set - 18" D.Fir, N.25°W. 7.7', blazed & scribed "S 1/4 SEC 31 BT".
12" D.Fir, N.46°E. 13.1'. blazed & scribed "S 1/4 SEC 31 BT".
9" D.Fir, S.53°E. 15.8', blazed & scribed "N 1/4 SEC 6 BT".
13" D.Fir, S.15°W. 32.7', blazed & scribed "N 1/4 SEC 6 BT".

194

C 1/4 Cor Sec. 32
Monument FD. - 1" I.P. w/ YPC "Weyer Co"
Accessories FD. - 38" D.Fir, N.65°W. 40.3', healed face
22" W.Fir, S.43°W. 57.3', open face
Monument SET - 5 1/2" steel fence post, 1' south

195

Sec. Cor. to 32, 33 & 4, 5 of T22-5
Monuments FD. - 1" OD I.P.
Monuments SET - 6" fence post 1" west
Accessories FD. - 50" D.Fir Stump, N.42°E. 12.2', healed face
17" D.Fir, N.52°W. 17.7', healed face
15" D.Fir Stump, (S37°W. 39.1'), missing
17" D.Fir Stump, (S.22°E. 31'), missing

196

1/4 Corner for Sections 5 & 8
Found - "T" iron set in Haines 1958 survey M7-66 See Ren. # 36
16" Fir stump, S.35°W., 25.4 ft. scar vis. 1958 BT.
24" Fir stump, N.25°E., 28.2 ft. scar vis. 1958 BT.
New BTs- 6" Fir, N.12°W., 39.9 ft. scribed/metal washer/painted red.
12" Alder, N.69°W., 11.2 ft. Bark scribed/metal washer/painted red.

197

Center 1/4 for Section 5
Set - 5/8" x 30" iron pin with yellow plastic cap.
BTs - 10" Fir, N.25°E., 25.4 ft. scribed, mtl. washer, painted red
12" Fir, S.50°E., 26.8 ft. scribed, mtl. washer, painted red
12" Fir, N.45°W., 36.6 ft. scribed, mtl. washer, painted red
16" Fir, S.59°W., 36.6 ft. scribed, mtl. washer, painted red

Harvey Christensen of N.W. Timberland Cons.
Nov. 10, 1994
M 121 - 21

Les Roberts
For: Seneca Jones Timber
Dec. 1994
M121 - 30