

Douglas County Surveyor's Record of  
Government Corners Renewed

21 T. S. 5 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21991

203

1/4 Corner for Sections 35 & 36. See renewal # 16.  
 Found - 3/4" iron pipe set by B.M. McGillicuddy in C.S. 41/182  
 - 12" Fir stump, S.78°E., 49.7 ft. (scribe vis.) 1855 BT  
 - 48" Fir snag, S.54°W., 26.7 ft. (scar vis.) 1953 BT  
 - 31" Fir Stump, N.24°E., 46.6 ft. (scribe vis.) 1953 BT  
 New BTs -  
 - 10" Fir, N.20°W., 18.5 ft. (scribed/painted red) 1994 Riley  
 BT)  
 - 12" Fir, S.07°W., 12.7 ft. (scribed/painted red) 1994 Riley  
 BT)  
 Found - 5/8" iron pin set by Gerald Riley in Nov. 1994. Pin bears  
 N.63°46'W., 7.64 ft. Also Bt's by Riley in Nov. 1994:  
 - 10" Fir, S.51°E., 16.4 ft. (scribe vis.), 1994 BT  
 - 10" Fir, North, 13.9 ft. (scribe vis.), 1994 BT  
 - 12" Fir, S.19°E., 16.9 ft. (scribe vis.), 1994 BT  
 - 12" Fir, N.31°E., 23.5 ft. (scribe vis.), 1994 BT

204

1/4 Corner for Sections 26 & 35.  
 -No original evidence found.-  
 Set - 5/8" x 30" iron pin w/yellow plastic cap marked "Roberts PLS  
 1039" by single proportionate measurement.  
 New BT's - 8" Maple, N.36°E., 49.1 ft. (scribed/painted red)  
 - 8" Fir, S.45°E., 11.9 ft. (scribed/painted red)  
 - 8" Fir, S.64°W., 22.7 ft. (scribed/painted red)  
 - 10" Fir, N.08°W., 35.0 ft. (scribed/painted red)

205

Center 1/4 for Section 26  
 Set - 5/8" x 30" iron pin w/yellow plastic cap "Roberts PLS 1039"  
 New BT's - 6" Fir, N.78°W., 65.3 ft. (scribed/painted)  
 - 12" Maple, N.76°E., 23.5 ft. (scribed/painted)  
 - 24" Spruce, N.40°W., 31.6 ft. (scribed/painted)  
 - 40" Fir, S.40°W., 47.9 ft. (scribed/painted)

206

1/4 Corner for Sections 33 & 34 See renewal #101  
 Found - U.S.B.L.M. Brass cap dated 1981  
 Broken Haines "T" iron, N.70°W., 10.3 ft.  
 record: N.62°W., 10.0 ft. - 1959 Haines  
 27" Oak, S.60°E., 63.3 ft. to set spike - closed face  
 record: S.60°E., 97 lks. - 1981 B.L.M.  
 18" Fir stump, N.24°W., 39.0 ft. - closed face  
 record: N.25½°W., 60 lks. - 1981 B.L.M.  
 New Accessories -  
 7" Fir, S.51°W., 47.0 ft. to "W" nail - scribed "¼ S33 BT"  
 22" Oak, S.88°E., 136.5 ft. to "W" nail - scribed "¼ S34 BT"  
 10" Fir, N.48°E., 237.3 ft. to "W" nail - scribed "¼ S34 BT"

207

1/4 Corner for Section 34; & Section 3 T.22-5 See renewal #165  
 Found - 1" I.P w/yellow cap inscribed "Weyer Co" - 1988; M107-26  
 72" Fir stump, N.7½°E., 47.5 ft. - axe work visible  
 record: N.8°E., 72 lks. 1855 G.L.O.  
 21" Fir, S.1°W., 42.8 ft. to "W" Nail - scribe visible  
 record: S.2°W., 42.8 ft. to "W" Nail - 1988 Weyerhaeuser  
 20" Fir, S.68½°W., 60.8 ft. to "W" Nail - scribe visible  
 record: S.70°W., 60.8 ft. to "W" Nail - 1988 Weyerhaeuser  
 20" Fir, N.39 3/4°W., 28.9 ft. to "W" Nail - scribe visible  
 record: N.38°W., 28.9 ft. to "W" Nail - 1988 Weyerhaeuser  
 New Accessories -  
 6 ft. metal fence post bears south 1 ft.

Les Roberts  
 For: Giustina Resources Inc.  
 Jan. 1996  
 M 123 - 29

Daniel Baker  
 For: Weyerhaeuser Co.  
 Feb. 1996  
 M124 - 12