

Douglas County Surveyor's Record of  
Government Corners Renewed

T 21 S. T. S. R 5 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

70

$\frac{1}{4}$  Corner to Sections 12 and 13.  
Found - Rotted Fir Stump, 66", N.46°E. 46.2 ft., barely visible old bark scribing  $\frac{1}{4}$ S BT".  
Stump Hole with fragments of rotted fir roots & part of stump S.63°W. 101.6 ft. Too far gone to find scribing or axe marks.  
Rotted Fir Stump S.38°W. 15.5 ft., scribing visible "BT" - not Orig. B.T., scribing looks like Thiel's.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T21S R5W  $\frac{1}{4}$ 

S12
S13

  
Office, 1962  
New B.T.'s: 8" D. Fir S.50 $\frac{1}{2}$ °W. 20.0 ft. Mkd:  $\frac{1}{4}$  S13 CS BT.  
19" D. Fir N.36°W. 29.8 ft. Mkd:  $\frac{1}{4}$  S12 CS BT.

*Fd. OK 6/90 M110-25*

71

Section Corner to Sections 11 - 12 - 13 - 14.  
Found - Rotted Fir Stump N.67°W. 45.5 ft., scribing visible on old face.  
Badly burned Fir Snag N.62°E. 33.0 ft., no scribing found.  
Fir Tree, now 60", S.18°E. 54.8 ft. Old injury on bark, No scribing found.  
Fir Stump, N. face burned away, S.10°W. 91.1 ft., no scribing fd.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T21S R5W 

S11	S12
S14	S13

  
Office, 1962  
Blaze & Rescribe: 60" Fir S.18°E. 57.0 ft. (to center) T21S R5W S13 CS BT.  
New BT's: 18" D. Fir N.48°E. 37.3 ft. Mkd: T21S R5W S12 CS BT.  
6" D. Fir N.45°W. 27.0 ft. Mkd: T21S R5W S11 CS BT.  
18" D. Fir S. 5°W. 58.2 ft. Mkd: T21S R5W S14 CS BT.  
Fence Corner - Fences East & North - bears East 24 feet.

*Fd OK 6/90 M110-25*

72

Section Corner to Sections 2 - 1 - 11 - 12.  
Found - Fir Snag, now 30", S.59°W. 66.0 ft. This tree had been opened previously & good scribing visible on small portion of old face.  
Fir Snag, now 80", S.65°E. 108 ft., shows good scar.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T21S R5W 

S 2	S 1
S11	S12

  
Office, 1962  
Found 4 trees scribed about 8 years ago:  
10" I. Cedar N.70°W. 52.0 ft. scribing visible in nearly clsd. scars.  
12" D. Fir N.83 $\frac{1}{2}$ °E. 38.7 ft., scar closed.  
12" D. Fir S.84 $\frac{1}{2}$ °E. 37.9 ft., scar closed.  
12" Maple, in clump, S.2 $\frac{1}{2}$ °W. 39.2 ft., scribing visible.  
Blaze & Scribe one new Tree:  
6" D. Fir S.23°W. 33.4 ft. Mkd: T21S R5W S11 CS BT.

*Fd 2 used 6/90 M110-25 M110-31*

73

$\frac{1}{4}$  Corner to Sections 1 and 12.  
Found - Scribed Wooden Stake at Corner.  
Old Fir Stump S. 4°E. 7.0 ft. found bark scribing  $\frac{1}{4}$  BT".  
Set - Brass Cap at Cor. Mkd: County Surveyor's T21S R5W  $\frac{1}{4}$ 

S 1
S12

  
Office, 1962  
New BT's: 10" D. Fir S.64 $\frac{1}{2}$ °W. 22.3 ft. Mkd:  $\frac{1}{4}$  S12 CS BT.  
12" D. Fir N.1°W. 21.4 ft. Mkd:  $\frac{1}{4}$  S1 CS BT.

RE-RENEWED. SEE CORNER NO. #171

74

$\frac{1}{4}$  Corner to Sections 24, T21-5W. & Sec. 19, T21-4W.  
No valid evidence found except for very old fenceline going due E. from computed corner. The fences going N'ly. & W'ly. are random. Valid bearing trees were non-existent.  
Set a 1" x 36" Steel Pipe 1 ft. below top of field, from which pipe a:  
6" D. Fir bears S.88°E. 31.8 ft., scribed  $\frac{1}{4}$ S BT".  
9" D. Fir bears S.34°W., 65.3 ft. scribed  $\frac{1}{4}$ S BT".  
(Also, the pipe is approximately 30 ft. West and 5 ft. North of corner of the field.  
FND. OK 7/92 BY FINDORFF 1993-0016

*Fd OK Les Roberts 7-96 M125-47*

Bruce A. Shaner  
For L. Kruse & Weyerhaeuser Co.  
Feb. 1962  
RM 2 - 17

75

Wilford N. Haines.  
Feb. 1962  
C.S. File No. 51/234

$\frac{1}{4}$  Corner to Sections 7 and 8.  
Found - T. Iron set in 1957. - Ren. #38  
All BT's. have been knocked down & burned. Found Alder N.17°W. 29.7 ft.  
New BT's: 26" Fir N. 1°W. 146.0 ft.  
16" Fir N.19°E. 185.8 ft.