

**Douglas County Surveyor's Record of
Government Corners Renewed**

T. 21 S. T. S. R. 5 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21661

$\frac{1}{4}$ Corner to Sections 6 and 5. *FD. OK 12/94 BY ROBERTS M 121-30* **76**
 Found - Old Fir Stump, 30", N. 89° E. 43.5 ft., opened previously.
 Good scribing "BT $\frac{1}{4}$ S" visible on old face.
 No trace found of N.W. BT.
 Set - At Corner Set Brass Cap Mkd: County Surveyor's Office, 1962
 T21S R5W $\frac{1}{4}$ S6/S5
 New BT's: 24" D. Fir N. 79° E. 40.7 ft. Mkd: $\frac{1}{4}$ S5 CS BT.
 5" D. Fir N. 66° W. 53.1 ft. Mkd: $\frac{1}{4}$ S6 CS BT.

$\frac{1}{4}$ Corner to Sections 18 and 17. **77**
 Found - Rock Mound at Corner, No markings found on any rock.
 Rotted Fir Snag S. 16° E. 19.8 ft. scribed " $\frac{1}{4}$ " visible
 on charred face, facing corner.
 The cedar BT. to the S.W. is down & impossible to tell
 just where it stood, however, it is approx. right dist.
 & bear., vis. - S. 48° W. 32.3 ft. Rolled Cedar over & found
 good scribing "BT" on old face. - was lying face down.
 Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962
 T21S R5W $\frac{1}{4}$ S18/S17
 New BT's: 20" D. Fir N. 22° W. 8.6 ft. Mkd: $\frac{1}{4}$ S18 CS BT.
 15" R. Cedar N. 82 $\frac{1}{2}$ ° E. 24.6 ft. Mkd: $\frac{1}{4}$ S17 CS BT.
 Corner lies in bottom of Canyon, approx. 10 ft. South of small
 stream flowing East.

Section Corner to Sections 20 - 21 - 28 - 29. **78**
 Found - Fir Stump, 48", at corner, scribing "S21 T21S" visible
 on N.E. face, previously opened. Good scar on N.W.
 face, not opened. Scribed "S29" visible on S.W. face,
 previously opened. No scar visible on S.E. face. Ring
 count shows scribing to have been made about the time of
 original survey. Remnants of old Maple Stump & Maple
 sprouts bear N. 63° W. 14.5 ft. No trace fd. of any other
 orig. BT's. I believe this stump to have been marked for
 corner by Orig. survey or though not called for in Orig.
 notes. Haines "T" Iron driven in center of stump.
 Did Not Set Brass Cap. - Stump 48" diam. & 6 ft. High is Corner.
 New BT's: 8" D. Fir N. 46° W. 22.1 ft. Mkd: T21S R5W S20 CS BT.
 8" I. Cedar S. 11° W. 27.4 ft. Mkd: T21S R5W S29 CS BT.
 10" D. Fir S. 53° E. 35.2 ft. Mkd: T21S R5W S28 CS BT.
 No trees avail. in N.E. Quad.

$\frac{1}{4}$ Corner to Sections 17 and 20. **79**
 Set 1" x 1" x 36" T. Iron from Orig. BT's. *120*

Section Corner to Sections 16 - 17 - 20 - 21 **80**
 Found - 12" Fir S. 32° W. 33 lks., now 42", rescribe on East Side.
 60" Fir S. 33° E. 10 lks., now 62", rescribe on West Side.
 Hole for 70" Fir N. 70° W. 38 lks. *127*
 Set - 1" x 1" x 36" T. Iron for Corner.

$\frac{1}{4}$ Corner to Sections 20 and 21. **81**
 Found - 22" Fir N. 73° W. 24 lks., now about 36", rescribed on S. Side.
 Set - 1" x 1" x 36" T. Iron & scribed:
 50" Fir N. 21° E. 16.5 ft.
 36" Fir N. 53° E. 44 lks., down.
COR. OK. JUNE 65 B.E.E.

$\frac{1}{4}$ Corner to Sections 20 and 29. **82**
 Found - Scribed Stake at fence corner. I was at this corner about
 1946. There was part of Cedar BT. S. 28° W. 24 lks. There
 is a Fir Stump N. 51° W. 69 lks. - *SEARCHED FOR; NOT FOUND*
 Set - 1" x 1" x 36" T. Iron by Stake. *SEPT. 1965. C.B. 54/14*

Center $\frac{1}{4}$ Corner to Section 20. **83**
 Set - 1" x 1" x 36" T. Iron & Scribed;
 12" Fir S. 59° E. 28.7 ft.
 18" Fir N. 63° W. 24.7 ft.

Milo E. Godfrey
 Vernon Tracy & Clete Putnam
 March 1962
 C. S. File No. 49/89

Wilford N. Haines
 For Woolley Logging Co.
 February 20, 1962
 Map File M 23 - 34