

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 21 S. T. S. R. 5 W. R. W. W. M.

FOKE-CHAPMAN CO., EUGENE, ORE. 21881

95

Mile E.  
Godfrey & Crew  
C. S. File  
No. 49/68

FD 3C  
G. Riley  
12/23  
M 117-77

Wit. Cor. to Secs. 25 & 36, T21-5W. & Sec. 30 & 31, T21-4W.  
Found - 1 1/2" Iron Pipe on bank of Pass Creek. See Ren. #13  
Ash N.55°E. 70.0 ft., scribing visible on open face. Tree dead.  
14" Maple S.66°E. 65.2 ft., shows scars. This tree across Pass Creek.  
Dead Ash Tree S.65°W., appears to be approx. correct dist., in  
thick blackberry jungle, distance not measured.  
Reblaze & Scribe - 14" Maple S.66°E. 65.2 ft. Mkd: T21S R4W WC S31 CS BT.  
New BT: 18" Alder S.6°W. 65.8 ft. Mkd: T21S R5W WC S36 CS BT.  
(Alder is across Creek from corner scribed 5 ft. high.  
No other trees available.

Oct. 26, 1964

C. S.  
File No. 49/  
68

1/4 Sec. Cor. to Sec. 36, T21-5W. & Sec. 31, T21-4W.  
Found 3/4" Iron Pipe, top approx. 12" above ground. - Ren. #12  
20" Fir Stump N.14 1/2°E. 37.9 ft. (to face), good scribing visible.  
24" Fir Stump N.10 1/2°W. 84.6 ft., good scribing visible.  
DID NOT SET BRASS CAP  
New BT's: 16" D. Fir S.87 1/2°W. 29.4 ft. Mkd: 1/4 S36 CS BT.  
5" W. Fir S.83 1/2°E. 18.0 ft. Mkd: 1/4 S31 CS BT.  
Note - An old fence corner, fences north & east, bears N.40°W. 8 feet.  
Corner is approx. 300 ft. south of power line.

Oct. 27, 1964

Sec. Cor. to Secs. 18 & 19, T21-4W. & Secs. 13 & 24, T21-5W.  
Found - 3/4" Iron Pipe at corner, (See Ren. No. 5. - T21-4W)  
23" Fir S.48 1/2°E. 34.3 ft., prev. opened, good scribing vis. on old fc.  
Fir Stump N.71 3/4°W. 129.0 ft., scribing visible, "T21".  
New BT's: 27" D. Fir S.32 1/2°E. 37.4 ft. Mkd: T21S R4W S19 CS BT.  
12" D. Fir N.69 1/2°W. 133.2 ft. Mkd: T21S R5W S13 CS BT.  
No trees near to S. W. or N. E.  
Corner is approx. 1 foot south of E. & W. Fence Line.

1/4 Corner Sec. 30, T21-4W. & Sec. 25, T21-5W.  
Found - Old Fir Stump S.37°W. 54.1 ft., cut open & fd. good scribing.  
38" old Fir Stump S.20°E. 16.5 ft., shows very good scar.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964  
T21S R5W 1/4 S25/S30 R4W  
New BT's: 11" D. Fir S.78°W. 6.8 ft. Mkd: 1/4 S25 CS BT.  
12" D. Fir S.54°E. 3.3 ft. Mkd: 1/4 S30 CS BT.  
Remnants of old fence lines extend N. & E. from Corner.

Section Corner to Sections 21 - 22 - 27 - 28.  
See Ren. No. 86 = The 9" Fir N.18°E. 98.4 ft. mkd. in 1962  
is now dead, but still standing.  
New BT: 7" Madrone N. 9° W. 147.2 ft. Mkd: T21S R5W S21 CS BT.

1/4 Corner to Sec. 33, T21-5W. & Sec. 4, T22-5W.  
(See Renewal #10, recorded T22S R5W)  
Found - 3/4" I. Pipe.  
Fir Stump N.47°W. 66.8 ft., bark scribing visible "33 21/5".  
16" White Oak S.51°W. 147.9 ft., shows very plain scar.  
No trace of Original Bearing Trees.  
20" Fir S.66°W. 30.0 ft., recently scribed, but no record.  
New BT's: 38" Doug. Fir N.28°W. 20.0 ft. Mkd: 1/4 S33 CS BT.  
(This Tree in Fence Line N. & S.)  
DID NOT SET BRASS CAP.

Dec. 1, 1964

Wit. Corner 1/4 Corner to Sections 33 and 34.  
Found - "T" Iron & Cap set by Haines N.62°W. 10.0 ft. (See Ren. #50)  
Stump of BT (12" Fir N.62°W. 49.7 ft.) scribing vis. (See Ren. #4)  
Old, rotted Fir Stump S.37°E. 107 ft. (Orig. BT) No marks visible.  
New BT's: 9" W. Oak N.30°W. 11.5 ft. Mkd: 1/4 S33 CS BT.  
20" D. Fir N.12°E. 41.2 ft. Mkd: 1/4 S34 CS BT.  
(New BT's. bear. & dist. from Wit. Cor. - Haines "TW Iron set  
for 1/4 Corner, other found stump dist. & bear. from 1/4 Corner).  
Nov. 27, 1964

Milo E. Godfrey, Deputy County Surveyor  
Wm. Stoffel & Mike Stone  
November 1964  
C. S. File No. 49/68

RE-RENEWED CORNER NO. #169  
RE-RENEWED CORNER NO. 134

RE-RENEWED CORNER NO. #179  
RE-RENEWED CORNER NO. #206

96

97

98

99

100

101