

Douglas County Surveyor's Record of
Government Corners Renewed

T. 21 S. T. S. R. 6 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

103

M. Godfrey &
Crew
Sept. 1962
C. S. File
No. 49/143

$\frac{1}{4}$ Section Corner to Sections 16 and 15.
Found - Fir, now 70", S.47°E. 19.8 ft., to face. Chop open & find
good scribing "S BT".
Stub of Fir Snag, 60", N.45°W. 44.9 ft., to face. Good bark
scribing, "S" on loose piece of bark lying at base of snag.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962
T21S R6W $\frac{1}{4}$ S16/S15
New BT's: 7" D.Fir N.28°E. 13.8 ft. Mkd: $\frac{1}{4}$ S15 CS BT.
10" D.Fir N.17°W. 11.4 ft. Mkd: $\frac{1}{4}$ S16 CS BT.

Wilford N.
Haines
For Woolley
Logging
Aug. 1962
M 24 - 21

$\frac{1}{4}$ Corner to Sections 19 and 20.
Found - Orig. 10" Fir, (now 52") S.52°W. 74 lks.
Set - 1" x 1" x 36" T. Iron
Scribed New Bearing Trees:
9" Fir S.7°E. 65.4 feet.
20" Fir S.75°W. 51.3 feet.

RE-RENEWED SEE CORNER NO. #134 104

105

Wilford N. Haines
For Woolley Logging Co.
Surveyed about 1955
Map filed May 1962
C. S. File No. 51/234

$\frac{1}{4}$ Corner to Sections 8 and 17.
Set T Iron and scribed 2 trees.
Milo Godfrey found this $\frac{1}{4}$ corner as renewed by Haines.
No trace of Original Corner found - Corner lies in
small, very steep draw, running North.
New BT's: 32" D.Fir S.51°E. 21.3 ft., blazed & scribed, scribing
"A" & "B" visible through pitch in still open scar.
Haines' Metal Disc fastened to this tree.
20" D.Fir N.54°W. 18.8 ft. scribing " $\frac{1}{4}$ S BT" visible in open scar.

Section Corner to Sections 8 - 9 - 16 - 17.
Found Northwest Bearing Tree and
Set "T" Iron.

RE-RENEWED SEE CORNER NO. 99 106

106

Section Corner to Sections 7 - 8 - 17 - 18
See Corner No. 9, 1957, renewal. Also Map File M 8 - 7.

107

WILFORD N. HAINES
for Woolley
Logging
1962
Map M 27 - 31

$\frac{1}{4}$ Corner to Sections 19 and 30.
No trace of Original Corner.
Set - 1" x 1" x 36" T. Iron & Scribed:
6" Fir S.77°E. 29.5 feet
30" Fir N.54°W. 13.0 feet.

108

Reference Point
only

$\frac{1}{4}$ Corner to Sections 30 and 29. ($\frac{1}{4}$ Cor. not found, not set)
Set - 1" x 1" x 36" T. Iron for Ref. Point. SEE M 27-31
Scribed - 24" R. Cedar N.77 $\frac{1}{2}$ °E. 25.5 feet.

108A

$\frac{1}{4}$ Corner to Sections 30 and 31.
Set - 1" x 1" x 36" T. Iron from which:
Scribed - 10" Hemlock N.68°E. 9.5 feet
8" Hemlock S.42°W. 4.5 feet.

109

Milo E. Godfrey
Wm. Stoffel - M. Stone
Mike Darby - J. Halterman
March 3, 1964
C. S. File No. 49/143

Sec. Cor. to Secs. 7 & 18, T21-6W. & Secs. 12 & 13, T21-7W.
Found - Haines' "T" Iron at Cor. in creek bed. See Ren. No. 14.
30" Fir N.45°E. 57.5 ft., Haines' bark scribing visible.
Tree standing and alive.
Orig. BT., 20" Fir N.20°W. 42.2 ft., uprooted & down, old blaze
prev. opened, scribing visible on old face, "BT S12 T21 R7W".
Haines' S.W. BT., 40" Fir S.45°W. 23.3 ft., also uprooted & down.
Set - Wit. Cor. 23 ft. East of Corner (Sec. Line runs right in Creek bed)
Brass Cap at Cor. Mkd: County Surveyor's T21S W C S12 | S 7
23 ft. W. to Corner. Office, 1964 R7W S13 | S18 R6W
Haines' N.E. BT. to Sec. Cor. - 30" Fir (bark scribed) bears N.20°E. 45.5 ft.,
from Wit. Corner, not rescribed.
New BT's: 9" Hemlock N.14°W. 75.0 ft. Mkd: T21S R7W S12 CS BT.
36" Red Cedar S.22°W. 125.6 ft. Mkd: T21S R7W S18 CS BT.

110

WIT. COR. IN
W. EDGE OF
LOGGING
ROAD.