

Douglas County Surveyor's Record of
Government Corners Renewed

T. 21 S. T. S. R. 6 W. R. W. W. M.

KOKS-CHAPMAN CO., EUGENE, ORE. 21881

118

1/4 Corner to Sections 33 and 32.
Found - Original Fir Bearing Tree & Stump Hole for Madrone BT.
Set - "T" Iron and scribed:
New BT's: 24" Fir S. 15° E. 51.0 ft.
20" Fir N. 28° W. 54.0 ft.

119

1/4 Corner to Sections 28 and 33.
Corner set by single proportional measurement.
Set - "T" Iron and scribed:
New BT's: 10" Madrone N. 69° W. 23.0 ft.
40" Fir S. 86° W. 13.6 ft.

120

Section Corner to Sections 27 - 28 - 3# - 33.
Found - 24" Fir, now stump, N. 82° E. 20 lks.
36" Fir, dead & down, S. 51° E. 56 lks.
Set - 1/2" Steel Road and scribed:
New BT's: 12" Fir S. 72° W. 234.8 ft.
28" Fir N. 86° W. 121.2 ft.
16" Fir N. 1° 43' E. 135.5 ft.
(Note - Corner is in ditch of Road)

121

1/4 Corner to Sections 33 and 34.
Found - 30" Fir Stump N. 55° E. 25 lks.
9" Fir Stump S. 36° W. 14 lks.
Set - "T" Iron and scribed:
New BT's: 16" W. Fir N. 9° W. 11.5 ft.
16" W. Fir N. 66° E. 99.6 ft.

122

1/4 Corner to Sections 27 and 28.
Found - 18", now 26" Fir N. 33° W. 45 lks.
Set - "T" Iron and scribed:
New BT's: 18" Fir N. 67° E. 38.0 ft.
20" Fir S. 40° W. 37.5 ft.

123

Sec. Corner to Sections 28 - 29 - 32 - 33.
Found - Co.Surv. Brass Cap at Corner, See Ren. #70.
Orig. now 24" Fir S. 31° E. 19.0 ft., scribe visible on open blaze. Only live Orig. BT.
Orig. N.W. BT., now dead. N.E. CS BT, now dead.
12" Fir S1 54° W, 22.1 ft., alive, blazes nearly healed.
New BT's: 6" D.Fir N. 70° W. 20.2 ft. mkd. T21S R6W S29 CS BT.
8" D.Fir S. 78° E. 19.8 ft. mkd. T21SR6W S33 CS BT.
8" D.Fir S. 25° E. 71.8 ft. mkd. T21S R6W S28 CS BT.
Note - This corner lies on top of ridge, course N.30°E. -S.30°W.

124

1/4 Corner to Sec. 36, T21S R7W & Sec. 31, T21S R6W.
Found: 40" D. Fir, (down), N.53°E., (Rec.N.53°W.) 28.4 ft.
Scribe visible.
6" Hemlock, now 10", N.31°W., 16.8 ft. Shows good scar.
Also: Haines T. Iron at 1/4 Corner. Ren. #42
New BT: 7" Hemlock, S.54°E., 24.0 ft. Scribed 1/4 S31 CS BT.

125

Section Conner to Secs. 25 & 36, T21S R7W & Secs. 30 & 31, T21S R6W.
Found: 36" D. Fir, N.72°W., 53.3 ft. Bark Scribed.
30" D. Fir, N.40°W., 60.6 ft. Bark Scribed.
6" Hemlock, S82°E., 41.7 ft.
Also: Haines T. Iron at Section corner. Ren. #41
New BT's: 10" D. Fir, S.19°W., 12.5 ft. Scribed T21S R7W S36 CS BT.
5" D. Fir, S.28°E., 37.2 ft. Scribed S31 CS BT.

Note - These corners searched for & orig. not found in 1961 by M.E.G., See C.S. File No. 49/143. V.R. Tracy returned to same corners in April, 1967, not sufficient evidence, See C.S. File No. 54/14. Signed: [Signature]

WOOLLEY Logging Co.
By Wilford N. Haines
March, 1967
Map File M 32 - 71

Vernon "Ray"
Tracy &
Grew
4/3/67
C.S. File
No. 54/14

John M. Powell
J. Heritage & D. Shultze
C.S. File 56/12
April 1972

RE-RENEWED CORNER NO.

FD OK 2/94 M118-39

MICROFILM TO HERE 10/67

Jan. 1972

4/12/72