

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 21 S. T.S. R. 6 W. R.W.W.M.

ROKE-CHAPMAN CO., EUGENE, ORE. 21881

Township Corner: Secs. 33 & 34, T21-6W. 128

Secs. 3 & 4, T22-6W.

Found - C.S. Brass Cap, properly marked in 1961, See Ren. #72.

in corner of new fence.

14" D. Fir N. 17° E. 10.7 ft., pitched over scribing.

10" Yew N. 48° W. 49.4 ft., scribing visible.

26" D. Fir (Grand Fir) S. 3° W. 37.3 ft., now snag.

15" G. Fir S. 72° W. 30.4 ft., scribe pitched over.

New BT: 8" Maple S. 48° E. 10.5 ft., bark scribed with  
knife, " S 3 CS BT".

RE-RENEWED SEE CORNER NO. #146

Powell, John

Wit:  
P. Earle  
V. Yates  
L. Lewis  
C.S. File  
56/38

9/14/73

Sec. Cor. Secs. 32 & 33; Secs. 4 & 5 of T22-6

Found - 1961 County Surveyors Brass cap properly mkd. with stone  
alongside. Ren. No. 64

8" now 12" D. Fir, bears N. 85 1/2° W., 14.2 ft. showing healed blaze.

12" now 16" D. Fir, bears N. 6 1/2° E., 23.4 ft. showing healed blaze.

SW BT is now down.

17" now 22" D. Fir bears S. 20° E., 20.6 ft. showing healed blaze.

New BT - 20" D. Fir, bears S. 54° W., 34.9 ft. scribed "T22S R6W S5 CS BT".

127

Gary Langlitz  
P. Earle  
C. Goodwin  
C.S. 56/43  
2/14/74

Sec. Corner to Sec. 15, 14, 22 and 23

128

Found: Haines "T" iron and stumps of all original BT's also  
two new BT's set by Haines in 1960 REN. #52

I proportion the corner and set a brass cap on 1 1/2"  
Iron pipe stamped T 21 S

Douglas Co. Surveyor 15/14  
1975 22/23

R 6 W

Set stone beside brass cap.

From which: A 60" stump bears N55°W., 70.1 ft.

A 54" stump bears N30°E., 55.4 ft.

A 40" stump bears S38°E., 74.3 ft.

A 36" stump with visible scribe bears S57°W., 37.4 ft.

A 24" D. Fir with visible scar bears N69°W., 18.7 ft.

A 12" D. Fir with visible scar bears S31°E., 5.9 ft.

A 16" D. Fir scribed "T 21 S R6W S22 CS BT" in a  
double blaze bears S27°W., 22.8 ft.

Haines "T" iron bears N4°E., 5.0 ft. Compass Delination 20°

\*NOTE: There are no trees near by in the N.E.  
quadrant.

Clell Goodwin  
Lenora Ladig  
C.S. 57/30  
6/23/75

1/4 Corner to Sec. 15 and 22

129

Found: Haines "T" Iron and 11" Hemlock bearing N. 76° W., 14.1 ft. No  
sign of S.E. bearing tree REN. # 52

A search of the immediate area uncovers no sign of the orig. corner

New: A 16" Hemlock scribed "T21 S R6W S22 CS BT" in a double blaze  
bears S43 1/2° W., 26.9 ft.

I do not monument Haines corner but leave "T" iron intact.

Compass Delination 20°

Clell Goodwin  
Lenora Ladig  
C.S. 57/30  
6/24/75