

Douglas County Surveyor's Record of
Government Corners Renewed

T 21

T. S.

R 6

R. W. W. M.

MOORE-CHAPMAN CO., EUGENE, ORE. 97101

137

CONT - - -

Gregory Quibell
Deputy, Doug. Co.
Surveyors Office
Randy Smith
John Powell
May 10, 1983
C.S. 62/7

20" now 48" sawed fir stump with no blaze visible bears
N.87°W., 79.2 ft.
14" fir per Ren. #29, now 18" with well healed blaze bears
N.45°E., 32.3 ft.
14" fir, Ren. #29, now 20" with well healed blaze bears S.78°E.,
24.5 ft.
20" cedar, Ren. #29, now 29" with well healed blaze bears S.75°W.,
97.0 ft.
24" madrone, Ren. #29, now 26" stump bears N. 18°W., 104.9 ft.
16" fir per resurvey, now 26" with well healed blaze bears
N.6°E., 52.8 ft.
16" fir per resurvey, now 24" with well healed blaze bears
S.59°E., 35.6 ft.
6" fir per resurvey, now 16" with well healed blaze bears
S.37°W., 99.7 ft.
6" fir per resurvey, now 10" with well healed blaze bears
N.22°W., 108.9 ft.

Set - Since found hole fits well, I RESET found brass cap in its original
hole and add the marks 1983 to cap.

5/10/83

138

Lloyd D. Smith
For: Oregon State
Dept. of Forestry
Nov. 3, 1983
M 95 - 49

1/4 corner for Sec. 34 only of T.20-6 (on north bdy. of Sec. 3)
Set - 1 1/2" x 36" alum. pipe with 3 3/4" alum. cap with magnetic
insert mkd. Oregon State Board of forestry, set 30" in ground.
BT's - 10" hemlock, N.42°W., 24.5 ft. with yellow metal location poster.
34" fir, N.77°W., 46.2 ft.
4" x 4" x 72" white painted cedar post, N.36°E., 1.8 ft.
Corner falls in center of old road, course N.73°E., from S.24°W.

139

Douglas County
Surveyors Office
Stephen J. Flause
R. W. Smith
August 10, 1987
C.S. 62/45

Section corner for Secs. 4, 5, 8 and 9.
Found - 1962 County brass cap, properly marked, on a 1 1/4" O.D. iron pipe
firmly set and protruding 4" above ground. Ren. #100
Haines T-iron buried under fallen log is bent slightly and
leaning southeast 0.3 ft. from brass cap position. (found in
Ren. #100, not otherwise unrecorded)
No evidence of original post and stone found.
An original fir, 8" dia. now a 47" D. fir DBH with a previously
opened now fully re-healed single blaze, N.64°E., 29.0 ft. dist.
An original fir, 10" dia. now a 48" D. fir DBH with a previously
rescribed now fully re-healed single blaze bears N.74°E.,
28.4 ft. distant. (as per record)
Possible evidence of an original fir, 48" dia. now a rotted fir,
snag 37" DBH, 25 ft. tall previously opned but with no evidence
of blaze or scribing bears N.21°W., 20.2 ft. distant. (record
N.20°W., 18.5 ft. dist.)
A 30" D. fir now 33" DBH, with a fully healed single blaze bears
N.80°E., 36.8 ft. (as per record.) Ren. No. 100
A 12" D. fir now 16" DBH, fallen rotting and out of position with
a partially healed but rotted double blaze containing some
evidence of partial but illegible scribing; indistinct roothole
of this tree is near record bearing and distance. Ren. No. 100
A 25" D. fir now 30" DBH with a fully healed single blaze bears
N.3 1/2°W., 62.9 ft. (Rec. N.1°W., 64.3 ft.; distance checks well
as a slope distance.) Ren. No. 100
An unrecorded alder with a 1979 BT tag possibly signed JEJ, is
20" DBH bark scribed T21S R6W S8 BT and bears S.30°E., 19.1 ft.
(BT tag records S.29°E., 29 lks.)

No new monument set or new BTs scribed.

Monument lies at foot of southerly slope of steep walled flat bottomed draw;
and is approx. 70 ft. south of seasonal creek in draw and is approx. 200 ft.
southeast from confluence of creek indraw and creek in main canyon coursing
southwest.

FO OK 10/31 M121-24 AFB

8/10/87