

Douglas County Surveyor's Record of
Government Corners Renewed

T 21 T. S. R 6 R. W. W. M.

ROKE-CHAPMAN CO., EUGENE, ORE. 21981

144

Section Corner for 1 and 12; 6 and 7 of T.21-5

Found - 2½" dia. DCSO brass cap 1½" O.D. iron pipe protrudes 12" above ground. Ren. #34

Wilford N. Haines T-Iron marked "239" is found Northwest of BC/IP 0.5 ft. protrudes 7" above ground. (See Ren. #28 of T21-5 12" now rotted tipped out stump of indeterminable size, no scribing visible, root hole bears N.27°W., 9.9 ft. (orig. BT) 28" now 30" dia. 4 ft. high D.Fir stump with a galv. steel cap on top, a partially healed single blaze facing Southwest, has scribe marks "BT" visible, bears S.87°E., 10.4 ft. Ren. No. 34 22" now 22" dia. 3½ ft. high D.Fir stump with a galv. steel cap on top and a fully healed single blaze, bears S.48°E., 15.2 ft. Ren. No. 34

14" now 20" dia. 3½ ft. high rotted D.Fir stump with an open blaze, scribing "S12 BT" visible, bears S.17°W., 19.9 ft. (Rec. S.17°W., 21.5 ft.

48" now 40" dia. 4½ ft. high D.Fir stump with a fully healed blaze and a galv. steel cap on top, bears S.14°E., 53.1 ft. (1962 BLM BT)

62" now 60" dia. 3 ft. high D.Fir stump with a fully healed blaze and a galv. steel cap on top, bears S.45°W., 49.2 ft. (Rec. S.45°W., 47.5 ft. dist. to face) (1962 BLM tree)

4" now 15" D.Fir with a fully healed single blaze, bears N.18°W., 31.0 ft. (1962 BLM)

New BTs - 9" dia. Hemlock double blazed and scribed "T21S R5W S6 CS BT" bears N.66°E., 8.0 ft.

8" dia. D.Fir double blazed and scribed "T21S R6W S12 CS BT" bears S.19½°W., 8.0 ft.

12" dia. Hemlock double blazed and scribed "T21S R5W S7 CS BT" bears S.47½°E., 29.6 ft.

FD OK - D. EDWARDS - 7/96 - M 125 - 40 11/19/91

Doug. Co. Surveyors
Office
Randall Smith
Stephen Flause
November 19, 1991
C.S. 64/21

Douglas County
Surveyors Office
Randall Smith
Stephen Flause
March 16, 1992
C.S. File 64/24

145

Tsp. Corner - SE Corner Section 36

Found - 1990 DCSO brass cap flush with ground. (Set in 1990)
Note: Renewal of this corner not recorded in 1990. DCSO BC/IP was set at position of stone. (Set by Haines in 1943 per Ren. No. 33) Stone was set along edge of BC/IP below ground.

40" now 46" dia. D.Fir with a fully healed blaze, bears S.21°E., 31.0 ft. (agrees w/rec) Ren. No. 33

8" now 22" dia. D.Fir with a fully healed double blaze, bears N.72°E., 56.0 ft. (agrees w/record) Ren. No. 33

10" now 14" dia. B.Oak with a fully healed double blaze, bears S.28°W., 18.8 ft. (agrees w/rec) Ren. No. 33

8" now 11" dia. W.Oak with a fully healed double blaze, bears N.2°W., 10.0 ft. (agrees w/record) Ren. No. 33

20" now 39" dia. W.Oak with a fully healed blaze, bears S.7½°E., 97.9 ft. (Rec. S.7½°E., 95.7 ft. dist. is a face measurement Orig. BT.

24" now 24" dia. 1½ ft. high rotted Oak stump with a rotted blaze, no scribing visible, bears S.13°W., 138.6 ft. (agrees with record) Orig. BT.

Randall W. Smith and Stephen J. Flause set DCSO 1990 BC/IP during control survey on file in Douglas County Surveyor's Office.

FD OK - M 121 - 21 - 11/10/94 - 3/16/92

146

Section Corner for 33, 34; and 4 & 3 of T.22-6

Found - A 2½" dia. DCSO brass cap on a 1½" O.D. iron pipe protruding 9" above ground. Ren. #72

14" now 10" dia. rotted 2½ ft. tall D.Fir stump, scribing visible "31 CS BT" bears N.17°E., 10.7 ft. (agrees with record) Ren. No. 72

26" now rotted Fir stump of indeterminable size, no blazes or scribing visible bears S.3°W., 37.3 ft. (agrees w/record.

15" now down and rotted D.Fir no blazes or scribing visible root hole bears S.72°W., 30.4 ft. (agrees w/rec) Ren. No. 72

10" now 12" dia. Yew with a partially healed double blaze, rotting scribing visible "T21S R6W S33" bears N.48°W., 49.4 ft. (agrees w/record) Ren. No. 72

8" now 13" dia. Maple with illegible bark scribing bears S.48°E., 10.5 ft. (agrees w/record) Ren. No. 126

Cont. Next Page -

Douglas County
Surveyors Office
Randall Smith
Stephen Flause
Feb. 24, 1992
C.S. File 64/24