

Douglas County Surveyor's Record of  
Government Corners Renewed

21

T. S.

06

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97101

Les Roberts  
for: Seneca Timber Co  
Feb. 10, 1994  
M118-39

Center 1/4 cor. sec. 34 156  
Set - 5/8" x 30" I.P with yellow plastic cap  
New BT's - 10" fir, S.21°W., 16.7' (scribed/washer/painted red)  
14" alder, N.16°E., 23.6' (scribed/washer/painted red)  
14" fir, S.50°E., 21.9' (scribed/washer/painted red)  
38" cedar, N.33°W., 8.6' (scribed/washer/painted red)

S.E. cor. sec. 34 157  
(Ren 416)  
Found - Haines "T" iron set in survey M8-30  
22" fir stump, S.72°W., 22.5' (scribe vis.), 1884 B.T.  
40" fir stump, S.02°E., 37.0' (Bark scribe), 1884 B.T.  
16" fir stump, N.83°E., 48.5' (scar vis.), 1957 B.T.  
20" fir stump, N.30°W., 36.8' (scar vis.), 1957 B.T.  
38" fir stump, S.83°W., 21.5' (bark scribe), 1957 B.T.  
40" fir stump, S.02°E., 37.0' (bark scribe), 1957 B.T.  
New BT's-  
8" oak, S.39°W., 47.3' (scribed/washer/painted red)  
12" oak, S.11°E., 66.4' (scribed/washer/painted red)

David Wellman  
For: Weyerhaeuser Co.  
July 1994  
M120 - 55

Section Corner for Sections 35 & 36 T.20-6; Section 2 T21-6. 158  
CONDITION REPORT ONLY; SEE RENEWAL # 32  
Found - 2 1/2" BLM Brass Cap dated 1984.  
36" Fir, S.46 1/2°E., 25.0 ft. - visible scribing  
rec. S.45°E., 38 lks. - 1872 GLO  
32" Fir, N.72 1/2°W., 21.0 ft. - closed face, rec. unknown  
18" Fir, N.68 1/2°W., 12.0 ft. - closed face  
19" Fir, N.52°E., 48.4 ft. - closed face  
rec. N.51°E., 75 lks. 1962 BLM.  
20" Fir, N.53 1/2°E., 45.0 ft. - closed face  
rec. N.54°E., 45.5 ft. - 1958 Douglas County  
26" Fir stump, N.61 1/2°E., 17.4 ft.  
rec. N.62°E., 26 lks. - 1984 BLM  
rec. N.65 3/4°E., 25 lks. - 1962 BLM  
rec. N.17 1/2°E., 25 lks. - 1872 GLO

Steven Ness  
For: Weyerhaeuser Co.  
M 121 - 24 A&B  
Oct. 14, 1994

West 1/4 corner sec. 4 159  
Monuments Found - 2 1/2" DCSO brass cap on 1 1/2" i.p. N.8°45'35"E., 4.77'  
from set monument. Fd. 5/8" i.r. w/ yellow  
plastic cap mkd. "Marx & Assoc." on the side  
of the DCSO mon.  
Accessories FD. - (from set mon.)  
10" W.Hemlock, N.44°06'W. 24.7', two healed faces  
24" D.Fir, S.19°44'W. 7.6', two healed faces  
6" D.Fir, N.36°24'E. 26.8', two small partially  
healed faces, some scribing visible.  
8" D.Fir, N.73°06'E. 37.6', two healed faces  
Monument set - 2"x36" i.p. with 2 1/2" brass cap cemented to the top  
New Accessories- 24" D.Fir, N.30°35'E. 29', to center, 28.95' to "W"  
nail, scribed "1/4 S4 BT".  
24" D.Fir, N.86°41'W. 32.8', to center, 31.97' to  
"W" nail scribed "1/4 S5 BT".

Center 1/4 corner sec. 4 160  
Monument set - 2 3/4" brass cap cemented on 2"x40" i.p.  
Accessories mkd.- 12" D.Fir, N.74°51'E. 43.3' to center,  
no distance measured to "W" nail,  
scribed "C 1/4 S4 BT".  
11" W.Hemlock, N.21°24'E. 34.3, to center,  
33.8' to "W" nail, scribed "C 1/4 S4 BT".  
18" D.Fir, N.34°46'W. 12.6' to center, 11.76  
to "W" nail, scribed "C 1/4 S4 BT".