

Douglas County Surveyor's Record of  
Government Corners Renewed

21

T. S.

06

R. W. W. M.

KONE-CHAPMAN CO., EUGENE, ORE. 97101

Harvey Christensen -  
For: Seneca Jones  
Timber Co.  
1/1999  
M 131-17

1/4 Cor. secs. 9 & 10 165  
Set - 5/8"x30" rebar w/YPC "NICILS 2603" 0.2 ft above ground.  
16" D.Fir, N.20°E., 17.8 ft., blazed & scribed: "¼ S10 BT"  
12" BLM Maple, N.43°W., 4.6 ft., blazed & scribed: "¼ S9 BT"  
9" D.Fir, S.20°W., 25.0 ft., blazed & scribed: "¼ S9 BT"  
5" D.Fir, S.30°E., 23.7 ft., blazed & scribed: "X BT"  
6 ft. steel post 2 ft. South.  
Note - Fd. possible orig. Cedar (snag) West about 30 ft. - badly burnt.

Center 1/4 Sec. 14 166  
Set - 5/8"x30" rebar w/YPC "NICILS 2603" 0.2 ft above ground.  
45" D.Fir, N.31°E., 36.3 ft., stump-put RR spike, in top center /w "X"  
15" D.Fir, S.2°E., 47.0 ft., blazed & scribed "C¼ S14 BT"  
8" D.Fir, S.55°W., 14.8 ft., blazed & scribed "C¼ S14 BT"  
11" D.Fir, N.60°W., 28.8 ft., blazed & scribed "C¼ S14 BT"  
6 ft. steel post 1 ft. North.

David Edwards  
For: Seneca Jones  
Timber Co.  
Jan. 2000 -  
CS File 65/29-1

Corner Secs. 15, 16, 21, & 22 167  
Found - 1"x1" T-iron (Ren #<sup>51</sup>~~95~~)  
19" Fir N.80°E., 19.0 ft.  
10" Fir S.47°E., 5.5 ft.  
22" Fir S.24°W., 24.5 ft.  
New BT - 24" Fir N.15°W., 27.15 ft. to nail set side  
center below stump height, scribed S16  
BT.

1/4 Cor. Secs. 21 & 22 168  
Found - 1"x1" T-iron (Ren #<sup>57</sup>~~103~~)  
16" Fir N.20°W., 19.7 ft.  
8" Cedar East 13.00 ft. to nail set side center  
below stump height, scribed S22 BT.

Rob Ward - For:  
Seneca Jones  
Timber Co. - June  
2001 - M138-26

1/4 Cor. Secs. 13 & 24 169  
Found - Haines ½" rebar, 48.96' West and 1.27' north  
of our calculated mid point. (REN #116)  
Set - 5/8"x36" rebar w/2½" alum. cap mkd: T21S R6W ¼  
S13/S24 2001 LS 1091  
17" D.Fir bears N.4½°E., 28.1' blazed &  
scribed "¼ S13 BT"  
16" D.Fir bears N.80¼°E., 22.2' blazed &  
scribed "¼ S13 BT"  
14" D.Fir bears S.31½°E., 30.4' blazed &  
scribed "¼ S24 BT"  
18" D.Fir bears S.48½°W., 26.1' blazed &  
scribed "¼ S24 BT"  
Note - BTs have red painted bands plus yellow BT tags

Center 1/4 Cor. Sec. 24 170  
Set - 5/8"x36" rebar w/2½" alum. cap mkd: T21S R6W C¼  
S24 2001 LS 1091  
17" D.Fir bears N.43¼°W., 39.8' blazed & scribed  
"C¼ S24 BT"  
13" Twin Madrone bears N.85¼°E., 13.2' blazed &  
scribed "C¼ S24 BT"  
13" D.Fir bears S.10°E., 36.2' blazed & scribed  
"C¼ S24 BT"  
8" D.Fir bears S.87¼°W., 21.8' blazed & scribed  
"C¼ S24 BT"  
Note - BTs have red painted bands plus yellow BT tags