

Douglas County Surveyor's Record of
Government Corners Renewed

T 21 T. S. R 6 R.W.W.M.

KORE-CHAPMAN CO., EUGENE, ORE. 97501

Douglas Co.
Surveyors Office
Randall W. Smith,
Deputy
Stephen J. Flauser
Sept 2001
C.S. File
66/29-4 thru 6

Cor. Secs. 25, 26, 35 & 36 174
Found - 1958 Haines "T" iron protrudes 7" above ground.
10" now 24" dia., D.Fir w/fully healed blaze
bears N.50°W., 3.3 ft. (Rec. N.50°W., 2.6
ft.) OBT - Haines washer & nail in bark.
8" now 19" dia., D.Fir with a previously opened
healed blaze bears N.35°E., 4.0 ft. (rec.
N.55°E., 4.0 ft.) OBT
36" now 38" dia., D.Fir snag, bark scribed "X
S35 T21S R6 B" (the letter B with an upside
down T) with Haines washer & nail in bark,
bears S.57½°W., 25.8 ft. (1958) (Ren. #20)
9" now 15" dia., I.Cedar with a fully healed
single blaze 3½ ft. above ground bears
S.19°E., 38.6 ft. (Rec. S.22°50'E. 52.6 ft)
(1958) We looked at rec. nothing found.
New - 14" dia., W.Fir double blazed & scribed "T21S
R6W S35 CS BT" bears S.36°W., 14.0 ft.
Compass decl. 17½°E. C.S. File 66/29-7 9/12/2001

1/4 Cor. Secs. 35 & 36 175
Found - 1958 Haines "T" iron, protrudes 8" out of
ground. (Ren. #19)
28" D.Fir now roothole bears S.33°W., 8.3 ft.
(1958)
10" now 17" dia., D.Fir w/fully healed single
blaze bears N.33°W., 6.7 ft. (1958)
We open 2 large D.Firs approx 40" dia., trees
looking for OBTs both have large growth
rings not old enough.
New - 12" dia., W.Fir double blazed & scribed "¼ S36
CS BT" bears N.77°E., 22.0 ft.
9" dia., D.Fir double blazed & scribed "¼ S35
CS BT" bears N.82°W., 42.6 ft.
5" dia., D.Fir double blazed & scribed "¼ S35
CS BT" bears S.55½°W., 38.0 ft.
Compass Decl. 17½°E. C.S. File 66/29-12

25 + 26

1/4 Cor. Secs. 35 & 36 176
Found - 1961 Haines "T" iron protrudes 5" above ground.
(Ren. #46)
18" now 20" dia., 10 ft. high Cedar snag with
unhealed double blaze, scribing visible "¼
S T" bears N.7°W., 38.0 ft. (1961)
12" now 10" dia. 1½ ft. high rotted D.Fir stump
bears N.87°W., 95.5 ft. (1961)
New - 9" dia., Pistol butt D.Fir double blazed &
scribed "¼ S25 CS BT" CS BT" bears S.14°E.,
2.0 ft. to center of blazed trunk.
10" dia., D.Fir double blazed & scribed "¼ S26
CS BT" bears N.16½°W., 15.6 ft.
10" dia., I.Cedar double blazed & scribed "¼ S25
CS BT" bears N.17°E., 6.3 ft.
Compass Decl. 17½°E. C.S. File 66/29-13