

Douglas County Surveyor's Record of
Government Corners Renewed

21 T. S. 6 R. W. W. M.

NOTE - CHAPMAN CO., EUGENE, ORE. 97189

20

Northeast Corner to Section 35.
Found: Original B. T.'s to N. E. and N. W.
Scribed: 9" I. Cedar S.22°50'E., 52.6 ft.
36" Fir, S.57°19'W., 25.8 ft.
Set 1"xl"x36" Iron 1 Rod with Brass Cap inscribed.

174

21

North 1/4 Corner to Section 35.
Scribed 16" Fir S.71°17'W., 78.1 ft.
Set: 1"xl"x36" Iron 1 Rod with Brass Cap.

22

Northwest Corner to Section 35.
Found: Original B.T.'s.
Set: 1"xl"x36" Iron 1 Rod with Brass Cap.

23

West 1/4 Corner to Section 35.
Scribed 10" Fir, N.46°30'W., 241.0 ft.
14" Fir, S.20°15'E., 143.7 ft.
Set 1"xl"x36" Iron 1 Rod with Brass Cap

24

S.W. Corner of D.L.C. No. 42.
Found: Oak B.T.(Snag) to South for S.W. Corner.
D.L.C. #42 Corner bears S.84°37'E., 1199.54 ft. from
S. W. Corner Section 35, T21S R6W.
Scribed: 12" W. Oak, S.87°15'W., 23.2 ft.
22" W. Oak N.89°30'E., 40.5 ft.
Set 1"xl"x36" Iron 1 Rod with Brass Cap.

SHOULD BE
SEC. 2, T22S R6W

25

S.E. Corner of D.L.C. No. 42.
Found: Oak B.T. (snag) to N.W. for S.E. Corner D.L.C. #42.
Corner bears S.88°21'E., 3803.31 ft. from S.W. Corner
Section 35, T21S, R6W.
Scribed: 12" Fir, N.17°E., 57.0 ft.
Set 1"xl"x36" Iron 1 Rod with Brass Cap.

26

1/4 Section Corner to Sections 17 & 20.
Found - Both Original BT's.
Orig. 38", now 48" Snag shows good bark scribing 1/4S" bears
N.45°W. 23.1 ft.
Orig. 48", now 60" low cut stump bears S.50°W. 31.0 ft.
Stump cut below any possible scribe marks.
Set Brass Cap at Corner Mkd: 1/4 S17 T21S R6W County Surveyor's
S20 Office, 1958.
Note: I also find 6"x 6"x 6" Stone at Corner, not marked, may be
corner stone.
New BT's: 6" R.Fir bears S.69°E. 23.7 ft. scribed 1/4 S20 CS BT.
14" Hemlock " N. 3°E. 37.0 ft. scribed 1/4 S17 CS BT.

27

Section Corner to Sections 19, 20, 29, & 30.
Found - Three Original BT's:
Orig. 24", now 48" down Fir shows good bark scribing "BT - - -"
bears S.69°E. 15.2 ft.
Orig. 16", now 24" Fir N.40°W. 21.1 ft., shows good scar, I
do not open.
Orig. 16", now 24" Fir Snag N.38°E. 21.1 ft., shows good scar,
I do not open.
All BT's. check for bearing & distance.
Set Brass Cap at Corner Mkd: S19|S20 T21S R6W County Surveyor's
S30|S29 Office, 1958.
New BT's: 7" Cedar bears S.27°W. 31.5 ft. scribed S30 T21S R6W CS BT.
8" Cedar bears S.19°E. 47.8 ft. scribed S29 T21S R6W CS BT.
16" Maple bears N.80°E. 23.0 ft. scribed S20 T21S R6W CS BT.
The Original N. W. BT. O. K.

Wilford N. Haines
For Harold Woolley
December, 1957
Filed Jan. 21, 1958
Map File M. 8 - 30

James W. Byron, Deputy Surveyor
M. Godfrey
S. Bilow
May 20, 1958
C. S. File No. 49/89