

Douglas County Surveyor's Record of  
Government Corners Renewed

21 T. S. 6 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

$\frac{1}{4}$  Section Corner to Sec. 24, T21S R6W. & Sec. 19, T21S R5W. 44  
as determined by old B.T.'s:  
Found - 10" Fir S.45°E. 10.6 ft. which is now 31" with  
visible scribes.  
6" Fir N.79°W. 10.6 ft. which is now a decayed  
stump with some scribe markings visible.  
Set  $\frac{1}{2}$ " x 36" Iron Pipe from which:  
21" Fir bears S.79°W. 20.7 ft. mkd.  $\frac{1}{4}$  S24 BT.  
6" W.Red Cedar bears S. 6°E. 34.4 ft. mkd.  $\frac{1}{4}$  S19 B.T.  
Recent scribes on 36" Fir mkd.  $\frac{1}{4}$  S B.T. bears N. 7°W. 28.0 ft.  
from which a scribed stake bears S.23°W. 8.5 ft. This stake  
and scribed tree do not refer to this actual corner.  
This corner is approximately 200 feet north of small creek and  
120 feet south of ridge top.

Burton W. Holt  
Wit: Ken Hebard  
Feb. 24, 1960  
C. S. File No. 51/71

$\frac{1}{4}$  Section Corner to Sections 24 and 25. 45  
Found - 36" Cedar BT.,  $\frac{1}{4}$ S plain.  
Scribed new BT. on same Tree.  
Set - 1" x 1" x 36" T. Iron.

$\frac{1}{4}$  Section Corner to Sections 25 and 26. 46  
Found - No Trace of Original Corner. 176  
Set - 1" x 1" x 36" T. Iron.  
Scribed: 12" Fir N.87°W. 95.5 ft.  
18" Cedar N. 7°W. 38.0 ft.

Wilford N. Haines  
For Woolley Logging Co.  
Drain, Oregon  
July 1961  
Map File M 20 - 76

$\frac{1}{4}$  Corner to Sections 36 and 25. 47  
Found - No Trace Original Corner.  
Set - 1" x 1" x 36" T. Iron. 173  
Scribed: 5" Oak N.75°E. 48.6 ft.  
22" Oak S.74°W. 47.6 ft.

Section Corner to Sections 25-36-30-31. 48  
Found - T. Iron & Maple S.58°W. 14.5 ft. <sup>#22 T21-5</sup>  
I. Cedar N.69°W. 14.2 ft. Both Trees have been  
damaged by Fire. #113  
Scribed - 12" Cedar S.11°W. 83.6 ft.  
16" Fir N.33°W. 54.3 ft.

N. W. Corner D. I. C. No. 38. 49  
Found - Both Oak BT.'s. down.  
Set - 1" x 1" x 36" T. Iron 171  
Scribed - 20" Fir S.67°W. 15.2 ft.

N. E. Corner D. I. C. No. 38. 50  
Found - Scribed Stake & 22" Oak S.72°W. 47 lks.  
36" Fir S.87°W. 60 lks. 172  
Drove 12" x 1" x 36" T. Iron by Stake.

Section Corner to Sections 15 - 16 - 21 - 22. 51  
Found - Scribe on Slab of old B.T.  
Set - 1" x 1" x 36" T. Iron & Scribed: 167  
10" Fir N.80°E. 19.0 ft.  
6" Fir S.47°E. 5.5 ft.  
6" Fir N.69°W. 4.7 ft.  
9" Fir S.24°W. 24.5 ft.

Wilford N. Haines  
For Woolley Logging  
November 1960  
Map File M 20 - 77

$\frac{1}{4}$  Corner to Sections 15 and 22. 52  
Found - No trace of Original Corner. #129  
Set - 1" x 1" x 36" T. Iron & Scribed:  
6" Hemlock N.73°W. 14.0 ft.  
12" Alder S.13°E. 10.8 ft.