

Douglas County Surveyor's Record of  
Government Corners Renewed

T 21 S T.S. R 6 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 31881

Milo E. Godfrey, Deputy County Surveyor  
Vernon Tracy and Clete Putnam  
October 9 November 1961  
C. S. File No. 49/143

Section Corner to Sections 20 - 21 - 28 - 29.

68

Found - Badly burned Fir Snag, N.66°E. 29.7 ft. Did not open.

Fir Snag, now 24", S.36°E. 13.9 ft., opened & found good reverse scribing "8".

Fir Snag, now 27", S.47°W. 16.5 ft., shows good scar. Did not open.

Fir Stump, now 36", N.85°W. 13.2 ft., shows scar, did not open.

Set - Brass Cap Mkd: County Surveyor's Office, 1961

T21S R6W	S20	S21
	S29	S28

New BT's: 51" D.Fir S.68°W. 50.0 ft. Mkd: T21S R6W S29 CS BT.

8" D.Fir S.71°E. 54.4 ft. Mkd: T21S R6W S28 CS BT.

11" Chinquapin N.51°E. 48.5 ft. Mkd: T21S R6W S21 CS BT.

7" D.Fir North 51.2 ft. Mkd: T21S R6W S20 CS BT.

Section Corner to Sections 30 and 29 and 31 and 32.

69

Found - Haines "T" Iron & Cap at Corner.

Cedar Tree, now 16", N.85°W. 27 ft. This tree has been opened several years ago & faint scribing "21S2 visible on rotting face. No trace of any other BT's. found.

Do not Set Brass Cap.

Reblaze & Scribe 16" Cedar N.85°W. 27 ft. Mkd: T21S R6W S30 CS BT.

New BT's: 11" Hemlock S.68°E. 27.6 ft. Mkd: T21S R6W S32 CS BT.

8" D.Fir N.65°E. 38.8 ft. Mkd: T21S R6W S29 CS BT.

44" D.Fir S.73°W. 33.5 ft. Mkd: T21S R6W S31 CS BT.

Section Corner to Sections 29 - 28 - 32 - 33.

70

Found - Fir Tree, now 22", S.31°E. 19.0 ft, insd. of 16.5 ft., chopped open and found good scribing "S".

Fir Stump, low cut, S.32°W. 12.5 ft., No scars or scribing fd.

Fir, now 32", N.31°W. 17.7 ft. instead of 15.2 ft, Has been partly chopped open, old scars obliterated. Did not open. Rescribe S29 CS BT.

No trace found of Orig. N. E. Bearing Tree.

Set - Brass Cap Mkd: County Surveyor's Office, 1961

T21S R6W	S29	S28
	S32	S33

New BT's: 8" D.Fir S.54½°W. 22.1 ft. Mkd: T21S R6W S32 CS BT.

15" D.Fir N.46½°E. 75.3 ft. Mkd: T21S R6W S28 CS BT.

½ Cor. Sec. 36, T21-6W. & Sec. 31, T21-5W.

71

Found - W.Oak, now 30", S.51°E. 106.9 ft. Cut open & found good scribing "S". Face in perfect condition.

W. Oak, now 24", N.80°W. 70.0 ft shows good scars. Didn't open.

Set - Brass Cap Mkd: County Surveyor's Office, 1961 T21S

N.&S. Fence bears West 1.4 ft. ¼ R6W S36/S31 R5W

New BT's: 6" W.Oak S.63°E. 4.8 ft. Mkd: ¼ S31 CSBT.

7" W.Oak N.49°W. 19.2 ft. Mkd: ¼ S36 CS BT.

Sec. Cor. to Secs. 33 & 34, T21-6 and Secs. 4 & 3, T22-6.

72

Found - ½" Iron Pipe & 28" W.Fir S.40°W. with rotten center & no scribing left visible, 29.0 ft. from Iron Pipe,

record 35.0 ft. W.Haines says he has seen scribing on tree.

No other trees found.

Set - Brass Cap Mkd: County Surveyor's Office, 1961

S33	S34	T21-6W.
S4	S3	T22S R6W

New BT's: 14" D.Fir N.17°E. 10.7 ft. Mkd: T21S R6W S34 CS BT.

10" Yew N.48°W. 49.4 ft. Mkd: T21S R6W S33 CS BT.

26" D.Fir S. 3°W. 37.3 ft. Mkd: T22S R6W S 3 CS BT.

15" D.Fir S.72°W. 30.4 ft. Mkd: T22S R6W S 4 CS BT.