

Douglas County Surveyor's Record of
Government Corners Renewed

T 21 S. T. S. R 6 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97401

Section Corner to Sections 11 - 12 - 13 - 14. 83

Found - Fir Tree, now 46", S.33°W. 9.2 ft. Traces of old bark scribing visible "S14 S BT".

Rotted Remnants of old Fir Stump S.25°E. 60.7 ft.

Rotted Remnants of old Fir Stump N.14°W. 66.7 ft.

Fir Stump, 48", N.31°E. 70.0 ft. Center of whole S.W. side rotted away, no marks visible.

Set - Brass Cap Mkd: County Surveyor's Office, 1961 T21S R6W S11 | S12
S14 | S13

New BT's: 18" Hemlock N.32°W. 17.6 ft. Mkd: T21S R6W S11 CS BT.

22" I. Cedar N.84½°E. 35.1 ft. Mkd: T21S R6W S12 CS BT.

12" Hemlock S.42°E. 73.3 ft. Mkd: T21S R6W S13 CS BT.

Rescribe 46" Fir S.33°W. 11.0 ft. (to center of tree)

Mkd: T21S R6W S14 CS BT -part of old bark scrbg destroyed.

E.D. OK 4/14/75 - WOOLLEY LOGGING - C.S. 57/21

¼ Corner to Sections 3 and 2. 84

Found - 44" Fir Stump S.55°E. 10.6 ft., opened scar & found fragment of scribing, bottom of scar is almost at top of stump.

36" Fir S.67°W. 9.2 ft. (to face), Shows good scar at bottom. Tree has been rescribed (in bark) "½ S BT". Blaze & rescribe this tree (one scar) "½ S 3 CS BT" Dist. to center of tree 10.5 ft. Bearing O.K.

Set - Brass Cap at Corner Mkd: County Surveyor's Office, 1961 T21S R6W ¼ S3/S2

New BT: 6" Hemlock N.52½°E. 24.7 ft. Mkd: ¼ S2 CS BT.

¼ Corner to Sections 11 and 14. 85

Found - 48" Fir, now 72", ~~was~~ uprooted & down, N.21°E. 28.4 ft.

Found very faint bark scribing "½ S", barely visible.

No trace of S.W. BT found.

Set - Brass Cap at Corner Mkd: County Surveyor's Office, 1961 T21S R6W ¼ S11 | S14

New BT's: 20" Fir S.55°E. 13.4 ft. Mkd: ¼ S14 CS BT. *132*

15" Forked Hemlock N.37°E. 46.0 ft. Mkd: ¼ S11 CS BT.

¼ Corner to Sections 23 and 26. 86

Found - 20" Fir N. 3°E. 31 lks., wood scribe.

36" Fir S.10°W. 56 lks., bark scribe

Set - 1" x 1" x 36" T. Iron & scribed:

9" I. Cedar S.42°W. 31.4 ft.

¼ Corner to Sections 26 and 27. 87

Found - Rock with X.

Stump of 60" Fir N.46°E. 9 lks.

Set - 1" x 1" x 36" T. Iron by Rock

Scribed - 10" R. Cedar N.15°E. 5.5 ft.

14" Hemlock N.68°W. 26.5 ft.

Section Corner to Sections 22 - 23 - 26 - 27. 88

Found - Rock 12" x 14" x 36" with X.

16" Fir S.46°E. 15 lks. now 28" diam.

Set - 1" x 1" x 36" T. Iron by Rock & Scribed:

7" R. Cedar N.53½°E. 11.4 ft.

12" Hemlock N.29°W. 50.6 ft.

¼ Corner to Sections 6 and 7. 89

Found - Rock marked ½ S.

Both old BT's are rotten Fir stubs, no scribe.

Set - 1" x 1" x 36" T. Iron by Rock & scribed:

18" D. Fir S. 6°W. 15.8 ft.

12" D. Fir N.30°W. 40.5 ft. (This face has forked top)

Milo E. Godfrey, Deputy County Surveyor
Vernon Tracy and Clete Putnam
December 1961
C. S. File No. 49/143

Wilford N. Haines
Woolley Logging
December 1961
C. S. File No. 51/222
Map File M 21 - 75 & M 21 - 74

RE-RENEWED SEE CORNER NO. 130
RE-RENEWED SEE CORNER NO. 132
RE-RENEWED SEE CORNER NO. 112
RE-RENEWED SEE CORNER NO. 148